

Grounding contact

Wallbushing connector universal port

Characteristics

- Amphenol Radsok® technology
- IP67 wall-side to wall-side
- Oneside assembly with standard tools
- easy to mate and unmate

Applications

- Factory automation
- Windpower
- Switch gears
- ...




Technical Data

General Information	Standard	Value
Number of contacts		1 Pin, 1 Radsok and 1 cable socket
Termination technique (pin into Radsok)		latching (Pin into Radsok)
Wire gauge		10 - 25 mm ² (Radsok)
Termination technique (wall-side)		Screwing
Wall thickness		1,5 - 6 mm
Dimension of wall cut-out		Ø31,5mm ± 0,2 burr-free
torque for assembly of WBC		6Nm ± 3%
Temperature range	IEC 60512 - 11 - 9 IEC 60512 - 11 - 10	- 40 °C to + 120 ° C

Mechanical and electrical characteristics

Protection class (wall-side to wall-side)	IEC 60 529	IP67
Protection class (Radsok)	IEC 60 529	IP20
Rated voltage	IEC 61140 cl. 6	≤ 60V DC / ≤ 25V AC
contact resistance	IEC 60512; test 1	≤ 0,2 mOhm

Derating-Curves according to IEC 60512-2; test 5b



Tools

Electrohydraulic crimping tool	TE0500 / Klauke part number : EK 12042L
Crimping dies for N02 060 6164 002	10mm ² - TE0500 - 081 16mm ² - TE0500 - 061
Crimping dies for N02 060 6165 002	25mm ² - TE0500 - 041

Part numbers



C360 10D001 002 2 - Wallbushing Connector Universal Port 6mm



C360 G01 141 E2 - Housing for 6mm Radsok, 10 - 16mm²

C360 G01 341 E2 - Housing for 6mm Radsok, 25mm²



N02 060 6164 002 - Radsok contact 10 - 16mm²

N02 060 6165 002 - Radsok contact 25mm²

General information

We reserve the right to change the design due to improvement in quality, development or production requirements. This data sheet must not be used in any form or manner without our prior approval in writing (Copyright, Law, Fair Trading Law, Civil Code). All technical data have been measured in a laboratory environment and can be different during practical usage of the product. Any product information is for descriptive usage only and not legally binding; particularly the information does not constitute or provide any legal guarantees ("Beschaffenheitsgarantie" or "Haltbarkeitsgarantie")