Search Results

Evaluate
- FAQ's
Design a Solution
- Part Drawings
- PDF-Tie Harness ..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'THMSC60F-C30'**

Your search criteria matched only one product, shown below

THMSC60F-C30

- Designed to be attached to the wire harness during assembly
- Cable ties can be installed by hand or with Panduit automatic cable tie tools
- Used with harness board standoff posts
- Available with or without corrugated tubing location tab
- Natural nylon material for indoor use
- Heat stabilized nylon material (30) for high temperature applications – indoor use

Part Number	THMSC60F-C30
RoHS Compliancy Status	Compliant
Part Description	Tie Harness Mount Heat Stabilized
Product Type	Cable Tie Mounts- Through Panel Hole
Material	Heat Stabilized Nylon 6.6
Color	Black
UL Recognized	E136577
CE Compliant	No
Environment	Indoor/High Temp
Flammability Rating	V-2
Mounting Method	Fir Tree Hole Mount
Panel Hole Diameter Range (In.)	0.244 – 0.268
Panel Hole Diameter Range (mm)	6.2 – 6.8
Sub Brand	Cable Tie Mount
Type	Tie Harness Mount
Min. Order UOM	PC
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy