

Features

- ◆ Smallest encapsulated 20W Converter!
Ultra compact size: 1.0" x 1.0" x 0.4"
- ◆ Shielded metal case with isolated baseplate
- ◆ Ultrawide 4:1 input voltage ranges
- ◆ Very high efficiency up to 90%
- ◆ Output voltage adjustable
- ◆ Remote On/Off control
- ◆ Operating temp. range -40°C to +75°C
and up to 85 °C with heat-sink
- ◆ I/O isolation voltage 1500 VDC
- ◆ Input filter meets EN 55022 class A
without external components
- ◆ No minimum load required
- ◆ Lead free design, RoHS compliant
- ◆ 3-year product warranty



The THN-20WI series is the latest generation of high performance dc-dc converter modules with highest power density. The product achieves 20W output power while it comes in a metal case with dimensions of only 1.0"x 1.0"x 0.4".

All models have an ultra wide 4:1 input voltage range and precisely regulated output voltages, even under no load conditions. Highest efficiency of up to 90% makes this product very reliable and applicable in temperature ranges of up to 75°C or 85°C with optional mounted heat sink. Together with low input current characteristics at minimal load and remote On/Off control these converters are the ideal solution for battery-operated systems. Typical applications are in mobile equipments, instrumentation, distributed power architectures in communication and industrial electronics and everywhere where space on the PCB is critical.

Models

Order code	Input voltage range	Output voltage	Output current max.	Efficiency typ.
THN 20-2410WI	9 – 36 VDC (24 VDC nominal)	3.3 VDC	4500 mA	86 %
THN 20-2411WI		5.0 VDC	4000 mA	89 %
THN 20-2412WI		12 VDC	1670 mA	89 %
THN 20-2413WI		15 VDC	1330 mA	89 %
THN 20-2415WI		24 VDC	833 mA	91 %
THN 20-2422WI		±12 VDC	±833 mA	89 %
THN 20-2423WI		±15 VDC	±667 mA	89 %
THN 20-2425WI		±24 VDC (48 VDC)*	±417 mA	91 %
THN 20-4810WI	18 – 75 VDC (48 VDC nominal)	3.3 VDC	4500 mA	86 %
THN 20-4811WI		5.0 VDC	4000 mA	89 %
THN 20-4812WI		12 VDC	1670 mA	89 %
THN 20-4813WI		15 VDC	1330 mA	90 %
THN 20-4815WI		24 VDC	833 mA	91 %
THN 20-4822WI		±12 VDC	±833 mA	89 %
THN 20-4823WI		±15 VDC	±667 mA	89 %
THN 20-4825WI		±24 VDC (48 VDC)*	±417 mA	91 %

* The outputs can also be used in serial circuit for single 48 VDC operation.

Input Specifications

Input current at no load (at nominal input voltage)	– 24 Vin	3.3, 5.0, 24 VDC models: 12, 15, ± 12 , ± 15 VDC models: ± 24 VDC models:	10 mA typ. 6 mA typ. 12 mA typ.
	– 48 Vin	3.3, 5.0, ± 24 VDC models: 24 VDC models: all other models:	10 mA typ. 8 mA typ. 4 mA typ.
Start-up voltage / under voltage shut down		24 Vin models: 48 Vin models:	9 VDC / 8 VDC 18 VDC / 16 VDC
Surge voltage (1 sec. max.)		24 Vin models: 48 Vin models:	50 V max. 100 V max.
Reflected input ripple current			30 mAp-p typ.
Conducted noise (input)			EN 55022 class A, FCC part 15, level A without external components
ESD (electrostatic discharge)			EN 61000-4-2, air ± 8 kV, contact ± 6 kV, perf. criteria A
Radiated immunity			EN 61000-4-3, 10 V/m, perf. criteria A
Fast transient / Surge			EN 61000-4-4, ± 2 kV, perf. criteria A EN 61000-4-5, ± 2 kV perf. criteria A With external input capacitor e.g. Nippon chemi-con KY 200 μ F, 100 V, ESR 48 mOhm
Conducted immunity			EN 61000-4-6, 10 Vrms, perf. criteria A

Output Specifications

Voltage set accuracy			± 1 %
Output voltage adj. range		24 Vin models: all other models:	–10 / +20 % ± 10 % only for single output models see application note
Regulation	– Input variation ($V_{min} - V_{max}$)	single output models: dual output models:	0.2 % max. 0.5 % max.
	– Load variation (0 – 100 %)	single output models: dual output models balanced load: dual output models unbalanced load (25% /100%):	0.2 % max. 1.0 % max. 5.0 % max.
	Minimum load		not required
	Ripple and noise (20 MHz bandwidth)		single output models: 75 mVp-p typ. with external capacitor dual output models: 100 mVp-p typ. with external capacitor see application note
Temperature coefficient			± 0.02 %/K
Output current limitation			typ. 150 % of $I_{out max.}$, Hiccup
Short circuit protection			continuous, automatic recovery
Over voltage protection	3.3 VDC models:		3.7 – 5.4 Vout
	5 VDC models:		5.6 – 7.0 Vout
	12 VDC models:		13.5 – 19.6 Vout
	15 VDC models:		16.8 – 20.5 Vout
	24 VDC models:		29.1 – 32.5 Vout
Start up time (nominal Vin and constant resistive load)			30 ms typ. (for power on and remote on)
Transient response setting time			250 μ s typ. (25% load step change)
Max. capacitive load	3.3 VDC models:		7'000 μ F
	5 VDC models:		5'000 μ F
	12 VDC models:		850 μ F
	15 VDC models:		700 μ F
	24 VDC models:		220 μ F
	± 12 VDC models:		500 μ F (each output)
	± 15 VDC models:		350 μ F (each output)
		± 24 VDC models:	100 μ F

General Specifications


Temperature ranges	– Operating without heat sink – Operating with heat sink – Case temperature – Storage	–40°C to +75°C (with derating) –40°C to +85°C (with derating) +105°C max. –55°C to +125°C
Power derating	– Operating without heat sink – Operating with heat sink	2.0 %/K above 60°C 2.0 %/K above 70°C
Thermal impedance	– Natural convection – Natural convection with heat sink	17.6°C/W 14.8°C/W
Humidity (non condensing)		5 % to 95 % rel H max.
Reliability, calculated MTBF (MIL-HDBK-217F, at +25°C, ground benign)		>1.4 Mio. h
Isolation voltage (60sec.)	– Input/Output	1'500 VDC
Isolation capacitance	– Input/Output	1000 pF typ.
Isolation resistance	– Input/Output (500 VDC)	>1'000 MOhm
Remote On/Off	– On: – Off: – Off idle current:	3.0 ... 15 VDC or open circuit 0 ... 1.2 VDC or short circuit pin 6 and pin 2 1.5 mA
Switching frequency (fixed)		330 kHz typ. (pulse width modulation PWM)
Vibration and thermal shock		EN 61373, MIL-STD-810F
Safety standards		UL/cUL 60950-1, IEC/EN 60950-1
Safety approvals	– UL/cUL	www.ul.com -> certifications -> File e188913

Physical Specifications

Casing material		nickel coated copper
Baseplate		non conductive FR4
Potting material		silicone (UL 94V-0 rated)
Weight		15 g (0.53oz)
Soldering temperature		max. 265°C / 10 sec.
Environmental compliance	– Reach – RoHS	www.tracopower.com/overview/thn20wi RoHS directive 2011/65/EU

Application note: www.tracopower.com/products/thn20wi-application.pdf

Outline Dimensions



Pin-Out

Pin	Single	Dual
1	+Vin (Vcc)	+Vin (Vcc)
2	-Vin (GND)	-Vin (GND)
3	+ Vout	+ Vout
4	Trim	Common
5	-Vout	-Vout
6	Remote On/Off	

Dimensions in [mm], () = Inch
 Pin diameter $\varnothing$ 1.0 (0.04)
 Pin pitch tolerances: ± 0.25 (± 0.01)
 Tolerances: ± 0.5 (± 0.02)

Heat-Sink (Option)

Order code: THN-HS1

(cont.: heat-sink, thermal pad, 2 clamps)

Material: Aluminum

Finish: Anodic treatment (black)




Weight: 8 g (0.28oz) without converter

Thermal impedance after assembling: 14.8 K/W



Note:

The product label on converter has to be removed before mounting the heat-sink.
 For volume orders converters will be supplied with heat-sink already mounted. Please contact factory for quotation.
 Separate heat-sinks are only available for prototypes and small quantity orders.



Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at www.tracopower.com