

Features

- ◆ High power density encased 65 W power supply
- ◆ 2 x MOPP Medical safety according to AAMI/ANSI ES 60601-1:2005(R) and IEC/EN 60601-1 3rd edition
- ◆ Ready to meet ErP directive, < 0.3 W no load power consumption
- ◆ Highest efficiency across full load range
- ◆ Protection class II prepared
- ◆ Operating up to 5000m altitude
- ◆ Adjustable output voltage
- ◆ 3-year product warranty



The TPP 65 Series of 65 Watt AC/DC power supplies feature a reinforced double I/O isolation system according to latest medical safety standards (60601-3 3rd edition, 2 x MOPP).

The excellent efficiency of up to 93.5% allows a high power density for the standard 2.44" x 3.0" packaging format. The full load operating temperature range is -40°C to +60°C while it goes up to 85°C with 50% load derating (for single output models). They come with an active power factor correction and the EMC characteristic is dedicated for applications in industrial and domestic fields.

High reliability is provided by use of industrial quality grade components and an excellent thermal management. It makes the products an ideal solution for medical devices and for demanding safety and space critical applications.

Models

Order code	Output voltage (adjustment range)	Output current max.	Efficiency max.
TPP 65-105	5 VDC (4.5 - 5.5)	10.0 A	90 %
TPP 65-112	12 VDC (10.8 - 13.2)	5.42 A	92.5 %
TPP 65-115	15 VDC (13.5 - 16.5)	4.34 A	93.5 %
TPP 65-124	24 VDC (21.6 - 26.4)	2.71 A	93.5%
TPP 65-221	+12 VDC / +5 VDC (±10%)	5.42 A / 8 A	90 %
TPP 65-231	+15 VDC / +5 VDC (±10%)	4.34 A / 8 A	90.5 %
TPP 65-251	+24 VDC / +5 VDC (±10%)	2.71 A / 8 A	89 %
TPP 65-321M2	+12 VDC / +5 VDC / -12 VDC (±10%)	5.42 A / 8 A / 0.6 A	89 %
TPP 65-331M3	+15 VDC / +5 VDC / -15 VDC (±10%)	4.34 A / 8 A / 0.6 A	89.5 %
TPP 65-3512	+24 VDC / +5 VDC / +12 VDC (±10%)	2.71 A / 8 A / 0.6 A	87 %

Input Specifications

Input voltage range	– AC range (universal input) – DC range	85 – 264 VAC 120 – 370 VDC
Input frequency		47 – 63 Hz
Input current at full load	– at 115 VAC / 230 VAC	1.6 A max. / 0.9 A max.
Input protection		T3.15 A/250 VAC (internal fuse in both line & neutral)
Input inrush current	– at 230 VAC	60A
Zero load power consumption		< 0.15 W (acc. ErP directive)
Harmonic limits		EN 61000-3-2, Class A

Output Specifications

Voltage set accuracy		single output: $\pm 1\%$ multi output: $\pm 1\%$ Vout1 $\pm 2\%$ Vout2, Vout3
Regulation - single output	– Input variation – Load variation (0 - 100%)	5 VDC model: 0.2% max. 0.7% max. other models: 0.5% max.
Regulation - multi output	– Input variation – Load variation (0 - 100%) – cross regulation (25% / 100%)	0.2% max. 0.5% max. Vout1: 0.5% max. Vout2: 1.2% max. Vout3: 0.7% max. 1.5% max.
Minimum load		single and dual output: not required triple output: tba.
Temperature coefficient		0.02%/K
Hold-up time	– Vin = 115 VAC	16 ms typ.
Start-up time		<1s
Rise time		20 ms typ.
Output voltage adjustment		$\pm 10\%$
Ripple and noise - single output (20Mhz Bandwidth)		5 VDC model: 75 mVp-p typ. with cap. 10 μ F/25V 1206 X7R MLCC 12-24 VDC models: 75 mVp-p typ. with cap. 1 μ F/50V 1206 X7R MLCC
Ripple and noise - multi output (20Mhz Bandwidth)	– Vout 1 – Vout 2 – Vout 3	12 VDC model: 120 mVp-p typ. with cap. 1 μ F/50V 1206 X7R MLCC 15 VDC model: 150 mVp-p typ. with cap. 1 μ F/50V 1206 X7R MLCC 24 VDC model: 240 mVp-p typ. with cap. 1 μ F/50V 1206 X7R MLCC all models: 100 mVp-p typ. with cap. 10 μ F/25V 1206 X7R MLCC 12 VDC model: 120 mVp-p typ. with cap. 10 μ F/25V 1206 X7R MLCC 15 VDC model: 150 mVp-p typ. with cap. 10 μ F/25V 1206 X7R MLCC
Overvoltage protection		125 – 140% of nominal Vout
Overload protection by current limit		single output: at 145% Iout max. multi output: tba.
Short circuit protection		continuous (automatic recovery)
Transient response (25% load step change)	– Peak deviation – Recovery time	3% of Vout 600 μ s

General Specifications


Operating temperature		–40°C to +85°C with derating, see graph on p.3
Output power derating	– Temperature	single output: 2 %/K above +60°C at 230 VAC 2 %/K above +55°C at 115 VAC multi output: 1.67 %/K above +55°C at 230 VAC 1.71 %/K above +50°C at 115 VAC
	– Low input voltage	1.33 %/V below 100 VAC

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.


General Specifications (continued)

Storage temperature	-40°C to +85°C	
Humidity (non condensing)	5 – 95 % rel. H max.	
Altitude during operation	5000 m	
Switching frequency - single output (at 230 VAC)	5 VDC model:	60 kHz typ. (pulse width modulation)
	other models:	120 kHz typ. (pulse width modulation)
Switching frequency - multi output (at 230 VAC)	5 VDC model:	60 kHz typ. (pulse width modulation)
- Vout 1	other models:	115 kHz typ. (pulse width modulation)
- Vout 2		750 kHz typ. (pulse width modulation)
- Vout 3		510 kHz typ. (pulse width modulation)
Isolation voltage 1min (2 x MOPP insulation)		
- Input / Output	4000 VAC	
- Input / Case	2500 VAC	
Leakage current (at 264 VAC/60Hz)	75 µA max.	
Isolation resistance (at 500 VDC)	100 Mohm min.	
Reliability	- calculated MTBF at +25°C acc. to IEC 61709	1'494'000 h for single output models 1'059'000 h for multi output models
Protection class	class II prepared	
Electromagnetic compatibility (EMC), emissions	- Conducted input RI suppression - Harmonic current emissions - Voltage flicker - Radiated input suppression	EN 55022, class B IEC / EN 61000-3-2, class A IEC / EN 61000-3-3, (class tba.) EN 55011, class B
Electromagnets compatibility (EMC), immunity	- Electrostatic discharge ESD - RF field immunity - Electrical fast transients/burst immunity - Surge - Conducted RF - Magnetic field (only for single output models)	IEC / EN 61000-4-2, 8kV/6kV perf. criteria A IEC / EN 61000-4-3, 20V/m perf. criteria A IEC / EN 61000-4-4, ± 2kV perf. criteria A IEC / EN 61000-4-5, ± 1kV/± 2kV perf. criteria A IEC / EN 61000-4-6, 20 Vr.m.s perf. criteria A IEC / EN 61000-4-8, 10A/m perf. criteria A
Voltage dip and interruptions according to EN 60601-1-2 reference: 100 VAC / 50Hz	30%, 500ms perf. criteria A 60%, 100ms perf. criteria B > 95%, 10ms perf. criteria A > 95%, 5000ms perf. criteria B	
Safety standards and certification www.ul.com File e188913 (pending)	UL 60950-1, IEC/EN 60950-1, IEC/EN 60601-1 3rd edition, ANSI/AAMI ES60601-1:2005(R)2012	
Environment	- Vibration acc. IEC 60068-2-6; - Shock acc. IEC 60068-2-27	3 axis, sine sweep, 10–55Hz, 1g, 1oct/min 3 axis, 10g half sine, 11msShock 20 G (3 directions each 3 times)
Environmental compliance	- Reach - RoHS	www.tracopower.com/products/reach-declaration.pdf RoHS directive 2011/65/EU
Connection	screw terminal	

Single output models:





Multi output models:





All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Dimensions

Single output:



Multi output:



Screw Terminal

Input		Output	
Pin	CON 1	Pin*	CON 2
1	Line	1,2	- Vout
3	Neutral	3,4	+ Vout

*Terminal rated for 10 A max.
 (at higher current connection has to be splitted)

Weight: 172g (6.07 oz) single output
 221g (7.90 oz) multi output

Dimensions in inch, () = mm
 Tolerances: x.xx±0.02 (x.x±0.5) x.xxx±0.01 (x.xx±0.25)
 Wire dimensions range 26 - 16 AWG
 M3x0.5 screw locked torque MAX 5Kgf.cm/0.49N.m
 Terminal screw locked torque MAX 2Kgf.cm/0.2N.m

Costumized versions on request (e.g. open frame, PIN-connector, DIN-Rail clip)

Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at www.tracopower.com