

# Protect It! 1-Outlet Portable Surge Protector, Direct Plug-In, 600 Joules, Tel/Modem Protection

## MODEL NUMBER: TRAVELCUBE











### **Description**

The TRAVELCUBE is designed for convenient portable and economical surge protection. Small and powerful, the TRAVELCUBE features 540 joules and carries \$10K of insurance as well as a . Throw it in a briefcase or purse and have quality surge protection wherever you need it — hotel room, dorm, client office — anywhere!

#### **Features**

- Portable wall-mount cube stores easily in any bag or briefcase
- 1 NEMA5-15R AC outlet
- 540 joules of protection shields equipment from harmful surges, spikes and line noise
- Diagnostic LED displays protection status
- Built-in tel/modem surge protection
- Bonus 6-ft. phone cord included
- UL 1449 rated 3rd Edition
- \$10,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

# **Specifications**

OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(1) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15	
USB Charging	No	

### **Highlights**

- 1 AC outlet
- Direct plug-in design
- Built-in tel/modem surge protection
- 540 joule rating
- Diagnostic LED displays protection status
- \$10,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

# **Applications**

 Ideal for use with laptops, fax machines, electronic notepads, personal organizers and other portable electronic devices

### Package Includes

- TRAVELCUBE surge suppressor
- Bonus 6-ft. telephone cord



INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P input plug	
Input Cord Length (ft.)	0	
Input Cord Length (m)	0.00	
Input Cord Length Details	Direct plug-in	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	36000	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (red) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	540	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	150	
UL1449 Let Through Rating	500V	
EMI / RFI Filtering	Up to 20dB	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.83 x 5.12 x 6.50	
Shipping Dimensions (hwd / cm)	7.19 x 13.00 x 16.51	
Shipping Weight (lbs.)	.42	
Shipping Weight (kg)	0.19	
Unit Dimensions (hwd / in.)	1.49 x 2.16 x 3.07	
Unit Dimensions (hwd / cm)	3.78 x 5.49 x 7.80	
Unit Weight (lbs.)	.17	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Unit Weight (kg)	0.08	
Material of Construction	Plastic	
Form Factors Supported	Direct plug in suppressor supports wall-mounting directly into AC receptacle	
Metal Case	No	
SPECIAL FEATURES		
Right-Angle Plug	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3RD EDITION	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.