


## Infrared Emitting Diode, 950 nm, GaAs

### Description

TSTS710. series are infrared emitting diodes in standard GaAs technology in a hermetically sealed TO-18 package. Their glass lenses provide a very high radiant intensity without external optics.



94 8483

### Features

- Very high radiant intensity
- Suitable for pulse operation
- Narrow angle of half intensity  $\varphi = \pm 5^\circ$
- Peak wavelength  $\lambda_p = 950 \text{ nm}$
- High reliability
- Good spectral matching to Si photodetectors
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



### Applications

- Radiation source in near infrared range

### Absolute Maximum Ratings

$T_{amb} = 25^\circ\text{C}$ , unless otherwise specified

| Parameter                           | Test condition   | Symbol     | Value         | Unit             |
|-------------------------------------|--|------------|---------------|------------------|
| Reverse voltage                     |  | $V_R$      | 5             | V                |
| Forward current                     | $T_{case} \leq 25^\circ\text{C}$   | $I_F$      | 250           | mA               |
| Peak forward current                | $t_p/T = 0.5$ , $t_p \leq 100 \mu\text{s}$ ,<br>$T_{case} \leq 25^\circ\text{C}$ | $I_{FM}$   | 500           | mA               |
| Surge forward current               | $t_p \leq 100 \mu\text{s}$   | $I_{FSM}$  | 2.5           | A                |
| Power dissipation                   |  | $P_V$      | 170           | mW               |
|                                     | $T_{case} \leq 25^\circ\text{C}$   | $P_V$      | 500           | mW               |
| Junction temperature                |  | $T_j$      | 100           | $^\circ\text{C}$ |
| Storage temperature range           |  | $T_{stg}$  | - 55 to + 100 | $^\circ\text{C}$ |
| Thermal resistance junction/ambient |  | $R_{thJA}$ | 450           | K/W              |
| Thermal resistance junction/case    |  | $R_{thJC}$ | 150           | K/W              |

### Electrical Characteristics

$T_{amb} = 25^\circ\text{C}$ , unless otherwise specified

| Parameter            | Test condition                                      | Symbol     | Min | Typ. | Max | Unit |
|----------------------|---|------------|-----|------|-----|------|
| Forward voltage      | $I_F = 100 \text{ mA}$ , $t_p \leq 20 \text{ ms}$   | $V_F$      |     | 1.3  | 1.7 | V    |
| Breakdown voltage    | $I_R = 100 \mu\text{A}$                             | $V_{(BR)}$ | 5   |      |     | V    |
| Junction capacitance | $V_R = 0 \text{ V}$ , $f = 1 \text{ MHz}$ , $E = 0$ | $C_j$      |     | 30   |     | pF   |

## Optical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

| Parameter                     | Test condition   | Symbol          | Min | Typ.    | Max | Unit |
|-------------------------------|--|-----------------|-----|---------|-----|------|
| Radiant power                 | $I_F = 100\text{ mA}$ , $t_p \leq 20\text{ ms}$                          | $\phi_e$        |     | 7       |     | mW   |
| Temp. coefficient of $\phi_e$ | $I_F = 100\text{ mA}$  | $TK\phi_e$      |     | - 0.8   |     | %/K  |
| Angle of half intensity       |  | $\varphi$       |     | $\pm 5$ |     | deg  |
| Peak wavelength               | $I_F = 100\text{ mA}$  | $\lambda_p$     |     | 950     |     | nm   |
| Spectral bandwidth            | $I_F = 100\text{ mA}$  | $\Delta\lambda$ |     | 50      |     | nm   |
| Rise time                     | $I_F = 1.5\text{ A}$ , $t_p/T = 0.01$ , $t_p \leq 10\text{ }\mu\text{s}$ | $t_r$           |     | 400     |     | ns   |
| Fall time                     | $I_F = 1.5\text{ A}$ , $t_p/T = 0.01$ , $t_p \leq 10\text{ }\mu\text{s}$ | $t_f$           |     | 400     |     | ns   |
| Virtual source diameter       |  | $\emptyset$     |     | 1.5     |     | mm   |

## Type Dedicated Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

| Parameter         | Test condition                               | Symbol | Min | Typ. | Max | Unit  |
|-------------------|--|--------|-----|------|-----|-------|
| Radiant intensity | $I_F = 100\text{ mA}$ , $t_p = 20\text{ ms}$ | $I_e$  | 10  |      | 50  | mW/sr |

## Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified




Figure 1. Power Dissipation vs. Ambient Temperature




Figure 2. Forward Current vs. Ambient Temperature




Figure 3. Pulse Forward Current vs. Pulse Duration




Figure 6. Radiant Intensity vs. Forward Current




Figure 4. Forward Current vs. Forward Voltage




Figure 7. Radiant Power vs. Forward Current




Figure 5. Relative Forward Voltage vs. Ambient Temperature




Figure 8. Rel. Radiant Intensity/Power vs. Ambient Temperature




Figure 9. Relative Radiant Power vs. Wavelength





Figure 10. Relative Radiant Intensity vs. Angular Displacement

## Package Dimensions in mm



technical drawings  
according to DIN  
specifications

14486



## Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay:](#)

[TSTS7100](#)