

Standard, For General Purposes - Axial Lead Type



-

[illegible]

Technical drawing of a pressure relief vent assembly. The side view shows a central vent pipe with a sleeve (P.E.T.) and sealing rubber packing. Dimensions include 35MIN for the packing length, $L + \alpha \text{ MAX}$ for the sleeve length, and ϕD for the vent diameter. A top view shows the circular cross-section with a central hole of diameter ϕd and a maximum outer diameter of $\phi D \text{ MAX}$.

		(mm)	
α	$(\phi D < 10)$ 1	ϕD 5 to 13	16 to 18
	$(\phi D \geq 10)$ 2	ϕd 0.6	0.8

1 2 3 4 5 6 7 8 9 10 11

T V X 1 A 3 3 1 M A D

Configuration※

Capacitance tolerance (±20%)

Rated capacitance (330μF)

Rated voltage (10V)

Series name

Type

※ Configuration

ϕ D	Pb-free leadwire Pb-free PET sleeve
5 to 8	AD
10 to 18	CD

CAT.8100G

TVX
(02 type)

■ Dimensions

V		6.3		10		16		25		35		50		63		100	
Cap.(μF)	Code	0J		1A		1C		1E		1V		1H		1J		2A	
0.47	R47											5 × 12	5			5 × 12	10
1	010											5 × 12	10			5 × 12	18
2.2	2R2											5 × 12	23			5 × 12	28
3.3	3R3											5 × 12	28			5 × 12	34
4.7	4R7											5 × 12	34			5 × 12	40
10	100											5 × 12	50	5 × 12	55	6.3 × 12	60
22	220									5 × 12	70	6.3 × 12	85	6.3 × 12	90	8 × 16	120
33	330							5 × 12	80	6.3 × 12	90	6.3 × 16	110	6.3 × 16	120	8 × 16	150
47	470					5 × 12	85	6.3 × 12	100	6.3 × 16	120	6.3 × 16	130	8 × 16	160	8 × 20	190
100	101	5 × 12	110	6.3 × 12	130	6.3 × 16	160	6.3 × 16	170	8 × 16	210	8 × 16	220	8 × 20	260	10 × 26	340
220	221	6.3 × 16	200	6.3 × 16	210	8 × 16	260	8 × 16	280	8 × 20	340	10 × 21	410	10 × 26	480	13 × 26	560
330	331	6.3 × 16	250	8 × 16	300	8 × 16	320	8 × 20	380	10 × 21	460	10 × 26	560	13 × 26	650	13 × 31.5	750
470	471	8 × 16	330	8 × 16	350	8 × 20	430	10 × 26	510	10 × 26	610	13 × 26	730	13 × 31.5	840	16 × 31.5	970
1000	102	10 × 21	600	10 × 21	640	10 × 26	770	13 × 26	900	13 × 31.5	1060	16 × 31.5	1260	16 × 31.5	1330		
2200	222	13 × 26	1020	13 × 26	1090	13 × 31.5	1180	16 × 31.5	1480	16 × 31.5	1580	18 × 41	1920				
3300	332	13 × 26	1200	13 × 31.5	1390	16 × 31.5	1620	16 × 41.5	1710	16 × 41.5	2050						
4700	472	16 × 31.5	1500	16 × 31.5	1730	16 × 41.5	1840	18 × 41	2170								
6800	682	16 × 31.5	1840	16 × 41.5	1930	18 × 41	2310										
10000	103	16 × 41.5	2260	18 × 41	2350												

V		160		200		250		315		350		400		450	
Cap.(μF)	Code	2C		2D		2E		2F		2V		2G		2W	
1	010	6.3 × 12	13	6.3 × 12	13	6.3 × 16	14	6.3 × 16	14	6.3 × 16	12	8 × 16	14	8 × 16	14
2.2	2R2	6.3 × 16	23	6.3 × 16	23	8 × 16	27	8 × 16	27	8 × 16	24	8 × 20	28	10 × 21	31
3.3	3R3	8 × 16	33	8 × 16	33	8 × 16	33	8 × 20	36	8 × 20	32	10 × 21	38	10 × 21	38
4.7	4R7	8 × 16	39	8 × 16	39	8 × 20	45	8 × 20	45	10 × 21	46	10 × 21	46	10 × 26	50
10	100	8 × 20	60	10 × 21	70	10 × 21	70	10 × 26	80	13 × 26	85	13 × 26	85	13 × 26	85
22	220	10 × 26	120	13 × 26	140	13 × 26	140	13 × 31.5	150	13 × 31.5	140	16 × 31.5	150	16 × 31.5	150
33	330	13 × 26	170	13 × 26	170	13 × 31.5	190	16 × 31.5	210	16 × 31.5	190	16 × 41.5	210	18 × 41	230
47	470	13 × 31.5	230	13 × 31.5	230	16 × 31.5	260	16 × 31.5	260	16 × 41.5	260	18 × 41	290	Case size φ D × L (mm)	Rated ripple
100	101	16 × 41.5	430	16 × 41.5	430	16 × 41.5	430								

Rated ripple current (mA rms) at 85°C 120Hz

● Frequency coefficient of rated ripple current

V	Cap.(μF)	Frequency	120 Hz	300 Hz	1kHz	10kHz or more
6.3 to 100		0.47 to 47	1.00	1.35	1.57	2.00
		100 to 470	1.00	1.23	1.34	1.50
		1000 to 10000	1.00	1.10	1.13	1.15
160 to 450		1 to 100	1.00	1.25	1.40	1.60

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Nichicon:

[TVX1E102MCD](#) [TVX1E221MAD](#) [TVX1E222MCD](#) [TVX1E330MAD](#) [TVX1E331MAD](#) [TVX1E332MCD](#)
[TVX1E470MAD](#) [TVX1E471MCD](#) [TVX1E472MCD](#) [TVX1H010MAD](#) [TVX1H100MAD](#) [TVX1H101MAD](#) [TVX1H102MCD](#)
[TVX1H220MAD](#) [TVX1H221MCD](#) [TVX1H222MCD](#) [TVX1H2R2MAD](#) [TVX1H330MAD](#) [TVX1H331MCD](#)
[TVX1H3R3MAD](#) [TVX1H470MAD](#) [TVX1H471MCD](#) [TVX1H4R7MAD](#) [TVX1HR47MAD](#) [TVX1J100MAD](#) [TVX1J101MAD](#)
[TVX1J102MCD](#) [TVX1J220MAD](#) [TVX1J221MCD](#) [TVX1J330MAD](#) [TVX1J331MCD](#) [TVX1J470MAD](#) [TVX1J471MCD](#)
[TVX1V101MAD](#) [TVX1V102MCD](#) [TVX1V220MAD](#) [TVX1V221MAD](#) [TVX1V222MCD](#) [TVX1V330MAD](#) [TVX1V331MCD](#)
[TVX1V332MCD](#) [TVX1V470MAD](#) [TVX1V471MCD](#) [TVX2A010MAD](#) [TVX2A100MAD](#) [TVX2A101MCD](#)
[TVX2A220MAD](#) [TVX2A221MCD](#) [TVX2A2R2MAD](#) [TVX2A330MAD](#) [TVX2A331MCD](#) [TVX2A3R3MAD](#) [TVX2A470MAD](#)
[TVX2A471MCD](#) [TVX2A4R7MAD](#) [TVX2AR47MAD](#) [TVX2C010MAD](#) [TVX2C100MAD](#) [TVX2C101MCD](#)
[TVX2C220MCD](#) [TVX2C2R2MAD](#) [TVX2C330MCD](#) [TVX2C3R3MAD](#) [TVX2C470MCD](#) [TVX2C4R7MAD](#)
[TVX2D010MAD](#) [TVX2D100MCD](#) [TVX2D101MCD](#) [TVX2D220MCD](#) [TVX2D2R2MAD](#) [TVX2D330MCD](#)
[TVX2D3R3MAD](#) [TVX2D470MCD](#) [TVX2D4R7MAD](#) [TVX2E010MAD](#) [TVX2E100MCD](#) [TVX2E101MCD](#)
[TVX2E220MCD](#) [TVX2E2R2MAD](#) [TVX2E330MCD](#) [TVX2E3R3MAD](#) [TVX2E470MCD](#) [TVX2E4R7MAD](#)
[TVX2F010MAD](#) [TVX2F100MCD](#) [TVX2F220MCD](#) [TVX2F2R2MAD](#) [TVX2F330MCD](#) [TVX2F3R3MAD](#) [TVX2F470MCD](#)
[TVX2F4R7MAD](#) [TVX2G010MAD](#) [TVX2G100MCD](#) [TVX2G220MCD](#) [TVX2G2R2MAD](#) [TVX2G330MCD](#)
[TVX2G3R3MCD](#) [TVX2G470MCD](#) [TVX2G4R7MCD](#) [TVX2V010MAD](#)