

UBT

■ Dimensions

V(Code)		10 (1A)			16 (1C)			25 (1E)			35 (1V)			50 (1H)		
Cap. (μF)	Item Code	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})
4.7	4R7															
10	100													8 × 11.5	1.15	85
22	220													8 × 11.5	0.75	180
33	330													8 × 11.5	0.50	250
47	470													8 × 11.5	0.45	300
100	101				8 × 11.5	0.32	340	8 × 11.5	0.13	500				8 × 11.5	0.35	440
220	221	8 × 11.5	0.26	340	10 × 12.5	0.15	620	10 × 12.5	0.10	680	10 × 16	0.094	790	10 × 20	0.098	930
330	331	10 × 12.5	0.15	620	10 × 12.5	0.10	680	10 × 16	0.075	945	10 × 20	0.075	950	12.5 × 20	0.070	1330
470	471	10 × 12.5	0.10	680	10 × 16	0.075	945	10 × 20	0.057	1100	12.5 × 20	0.058	1330	12.5 × 25	0.055	1650
1000	102	10 × 20	0.057	1100	12.5 × 20	0.042	1490	12.5 × 25	0.033	1750	16 × 25	0.031	2010	16 × 31.5	0.031	2430
2200	222	12.5 × 25	0.033	1750	16 × 25	0.024	2300	16 × 31.5	0.020	2710	18 × 35.5	0.025	2790			
3300	332	16 × 25	0.024	2300	16 × 31.5	0.020	2710	18 × 31.5	0.017	3310						
4700	472	16 × 31.5	0.020	2710	18 × 31.5	0.018	3270									

V(Code)		63 (1J)			80 (1K)			100 (2A)		
Cap. (μF)	Item Code	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA _{rms})
10	100							8 × 11.5	1.50	150
22	220	8 × 11.5	2.00	130	8 × 11.5	1.50	150	10 × 12.5	0.80	480
33	330	8 × 11.5	1.50	150	10 × 12.5	0.80	480	10 × 12.5	0.80	480
47	470	10 × 12.5	0.59	530	10 × 12.5	0.80	480	10 × 16	0.55	630
100	101	10 × 16	0.41	690	10 × 20	0.39	790	12.5 × 20	0.25	990
220	221	12.5 × 20	0.16	1050	12.5 × 25	0.18	1240	16 × 25	0.11	1500
330	331	12.5 × 25	0.12	1290	12.5 × 31.5	0.16	1390	16 × 31.5	0.079	1790
470	471	12.5 × 31.5	0.097	1460	16 × 25	0.11	1500			

Rated ripple current (mA_{rms}) at 125°C 100kHz
Impedance (Ω) MAX. at 20°C 100kHz

● Frequency coefficient of rated ripple current

V	CV	Frequency			
		120Hz	300Hz	1kHz	10kHz or more
10 to 100	1000 > CV	0.50	0.64	0.83	1.00
	1000 ≤ CV	0.67	0.79	0.91	1.00

V(Code)		160 (2C)		200 (2D)		250 (2E)		350 (2V)		400 (2G)		450 (2W)	
Cap. (μF)	Item Code	Case size φD × L (mm)	Rated ripple (mA _{rms})	Case size φD × L (mm)	Rated ripple (mA _{rms})	Case size φD × L (mm)	Rated ripple (mA _{rms})	Case size φD × L (mm)	Rated ripple (mA _{rms})	Case size φD × L (mm)	Rated ripple (mA _{rms})	Case size φD × L (mm)	Rated ripple (mA _{rms})
4.7	4R7							10 × 20	53	10 × 20	53	10 × 25	58
10	100			10 × 20	78	10 × 20	78	10 × 25	85	10 × 25	86	12.5 × 20	86
22	220	10 × 20	115	10 × 25	126	12.5 × 20	128	12.5 × 25	139	12.5 × 31.5	142	16 × 25	154
33	330	10 × 25	154	12.5 × 20	157	12.5 × 25	171	16 × 25	189	16 × 25	189	16 × 31.5	203
47	470	12.5 × 20	187	12.5 × 25	204	16 × 25	225	16 × 31.5	243	16 × 31.5	243		
68	680	12.5 × 25	245	16 × 20	250	16 × 31.5	292						
100	101	16 × 25	329	16 × 25	329								
150	151	16 × 31.5	434										

Rated ripple current (mA_{rms}) at 125°C 120Hz

● Frequency coefficient of rated ripple current

V	Cap. (μF)	Frequency					
		50Hz	120Hz	300Hz	1kHz	10kHz	100kHz or more
160 to 450	4.7 to 33	0.75	1.00	1.25	1.50	1.75	1.80
	47 to 150	0.80	1.00	1.15	1.30	1.40	1.50

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Nichicon:

[UBT1C332MHD](#) [UBT1C471MPD](#) [UBT1C472MHD](#) [UBT1E101MPD](#) [UBT1H330MPD](#) [UBT1H331MHD](#)
[UBT1H3R3MPD](#) [UBT1K221MHD](#) [UBT1K330MPD](#) [UBT1K331MHD](#) [UBT1K470MPD](#) [UBT1K471MHD](#)
[UBT1C102MHD](#) [UBT1C221MPD](#) [UBT1C222MHD](#) [UBT1C331MPD](#) [UBT1H102MHD](#) [UBT1H220MPD](#)
[UBT1H221MPD](#) [UBT1H2R2MPD](#) [UBT1A331MPD](#) [UBT1A332MHD](#) [UBT1A471MPD](#) [UBT1A472MHD](#)
[UBT1C101MPD](#) [UBT1E471MPD](#) [UBT1H010MPD](#) [UBT1H100MPD](#) [UBT1H101MPD](#) [UBT1J220MPD](#) [UBT1J221MHD](#)
[UBT1J330MPD](#) [UBT1J331MHD](#) [UBT1A102MPD](#) [UBT1A221MPD](#) [UBT1A222MHD](#) [UBT1E102MHD](#)
[UBT1E221MPD](#) [UBT1E222MHD](#) [UBT1E331MPD](#) [UBT1E332MHD](#) [UBT1H470MPD](#) [UBT1H471MHD](#)
[UBT1H4R7MPD](#) [UBT1J101MPD](#) [UBT1K471MHD1TN](#) [UBT1V101MPD](#) [UBT1V102MHD](#) [UBT1V221MPD](#)
[UBT1V222MHD](#) [UBT2A4R7MPD](#) [UBT2C101MHD](#) [UBT2C151MHD](#) [UBT2C220MPD](#) [UBT2G220MHD](#)
[UBT2G330MHD](#) [UBT2G470MHD](#) [UBT1J470MPD](#) [UBT1J471MHD](#) [UBT1K101MPD](#) [UBT1K220MPD](#) [UBT2A220MPD](#)
[UBT2A221MHD](#) [UBT2A330MPD](#) [UBT2A331MHD](#) [UBT2A470MPD](#) [UBT2E100MPD](#) [UBT2E220MHD](#)
[UBT2E330MHD](#) [UBT2E470MHD](#) [UBT2E680MHD](#) [UBT1V331MPD](#) [UBT1V471MHD](#) [UBT2A100MPD](#)
[UBT2A101MHD](#) [UBT2D220MPD](#) [UBT2D330MHD](#) [UBT2D470MHD](#) [UBT2D680MHD](#) [UBT2V4R7MPD](#)
[UBT2W100MHD](#) [UBT2W220MHD](#) [UBT2W330MHD](#) [UBT2W4R7MPD](#) [UBT2C330MPD](#) [UBT2C470MHD](#)
[UBT2C680MHD](#) [UBT2D100MPD](#) [UBT2D101MHD](#) [UBT2G4R7MPD](#) [UBT2V100MPD](#) [UBT2V220MHD](#)
[UBT2V330MHD](#) [UBT2V470MHD](#) [UBT1V470MPD](#) [UBT1E470MPD](#) [UBT2A100MHD](#) [UBT1H100MPD1TD](#)
[UBT1A221MPD1TD](#) [UBT2A221MHD8](#)