



SIGN	DATE	DESCRIPTION	APPROVER
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

- Material**
- Insulator: Glass Filled Polyester
  - Flammability: UL94V-0
  - Contacts: Phosphor Bronze
  - Contact Plating: See options
  - Shell: Brass
  - Shell Plating: 80u" Ni over 50u" Cu
  - Rear Shell: Steel with Ni plating
- Ratings**
- Current: 1A
  - Voltage: 30V AC(r.m.s.)
  - Dielectric Withstanding Voltage: 750V AC at sea level
  - Contact Resistance: <30mΩ
  - Insulation Resistance: >1,000 MΩ
  - Operating Temperature: -20° ~ +60°
  - Storage Temperature: -0° ~ +50°

RHS Compliant

PART NUMBER:  
**USB-A2VSXX**

COLOR:  
 B: Black  
 W: White

PLATING:  
 6: Selective Gold Flash (Std.)  
 8: Selective 30u" Gold  
 9: Selective 50u" Gold

<b>OST ON-SHORE TECHNOLOGY, INC.</b>							
TITLE	USB - A type, Vertical, thru hole, Dual Port						
PART NO.	USB-A2VSXX			DWG NO. USB-A2VSXX.DWG			
APPROVED	CHECKED	DESIGNED	DRAWN	4050			
	Marvin 2002.03.12	Marvin 2002.03.12	Marvin 2002.03.12	Tolerance			
				UNIT: mm/inches		X* ±*	
				SCALE: NONE		XX ±0.30/0.12	
				SHEET: 01/01		XXX ±0.20/0.08	
				REV.: A		XXX ±0.10/0.04	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.