










DETAIL A
POSITION "T" SHOWN
FOR REFERENCE



DETAIL B
POSITION "T" SHOWN
FOR REFERENCE



SIZE	C DIM	(L DIM)
04	.115	(.075)
09	.240	(.200)
15	.390	(.350)

	25	.640	(.600)
	37	.940	(.900)
	51	1.290	(1.250)

1. INSULATOR MATERIAL: RYTON (POLYPHENYLENE SULFIDE) PER MIL-M-24519 OR LCP PER ASTM D5138
2. OPTIONAL POLARIZATION POSITION SHOWN FOR REFERENCE ONLY. IF POLARIZATION GUIDE POST(S) ARE REQUIRED ON THE MATING PLUG, THE CORRESPONDING LOCATION MUST BE SPECIFIED IN THE NANONICS PART NUMBER. THE CONTACT CAVITY IS LEFT EMPTY FOR ACCEPTANCE OF THE PLUG GUIDE POST AND IS A NON OPERATIONAL CAVITY.
3. OPTIONAL POLARIZATION GUIDE POST SHOWN FOR REFERENCE ONLY. IF GUIDE POST(S) ARE REQUIRED, THE LOCATION MUST BE SPECIFIED IN THE NANONICS PART NUMBER AND IS A NON OPERATIONAL CAVITY. GUIDE POST MATERIAL IS 303 STAINLESS STEEL, PASSIVATED PER SAE-AMS-QQ-P-35.
4. POLARIZING POSITIONS MUST MATCH ON BOTH ENDS OF THE ASSEMBLY.
5. THIS CONFIGURATION MAY BE TERMINATED WITH 28 AWG SOLID, 30 AWG STRANDED OR SMALLER WIRE. CONDUCTOR TYPE AND LENGTH MUST BE SPECIFIED IN NANONICS PART NUMBER.
6. WHEN ORDERING THESE SIZES, FIRST CONSULT TYCO ELECTRONICS/NANONICS FOR ADDITIONAL INFORMATION.
7. LENGTH TOLERANCE: UP TO 25.0 INCHES, $^{+0.25}_{-0.00}$; 25.0 INCHES AND LONGER, $^{+1\%}_{-0.00}$
8. PREVIOUSLY IDENTIFIED AS NANONICS 303-0108

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. SCHOLL 05-01-02 CHK M. STORRY 05-01-02 APVD D. MORALES 01-27-04		tyco <i>Electronics</i> Tyco Electronics Corporation Harrisburg, PA 17105	
DIMENSIONS: INCHES 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± .010 3 PLC ± .005 4 PLC ± - ANGLES ± 1°		NAME JUMPER ASSEMBLY, PLUG TO RECEPTACLE, UNSHROUDED STRIP, PLASTIC	
MATERIAL SEE NOTES		FINISH SEE NOTES			
		WEIGHT -		SIZE A2	
				CAGE CODE 00779	
				DRAWING NO C-1589752	
				RESTRICTED TO -	
CUSTOMER DRAWING				SCALE 6:1	
				SHEET 1 of 1	
				REV D	