

[Products](#)[Industries](#)[Resources](#)[About TE](#)[Support Center](#)[My Account](#)[Home](#) > [Products](#) > [Relays](#) > [Product Feature Selector](#) > Product Details

## V23100V4024A 1 Product Details

 [Share](#) [Print](#) [Email](#)

V23100V4024A 1

TE Internal Number: 1-1393763-5

 [Active](#)

### Communications/Signal PC Board Relays

 [Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- V23100-V4 / Dry Reed relay DIP & SIL Series
- DC Actuating System
- Input Voltage = 24 VDC
- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Contact - Rated Current = .5 A

[View all Features](#)

#### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- [Reed Relay Datasheet](#) (PDF, English)

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Series](#) = V23100-V4 / Dry Reed relay DIP & SIL
- Termination Type = Through Hole

#### Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 24
- Contact - Rated Current (A) = 0.5
- [Coil Resistance \( \$\Omega\$ \)](#) = 2000
- Coil - Rated Power (mW) = 288
- [Insulation - Special Features](#) = None
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 1500

#### Body Features:

- Polarized = No

#### Contact Features:

- Mounting Options = PC Board
- Enclosure Type = Ultrasonic Cleanable
- Contact Base Material = Rhodium
- Approx. Dimensions (L x W x H) (mm [in]) = 19.30 x 7.50 x 5.70 [.760 x .295 x .224]
- Option = With Electrostatic Shield
- DIP Package Style = Flat
- Contact Configuration = Bifurcated
- Pin Configuration = DIP

#### Configuration Features:

- [Contact Arrangement](#) = 1 Form A, SPST-NO, 1 N/O
- [Coil - Magnetic System](#) = Non Polarized, Monostable
- Coil Suppression Diode = Without

#### Industry Standards:

- Approved Standards = cUL
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

#### Other:

- Brand = Axicom

### Corporate Information

[Who We Are](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)

### Quick Links

[Check Distributor Inventory](#)[Cross Reference](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)

### Customer Support

[Email or Chat With Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage your Account](#)

### Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address

