

Search



narrow your search

Products

- ? Controls Monitoring and Lighting (353)
- ? Machine Safety (1726)
- ? Sensors (7015)
- ? Switches (9585)

Technology

- ? Control and Instrumentation(1051)
- ? Electromechanical (9146)
- ? Magnetic (505)
- ? Microstructure (2298)
- ? Thick Film(1764)
- ? More...

Need Help?

Click here to contact us



VP25K2000 Wirewound Resistors

(Home: Products)



VP Fixed Series, 2 kOhms, 25.0 W, Fixed, Wirewound Resistor

Actual product appearance may vary.

Sales & Service



Distributor Inventory



Overview

Specs

Documentation

Application Notes

Description

The VP and VK Series resistors are intended for applications requiring high power resistors. The resistors have lug terminals, which are solderable and they can also be bracket mounted. They have tinned lug terminals solderable to MIL-R-26 standards. They have tubular ceramic cores and vitreous enamel coatings and are very suitable for rugged applications. These resistors can be bracket mounted.

Note: Not suitable for high frequency applications.

Features

Features

- ? Rugged vitreous enamel coating
- ? Suitable for high wattage applications
- ? All-welded construction
- ? Meets or exceeds MIL-R-26 standards

Potential Applications

Potential Applications

- ? Power supplies
- ? Power dissipation circuits
- ? Load adjustors for power amplifiers