


Schottky Rectifier, 3.3 A


C-16

FEATURES

- Low profile, axial leaded outline
- High frequency operation
- Very low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Lead (Pb)-free plating
- Designed and qualified for industrial level


RoHS
COMPLIANT

DESCRIPTION

The 31DQ.. axial leaded Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection

PRODUCT SUMMARY

| | |
|-------------|----------|
| $I_{F(AV)}$ | 3.3 A |
| V_R | 90/100 V |

MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL | CHARACTERISTICS | VALUES | UNITS |
|-------------|---------------------------|-------------|-------|
| $I_{F(AV)}$ | Rectangular waveform | 3.3 | A |
| V_{RRM} | | 90/100 | V |
| I_{FSM} | $t_p = 5 \mu s$ sine | 210 | A |
| V_F | 3 Apk, $T_J = 25^\circ C$ | 0.85 | V |
| T_J | | - 40 to 150 | °C |

VOLTAGE RATINGS

| PARAMETER | SYMBOL | 31DQ09 | 31DQ10 | UNITS |
|--------------------------------------|-----------|--------|--------|-------|
| Maximum DC reverse voltage | V_R | | | |
| Maximum working peak reverse voltage | V_{RWM} | 90 | 100 | V |

ABSOLUTE MAXIMUM RATINGS

| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
|--|-------------|---|--------|-------|
| Maximum average forward current See fig. 4 | $I_{F(AV)}$ | 50 % duty cycle at $T_L = 108^\circ C$, rectangular waveform | 3.3 | A |
| Maximum peak one cycle non-repetitive surge current See fig. 6 | I_{FSM} | 5 μs sine or 3 μs rect. pulse | 210 | |
| Non-repetitive avalanche energy | | 10 ms sine or 6 ms rect. pulse $T_J = 25^\circ C$, $I_{AS} = 1 A$, $L = 6 mH$ | 34 | |
| Repetitive avalanche current | I_{AR} | Current decaying linearly to zero in 1 μs Frequency limited by T_J maximum $V_A = 1.5 \times V_R$ typical | 0.5 | A |

ELECTRICAL SPECIFICATIONS

| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS | |
|---|--------------------------------|---|---------------------------------------|--------|-------|--|
| Maximum forward voltage drop See fig. 1 | V _{FM} ⁽¹⁾ | 3 A | T _J = 25 °C | 0.85 | V | |
| | | 6 A | | 0.97 | | |
| | | 3 A | T _J = 125 °C | 0.69 | | |
| | | 6 A | | 0.80 | | |
| Maximum reverse leakage current See fig. 4 | I _{RM} ⁽¹⁾ | T _J = 25 °C | V _R = Rated V _R | 1 | mA | |
| | | T _J = 125 °C | | 3 | | |
| Typical junction capacitance | C _T | V _R = 5 V _{DC} (test signal range 100 kHz to 1 MHz) 25 °C | | 110 | pF | |
| Typical series inductance | L _S | Measured lead to lead 5 mm from package body | | 9.0 | nH | |
| Maximum voltage rate of charge | dV/dt | Rated V _R | | 10 000 | V/μs | |

Note

(1) Pulse width < 300 μs, duty cycle < 2 %

 THERMAL - MECHANICAL SPECIFICATIONS

| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
|---|--|-------------------------------------|-------------|-------|
| Maximum junction and storage temperature range | T _J ⁽¹⁾ , T _{Stg} | | - 40 to 150 | °C |
| Maximum thermal resistance, junction to ambient | R _{thJA} | DC operation Without cooling fin | 80 | °C/W |
| Typical thermal resistance, junction to lead | R _{thJL} | DC operation | 15 | |
| Approximate weight | | | 1.2 | g |
| | | | 0.042 | oz. |
| Marking device | | Case style C-16 | 31DQ09 | |
| | | | 31DQ10 | |

Note(1) $\frac{dP_{tot}}{dT_J} < \frac{1}{R_{thJA}}$ thermal runaway condition for a diode on its own heatsink




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage




Fig. 4 - Maximum Allowable Lead Temperature vs. Average Forward Current




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage




Fig. 5 - Forward Power Loss Characteristics

Note

(1) Formula used: $T_C = T_J - (P_d + P_{dREV}) \times R_{thJL}$;
 $P_d = \text{Forward power loss} = I_{F(AV)} \times V_{FM} \text{ at } (I_{F(AV)}/D)$ (see fig. 6); $P_{dREV} = \text{Inverse power loss} = V_{R1} \times I_R (1 - D)$; I_R at $V_{R1} = 80\%$ rated V_R




Fig. 6 - Maximum Non-Repetitive Surge Current

ORDERING INFORMATION TABLE

| Device code | 31 | D | Q | 10 | TR |
|-------------|----|---|---|----|----|
| 1 | | | | | |
| 2 | | | | | |
| 3 | | | | | |
| 4 | | | | | |
| 5 | | | | | |

1 - 31 = 3.1 A (axial and small packages - current is x 10)
2 - D = DO-201 package
3 - Q = Schottky Q.. series
4 - 10 = Voltage ratings 09 = 90 V
10 = 100 V
5 - • TR = Tape and reel package (1200 pcs)
• None = Box package (500 pcs)

| LINKS TO RELATED DOCUMENTS | |
|----------------------------|---|
| Dimensions | http://www.vishay.com/doc?95242 |
| Part marking information | http://www.vishay.com/doc?95304 |
| Packaging information | http://www.vishay.com/doc?95309 |
| SPICE model | http://www.vishay.com/doc?95300 |

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.