



## Standard Recovery Diodes, 165 A to 230 A (INT-A-PAK Power Modules)



INT-A-PAK

### FEATURES

- High voltage
- Electrically isolated by DBC ceramic ( $\text{Al}_2\text{O}_3$ )
- 3500  $V_{\text{RMS}}$  isolating voltage
- Industrial standard package
- High surge capability
- Glass passivated chips
- Modules uses high voltage power diodes in four basic configurations
- Simple mounting
- UL approved file E78996 
- Designed and qualified for multiple level
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT

### PRODUCT SUMMARY

|                    |                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------|
| $I_{\text{F(AV)}}$ | 165 A to 230 A                                                                               |
| Type               | Modules - Diode, High Voltage                                                                |
| Package            | INT-A-PAK                                                                                    |
| Circuit            | Single diode, two diodes common anode, two diodes common cathode, two diodes doubler circuit |

### APPLICATIONS

- DC motor control and drives
- Battery chargers
- Welders
- Power converters

### MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL              | CHARACTERISTICS | VSK.166..   | VSK.196.. | VSK.236.. | UNITS                        |
|---------------------|-----------------|-------------|-----------|-----------|------------------------------|
| $I_{\text{F(AV)}}$  |                 | 165         | 195       | 230       | A                            |
|                     | $T_{\text{C}}$  | 100         | 100       | 100       | $^{\circ}\text{C}$           |
| $I_{\text{F(RMS)}}$ |                 | 260         | 305       | 360       | A                            |
| $I_{\text{FSM}}$    | 50 Hz           | 4000        | 4750      | 5500      |                              |
|                     | 60 Hz           | 4200        | 4980      | 5765      |                              |
| $I^2t$              | 50 Hz           | 80          | 113       | 151       | $\text{kA}^2\text{s}$        |
|                     | 60 Hz           | 73          | 103       | 138       |                              |
| $I^2\sqrt{t}$       |                 | 798         | 1130      | 1516      | $\text{kA}^2\sqrt{\text{s}}$ |
| $V_{\text{RRM}}$    |                 | 400 to 1600 |           |           | V                            |
| $T_{\text{J}}$      | Range           | -40 to +150 |           |           | $^{\circ}\text{C}$           |

### ELECTRICAL SPECIFICATIONS

#### VOLTAGE RATINGS

| TYPE NUMBER                            | VOLTAGE CODE | $V_{\text{RRM}}$ , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE<br>V | $V_{\text{RSM}}$ , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE<br>V | $I_{\text{RRM}}$ AT 150 $^{\circ}\text{C}$<br>mA |
|----------------------------------------|--------------|-----------------------------------------------------------------|---------------------------------------------------------------------|--------------------------------------------------|
| VS-VSK.166<br>VS-VSK.196<br>VS-VSK.236 | 04           | 400                                                             | 500                                                                 | 20                                               |
|                                        | 08           | 800                                                             | 900                                                                 |                                                  |
|                                        | 12           | 1200                                                            | 1300                                                                |                                                  |
|                                        | 14           | 1400                                                            | 1500                                                                |                                                  |
|                                        | 16           | 1600                                                            | 1700                                                                |                                                  |



| FORWARD CONDUCTION                                             |                     |                                                                                                                                                                                                      |                                  |                                                                 |         |         |         |                    |
|----------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-----------------------------------------------------------------|---------|---------|---------|--------------------|
| PARAMETER                                                      | SYMBOL              | TEST CONDITIONS                                                                                                                                                                                      |                                  |                                                                 | VALUES  |         |         | UNITS              |
|                                                                |                     |                                                                                                                                                                                                      |                                  |                                                                 | VSK.166 | VSK.196 | VSK.236 |                    |
| Maximum average on-state current at case temperature           | I <sub>F(AV)</sub>  | 180° conduction, half sine wave                                                                                                                                                                      |                                  |                                                                 | 165     | 195     | 230     | A                  |
|                                                                |                     |                                                                                                                                                                                                      |                                  |                                                                 | 100     | 100     | 100     | °C                 |
| Maximum RMS on-state current                                   | I <sub>F(RMS)</sub> |                                                                                                                                                                                                      |                                  |                                                                 | 260     | 305     | 360     | A                  |
| Maximum peak, one-cycle on-state, non-repetitive surge current | I <sub>FSM</sub>    | t = 10 ms                                                                                                                                                                                            | No voltage reapplied             | Sine half wave, initial T <sub>J</sub> = T <sub>J</sub> maximum | 4000    | 4750    | 5500    |                    |
|                                                                |                     | t = 8.3 ms                                                                                                                                                                                           |                                  |                                                                 | 4200    | 4980    | 5765    |                    |
|                                                                |                     | t = 10 ms                                                                                                                                                                                            | 100 % V <sub>RRM</sub> reapplied |                                                                 | 3350    | 4000    | 4630    |                    |
|                                                                |                     | t = 8.3 ms                                                                                                                                                                                           |                                  |                                                                 | 3500    | 4200    | 4850    |                    |
| Maximum I <sup>2</sup> t for fusing                            | I <sup>2</sup> t    | t = 10 ms                                                                                                                                                                                            | No voltage reapplied             |                                                                 | 80      | 113     | 151     | kA <sup>2</sup> s  |
|                                                                |                     | t = 8.3 ms                                                                                                                                                                                           |                                  |                                                                 | 73      | 103     | 138     |                    |
|                                                                |                     | t = 10 ms                                                                                                                                                                                            | 100 % V <sub>RRM</sub> reapplied |                                                                 | 56      | 80      | 107     |                    |
|                                                                |                     | t = 8.3 ms                                                                                                                                                                                           |                                  |                                                                 | 52      | 73      | 98      |                    |
| Maximum I <sup>2</sup> √t for fusing                           | I <sup>2</sup> √t   | t = 0.1 ms to 10 ms, no voltage reapplied                                                                                                                                                            |                                  |                                                                 | 798     | 1130    | 1516    | kA <sup>2</sup> √s |
| Low level value of threshold voltage                           | V <sub>F(TO)1</sub> | (16.7 % × π × I <sub>F(AV)</sub> < I < π × I <sub>F(AV)</sub> ), T <sub>J</sub> maximum                                                                                                              |                                  |                                                                 | 0.73    | 0.69    | 0.7     | V                  |
| High level value of threshold voltage                          | V <sub>F(TO)2</sub> | (I > π × I <sub>F(AV)</sub> ), T <sub>J</sub> maximum                                                                                                                                                |                                  |                                                                 | 0.88    | 0.78    | 0.83    |                    |
| Low level value on-state slope resistance                      | r <sub>t1</sub>     | (16.7 % × π × I <sub>F(AV)</sub> < I < π × I <sub>F(AV)</sub> ), T <sub>J</sub> maximum                                                                                                              |                                  |                                                                 | 1.5     | 1.3     | 1.2     | mΩ                 |
| High level value on-state                                      | r <sub>t2</sub>     | (I > π × I <sub>F(AV)</sub> ), T <sub>J</sub> maximum                                                                                                                                                |                                  |                                                                 | 1.26    | 1.2     | 1.07    |                    |
| Maximum forward voltage drop                                   | V <sub>FM</sub>     | I <sub>FM</sub> = π × I <sub>F(AV)</sub> , T <sub>J</sub> = 25 °C, 180° conduction<br>Average power = V <sub>F(TO)</sub> × I <sub>F(AV)</sub> + r <sub>f</sub> × (I <sub>F(RMS)</sub> ) <sup>2</sup> |                                  |                                                                 | 1.43    | 1.38    | 1.46    | V                  |

| BLOCKING                                           |           |                                                                 |         |         |         |       |
|----------------------------------------------------|-----------|-----------------------------------------------------------------|---------|---------|---------|-------|
| PARAMETER                                          | SYMBOL    | TEST CONDITIONS                                                 | VSK.166 | VSK.196 | VSK.236 | UNITS |
| Maximum peak reverse and off-state leakage current | $I_{RRM}$ | $T_J = 150\text{ °C}$                                           | 20      |         |         | mA    |
| RMS insulation voltage                             | $V_{INS}$ | 50 Hz, circuit to base, all terminals shorted, $t = 1\text{ s}$ | 3500    |         |         | V     |

| THERMAL AND MECHANICAL SPECIFICATIONS                     |                                   |                                                                                                                                                              |             |         |         |       |
|-----------------------------------------------------------|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|---------|---------|-------|
| PARAMETER                                                 | SYMBOL                            | TEST CONDITIONS                                                                                                                                              | VALUES      |         |         | UNITS |
|                                                           |                                   |                                                                                                                                                              | VSK.166     | VSK.196 | VSK.236 |       |
| Maximum junction operating and storage temperature range  | T <sub>J</sub> , T <sub>Stg</sub> |                                                                                                                                                              | -40 to +150 |         |         | °C    |
| Maximum thermal resistance, junction to case per junction | R <sub>thJC</sub>                 | DC operation                                                                                                                                                 | 0.2         | 0.16    | 0.14    | K/W   |
| Maximum thermal resistance, case to heatsink per module   | R <sub>thCS</sub>                 | Mounting surface smooth, flat and greased                                                                                                                    | 0.05        |         |         |       |
| Mounting torque ± 10 %                                    | IAP to heatsink<br>busbar to IAP  | A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads. | 4 to 6      |         |         | Nm    |
| Approximate weight                                        |                                   |                                                                                                                                                              | 200         |         |         | g     |
|                                                           |                                   |                                                                                                                                                              | 7.1         |         |         | oz.   |
| Case style                                                |                                   |                                                                                                                                                              | INT-A-PAK   |         |         |       |



## ΔR CONDUCTION PER JUNCTION

| DEVICES | SINUSOIDAL CONDUCTION<br>AT T <sub>J</sub> MAXIMUM |       |       |       |       | RECTANGULAR CONDUCTION<br>AT T <sub>J</sub> MAXIMUM |       |       |       |       | UNITS |
|---------|----------------------------------------------------|-------|-------|-------|-------|-----------------------------------------------------|-------|-------|-------|-------|-------|
|         | 180°                                               | 120°  | 90°   | 60°   | 30°   | 180°                                                | 120°  | 90°   | 60°   | 30°   |       |
| VSK.166 | 0.025                                              | 0.03  | 0.038 | 0.055 | 0.089 | 0.018                                               | 0.031 | 0.041 | 0.057 | 0.089 | K/W   |
| VSK.196 | 0.016                                              | 0.019 | 0.024 | 0.034 | 0.053 | 0.012                                               | 0.02  | 0.026 | 0.035 | 0.054 |       |
| VSK.236 | 0.009                                              | 0.010 | 0.014 | 0.018 | 0.025 | 0.008                                               | 0.012 | 0.015 | 0.019 | 0.025 |       |

### Note

- Table shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current





Fig. 7 - On-State Power Loss Characteristics





Fig. 8 - On-State Power Loss Characteristics





Fig. 9 - On-State Power Loss Characteristics




Fig. 10 - Current Ratings Characteristics




Fig. 12 - On-State Power Loss Characteristics




Fig. 11 - Current Ratings Characteristics




Fig. 13 - On-State Power Loss Characteristics




Fig. 14 - Maximum Non-Repetitive Surge Current




Fig. 15 - Maximum Non-Repetitive Surge Current





Fig. 16 - On-State Power Loss Characteristics





Fig. 17 - On-State Power Loss Characteristics





Fig. 18 - On-State Power Loss Characteristics




Fig. 19 - Current Ratings Characteristics




Fig. 21 - On-State Power Loss Characteristics




Fig. 20 - Current Ratings Characteristics




Fig. 22 - On-State Power Loss Characteristics






Fig. 23 - Maximum Non-Repetitive Surge Current




Fig. 24 - Maximum Non-Repetitive Surge Current





Fig. 25 - On-State Power Loss Characteristics





Fig. 26 - On-State Power Loss Characteristics







Fig. 27 - On-State Power Loss Characteristics




Fig. 28 - On-State Voltage Drop Characteristics




Fig. 30 - On-State Voltage Drop Characteristics




Fig. 29 - On-State Voltage Drop Characteristics




Fig. 31 - Thermal Impedance  $Z_{\theta JC}$  Characteristics




Fig. 32 - Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 33 - Thermal Impedance  $Z_{thJC}$  Characteristics

## ORDERING INFORMATION TABLE

Device code

| VS-VS | KD | 236 | 16 | PbF |
|-------|----|-----|----|-----|
|-------|----|-----|----|-----|

1

2

3

4

5

1

2

3

4

5

- Vishay Semiconductors product
- Circuit configuration
- Current rating:  $I_{F(AV)}$
- Voltage code x 100 =  $V_{RRM}$
- PbF = Lead (Pb)-free

### Note

- To order the optional hardware go to [www.vishay.com/doc?95172](http://www.vishay.com/doc?95172)




| CIRCUIT CONFIGURATION      |                            |                       |
|----------------------------|----------------------------|-----------------------|
| CIRCUIT DESCRIPTION        | CIRCUIT CONFIGURATION CODE | CIRCUIT DRAWING       |
| Two diodes doubler circuit | D                          | <p><b>VSKD...</b></p> |
| Two diodes common cathode  | C                          | <p><b>VSKC...</b></p> |
| Two diodes common anode    | J                          | <p><b>VSKJ...</b></p> |
| Single diode               | E                          | <p><b>VSKE...</b></p> |

| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95254">www.vishay.com/doc?95254</a> |

## INT-A-PAK DBC

**DIMENSIONS** in millimeters (inches)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[VS-VSKC166/08PBF](#) [VS-VSKC196/12PBF](#) [VS-VSKC236/12PBF](#) [VS-VSKD166/04PBF](#) [VS-VSKC196/04PBF](#) [VS-](#)  
[VSKC236/04PBF](#) [VS-VSKC236/16PBF](#) [VS-VSKD236/12PBF](#) [VS-VSKE196/08PBF](#) [VS-VSKD236/16PBF](#) [VS-](#)  
[VSKD196/12PBF](#) [VS-VSKD196/04PBF](#) [VS-VSKE166/04PBF](#) [VS-VSKD196/16PBF](#) [VS-VSKE166/12PBF](#) [VS-](#)  
[VSKE166/08PBF](#) [VS-VSKE236/12PBF](#) [VS-VSKJ236/16PBF](#) [VS-VSKJ166/16PBF](#) [VS-VSKJ236/04PBF](#) [VS-](#)  
[VSKC166/04PBF](#) [VS-VSKD236/04PBF](#) [VS-VSKJ236/12PBF](#) [VS-VSKE166/16PBF](#) [VS-VSKD166/14PBF](#) [VS-](#)  
[VSKD236/08PBF](#) [VS-VSKE236/16PBF](#) [VS-VSKD166/16PBF](#) [VS-VSKD166/08PBF](#) [VS-VSKJ166/04PBF](#) [VS-](#)  
[VSKE166/14PBF](#) [VS-VSKD166/12PBF](#) [VS-VSKC196/08PBF](#) [VS-VSKD196/08PBF](#) [VS-VSKE196/12PBF](#) [VS-](#)  
[VSKC166/16PBF](#) [VS-VSKC166/12PBF](#) [VS-VSKE196/16PBF](#) [VS-VSKE236/04PBF](#) [VS-VSKE196/04PBF](#)