

2 and 3-Wire *minifast*® Cordsets, Standard

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 300 V, 9 A



| Housing Style | Part Number         | Cable                                                                                         | Features                               | Pinout                        |
|---------------|---------------------|-----------------------------------------------------------------------------------------------|----------------------------------------|-------------------------------|
|               | WSM 20- *M          | AWM PVC Yellow<br>2x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50511-*M <sup>†</sup>            | <i>flexlife</i> ®                      | 1. BN<br>2. BU<br>            |
|               | WSM 30-*M           | AWM PVC Yellow<br>3x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50512-*M <sup>†</sup>            | <i>flexlife</i>                        | 1. GN/YE<br>2. BN<br>3. BU    |
|               | WSM 30-*M/S90       | AWM PUR Yellow<br>3x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50545-*M <sup>†</sup>            | <i>Cut Abrasion Immune</i>             |                               |
|               | WSM 311-*M          | AWM PVC Yellow<br>3x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50520-*M <sup>†</sup>            | <i>flexlife</i>                        | 1. GN<br>2. RD/BK<br>3. RD/WH |
|               | WSM 311-*M/S600     | SJOOW CPE, Yellow<br>3x18 AWG<br>105°C<br>8.0 mm OD<br>Cable #RF50658-*M <sup>†</sup>         | <i>Weld Flash Immune, Flame Immune</i> |                               |
|               | WSM 31-*M           | AWM PVC Yellow<br>3x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50513-*M <sup>†</sup>            | <i>flexlife</i>                        |                               |
|               | WSM 31-*M/S600      | SJOOW CPE Yellow<br>3x18 AWG<br>105°C<br>8.0 mm OD<br>Cable #RF50654-*M <sup>†</sup>          | <i>Weld Flash Immune, Flame Immune</i> |                               |
|               | WSM 31-*M/S759      | AWM PVC Grey<br>3x22 AWG<br>80°C<br>5.2 mm OD<br>Cable #RF04106-*M <sup>†</sup>               | <i>Braided Shield</i>                  |                               |
|               | WSM 31-*M/S816      | AWM PVC Yellow<br>3x20 AWG<br>105°C<br>5.2 mm OD<br>Cable #RF50674-*M <sup>†</sup>            | <i>flexlife</i>                        |                               |
|               | WSM 311-*M/XOR/S620 | AWM Irradiated PVC<br>Yellow, 3x18 AWG<br>80°C<br>5.7 mm OD<br>Cable #RF04159-*M <sup>†</sup> | <i>Weld Resistance</i>                 | 1. GN<br>2. RD<br>3. RD/WH    |

\* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass "WSM .."; "WS .." indicates nylon and "WSV .." indicates 316 stainless steel.  
<sup>†</sup> See Section N for *reelfast*® cable information.