
Power Lead





10 ±0.15 -

17.5



The materials in our power cords range have been independently tested by an appropriate third party and we retain these records and intend to repeat such tests on an ongoing basis as part of our quality control procedures. Testing methods include:

Dimensions: Millimetres





Power Lead



Features:

• EPA method 3050B : 1996 other acid digestion

BSEN1122 : 2001 method B other acid digestion

EPA method 3052B : 1996 other acid digestion

EPA method 3060 and EPA 7196 A : 1992

Atomic absorption spectrometer / inductively coupled plasma atomic emission spectrometer (ICP+AES) UV - VIS

spectrophotometer

End 1 : Schuko plug right angled black

Fuse : N / A

Lead : 200 metres HO5VV-F 3 × 0.75 black

End 2 : Cloverleaf (C5) black

Cables available with these connectors:

SVT 18 AWG × 3C - 16 AWG × 3C SJT 18 AWG × 3C - 14 AWG × 3C H05VV-F 3G 0.75 - 1.5 4 V -75 250 / 440 V 3G 0.75 - 1 227 IEC53 (RVV) 300 / 500 V 3G 0.75 - 1.5

Approvals:





Part Number Table

Description	Part Number
Lead, Euro to Cloverleaf, Black, 2 m	SH10188R

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-ELEC is the registered trademark of the Group. © Premier Farnell plc 2012.



