

## High Precision Bulk Metal® Foil Surface Mount Voltage Divider, TCR Tracking of < 0.5 ppm/°C, Tolerance Match of 0.01 % and Stability of ± 0.005 % (50 ppm)



### INTRODUCTION

Bulk Metal® foil technology out-performs all other resistor technologies available today for applications that require high precision and high stability.

This technology has been invented, patented and pioneered by Vishay. Products based on this technology are the most suitable for a wide range of applications.

BMF technology allows to produce customer oriented products designed to satisfy challenging and specific technical requirements. Model DSM offers low TCR (both absolute and tracking), excellent load life stability, tight tolerance, excellent ratio stability, and low current noise, all in one package.

The DSM surface mount divider provides a matched pair of Bulk Metal foil resistors in a small epoxy molded package. The electrical specification of this integrated construction offers improved performance and better real estate utilization over discrete resistors and matched pairs.

Our application engineering department is available to advise and make recommendations. For non-standard technical requirements and special applications, please contact us.


### FEATURES

- Temperature coefficient of resistance (TCR):  
Absolute:  $\pm 2 \text{ ppm/}^{\circ}\text{C}$  typical  
(- 55 °C to + 125 °C, + 25 °C ref.)  
Tracking: 0.5 ppm/°C typical
- Tolerance: absolute:  $\pm 0.02 \%$ ; match: 0.01 %
- Power rating at 70 °C: entire package: 0.1 W  
each resistor: 0.05 W
- Ratio stability: 0.005 % (0.05 W at 70 °C, 2000 h)
- Resistance range: 100 Ω to 12 kΩ per resistor
- Large variety of resistance ratios: 1:120
- Vishay Foil resistors are not restricted to standard values/ratios; specific "as required" values/ratios can be supplied at no extra cost or delivery (e.g. 1K234/2K345 vs. 1K/2K)
- Electrostatic discharge (ESD) up to 25 000 V
- Short time overload  $\leq 0.005 \%$
- Non inductive, non capacitive design
- Rise time: 1 ns effectively no ringing
- Current noise:  $< -40 \text{ dB}$
- Voltage coefficient:  $< 0.1 \text{ ppm/V}$
- Non inductive:  $< 0.08 \mu\text{H}$
- Non hot spot design
- Terminals: silver coated copper alloy
- Compliant to RoHS directive 2002/95/EC
- Prototype quantities available in just 5 working days or sooner. For more information, please contact [foil@vishay.com](mailto:foil@vishay.com)
- For better performances, please see DSMZ datasheet (Z-foil)




**RoHS\***  
COMPLIANT

**FIGURE 1 - SCHEMATIC**



### APPLICATIONS






- Instrumentation amplifiers
- Bridge networks
- Differential amplifiers
- Ratio arms in bridge circuits
- Medical and test equipment
- Military
- Airborne etc.



**TABLE 1 - MODEL DSM SPECIFICATIONS**


MODEL	ABSOLUTE TCR (- 55 °C TO + 125 °C, + 25 °C REF.) TYPICAL + MAX. SPREAD	RESISTANCE RATIO	TCR TRACKING	TOLERANCE	
				ABSOLUTE	MATCH
DSM	$\pm 2 \text{ ppm/}^{\circ}\text{C} \pm 3 \text{ ppm/}^{\circ}\text{C}$	R1/R2 = 1	1.0 ppm/°C	$\pm 0.02 \%$	0.01 %
		$1 < R1/R2 \leq 10$	2.0 ppm/°C	$\pm 0.05 \%$	0.02 %
		$10 < R1/R2 \leq 120$	3.0 ppm/°C	$\pm 0.1 \%$	0.05 %

\* Pb containing terminations are not RoHS compliant, exemptions may apply


**FIGURE 2 - POWER DERATING CURVE****FIGURE 3 - RECOMMENDED LAND****FIGURE 4 - TRIMMING TO VALUES**  
(Conceptual Illustration)**FIGURE 5 - TYPICAL RESISTANCE/TEMPERATURE CURVE**  
(For more details, see table 1)**FIGURE 6 - DIMENSIONS AND IMPRINTING**

**TABLE 3 - PERFORMANCE SPECIFICATIONS** (Test Method Per MIL-PRF-914)

SPECIFICATIONS	TYPICAL LIMITS
<b>Power Rating</b> at 70 °C	Entire package: 0.1 W Each resistor: 0.05 W
<b>Maximum Working Voltage</b> (each resistor)	25 V
<b>Working Temperature Range</b>	- 65 °C to + 125 °C
<b>Thermal Shock</b> 25 x (- 65 °C to + 125 °C)	ΔR = 0.01 % (100 ppm) ΔRatio = 0.005 % (50 ppm)
<b>Thermal Shock</b> 5 x (- 65 °C to + 125 °C) and <b>Power Conditioning</b> 1.5 rated power at 25 °C, 100 h	ΔR = 0.015 % (150 ppm) ΔRatio = 0.01 % (100 ppm)
<b>DWV</b> atmospheric pressure, 200 V (A.C.), 1 min	Successfully passed
<b>Insulation Resistance</b> 100 V (D.C.), 1 min	> 10 <sup>4</sup> MΩ
<b>Resistance to Soldering Heat</b>	ΔR = 0.01 % (100 ppm) ΔRatio = 0.005 % (50 ppm)
<b>Moisture Resistance</b> + 65 °C to - 10 °C; 90 % to 98 % RH; 0.1 x rated power, 240 h	ΔR = 0.02 % (200 ppm) ΔRatio = 0.005 % (50 ppm)
<b>Shock (Specified Pulse)</b> 100 G	ΔR = 0.005 % (50 ppm) ΔRatio = 0.0025 % (25 ppm)
<b>Vibration, High Frequency</b> (10 Hz to 2000 Hz), 20 G	ΔR = 0.01 % (100 ppm) ΔRatio = 0.005 % (50 ppm)
<b>High Temperature Exposure</b> 100 h at 125 °C	ΔR = 0.01 % (100 ppm) ΔRatio = 0.005 % (50 ppm)
<b>Low Temperature Storage</b> 24 h at - 65 °C	ΔR = 0.005 % (50 ppm) ΔRatio = 0.005 % (50 ppm)
<b>Load Life Stability</b> 2000 h at + 70 °C; rated power	ΔR = 0.005 % (50 ppm) ΔRatio = 0.005 % (50 ppm)
<b>Short Time Overload</b> 6.25 x rated power; 5 s	ΔR = 0.005 % (50 ppm) ΔRatio = 0.0025 % (25 ppm)
<b>Low Temperature Operation</b>	ΔR = 0.005 % (50 ppm) ΔRatio = 0.0025 % (25 ppm)
<b>Weight</b>	0.04 g



**FIGURE 7 - DSM 10K/10K, 20 UNITS, LOAD LIFE** 0.05 W each value, at + 70 °C


**FIGURE 8 - DSM 10K/10K, 20 UNITS, HIGH TEMPERATURE EXPOSURE,**  
100 h at 125 °C, followed by low temperature storage, 24 h at -65 °C



**TABLE 4 - RESISTANCE VALUE CODE LIST FOR POPULAR RATIOS**  
(other values available upon request)

VCODES	R1/R2 RATIO	R1	R2	VCODES	R1/R2 RATIO	R1	R2
V0052	100	10K	100R	V0080		1K	400R
V0065	50	10K	200R	V0081	2.5	500R	200R
		5K	100R	V0082		10K	5K
V0067	25	10K	400R	V0083		2K	1K
		5K	200R	V0084	2	1K	500R
V0069	20	10K	500R	V0085		400R	200R
		2K	100R	V0086		200R	100R
V0070				V0087	1.25	500R	400R
V0071		10K	1K				
V0072	10	2K	200R	V0001		10K	10K
V0073		1K	100R	V0002		5K	5K
V0074	5	5K	1K	V0059		2K	2K
V0075		2K	400R	V0004		1K	1K
V0076		1K	200R	V0091		500R	500R
V0077		500R	100R	V0090		400R	400R
V0246		10K	2K5	V0089		200R	200R
V0078	4	2K	500R	V0088		100R	100R
V0079		400R	100R				

**TABLE 5 - GLOBAL PART NUMBER INFORMATION (1)**
**NEW GLOBAL PART NUMBER: Y1485V0067BA9W (preferred part number format)**

**FOR EXAMPLE: ABOVE GLOBAL ORDER Y1485 V0067 B A 9 W:**
**TYPE: DSM**
**VALUES: 10K/400R**
**ABSOLUTE TOLERANCE: ± 0.1 %**
**TOLERANCE MATCH: 0.05 %**
**AER: standard**
**PACKAGING: waffle pack**
**HISTORICAL PART NUMBER: DSM 10K 400R TCR2 B A W (will continue to be used)**

**Note**

(1) For non-standard requests or additional values, please contact application engineering.

### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.