


MOC3020-MOC3023

Optoisolator
GaAs Infrared Emitting Diode and
Light Activated Triac Driver

The MOC3020-MOC3023 series consists of a gallium arsenide, infrared emitting diode coupled with a light activated silicon bilateral switch, which functions like a triac, in a dual in-line package.


These devices are especially designed for triggering power triacs while maintaining dielectric isolation from the trigger control circuit. They are mounted in dual in-line packages. These devices are also available in surface-mount packaging.



absolute maximum ratings: (25° C)

INFRARED EMITTING DIODE		
Power Dissipation	*100	milliwatts
Forward Current (Continuous)	50	milliamps
Forward Current (Peak) (Pulse width 1µsec 300 pps)	3	amperes
Reverse Voltage	3	volts

*Derate 1.33mW/°C above 25° C ambient.




OUTPUT DRIVER		
Off-State Output Terminal Voltage	400	Volts
On-State RMS Current (Full Cycle Sine Wave, 50 to 60 Hz)	100	milliamps
Peak Nonrepetitive Surge Current (PW = 10 ms, DC = 10°C)	1.2	amperes
Total Power Dissipation @ T _a = 25°C **300		milliwatts

**Derate 4.0 mW/°C above 25°C ambient.

SYMBOL	MILLIMETERS		INCHES		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	5.34	5.59	.180	.250	1
B	7.62 REF		.300 REF		2
C		8.64		.340	2
D	.406	.508	0.16	.200	3
E	1.01	1.27	.040	.070	
F	2.25	2.80	.090	.110	
G		2.16		.085	4
H	.203	.315	.008	.012	
I	2.54		.100		
J		.15		.15	
K	.381		.015		
L		.953		.038	
M	2.92	3.43	.115	.135	
N	0.10	0.30	.004	.012	

- NOTES
1. INSTALLED POSITION LEAD CENTERS
2. OVERALL INSTALLED DIMENSION
3. THESE MEASUREMENTS ARE MADE FROM THE SEATING PLANE
4. FOUR PLACES

TOTAL DEVICE	
Storage Temperature	-55°C to +150°C
Operating Temperature	-40°C to +100°C
Lead Soldering Time (at 260°C)	10 seconds
Isolation Surge Voltage: (Input to Output)	7500VAC (Peak AC Voltage, 60 Hz, 5 second duration)



Covered under U.I. component recognition program, reference file E51868

MOC3020-MOC3023

individual electrical characteristics (25°C)

EMITTER	SYMBOL	TYP.	MAX.	UNITS
Forward Voltage ($I_F = 10 \text{ mA}$)	V_F	1.2	1.5	volts
Reverse Current ($V_R = 3 \text{ V}$)	I_R	-	100	microamps
Capacitance ($V = 0$, $f = 1 \text{ MHz}$)	C_i	50		picofarads

DETECTOR See Note 1	SYMBOL	TYP.	MAX.	UNITS
Peak Off-State Current $V_{DRM} = 400 \text{ V}$	I_{DRM}	—	100	nanoamps
Peak On-State Voltage $I_{FM} = 100 \text{ mA}$	V_{FM}	2.5	3.0	volts
Critical Rate-of-Rise of Off-State Voltage $T_A = 85^\circ\text{C}$	dv/dt	12.0	—	volts $\mu\text{sec.}$

coupled electrical characteristics (25°C)

		SYMBOL	TYP.	MAX.	UNITS
IRED Trigger Current, Current Required to Latch Output (Main Terminal Voltage = 3.0 V, $R_L = 150 \Omega$)	MOC3020	I_{F1}	—	30	milliamps
	MOC3021	I_{F1}	—	15	milliamps
	MOC3022	I_{F1}	—	10	milliamps
	MOC3023	I_{V1}	—	5	milliamps
Holding Current, Either Direction		I_H	100		microamps

NOTE 1: Ratings apply to either polarity of Pin 6 — referenced to Pin 4.
 Voltages must be applied within dv/dt rating.