

Surface Mount Type

Series: **TK** Type: **V**



■ Features

- Endurance : 125 °C 3000 h
- Low ESR at -40 °C (50 % lower than TG series)
- Added ESR specification after the test
- Vibration-proof product is available upon request.
- RoHS directive compliant

■ Specifications

Category Temp. Range	-40 °C to +125 °C					
Rated W.V. Range	10 V.DC to 35 V.DC					
Nominal Cap. Range	47 µF to 470 µF					
Capacitance Tolerance	±20 % (120 Hz/+20 °C)					
DC Leakage Current	I ≤ 0.01 CV After 2 minutes					
tan δ	Please see the attached standard products list					
Characteristics at Low Temperature	W.V. (V)	10	16	25	35	(Impedance ratio at 120 Hz)
	Z(-25 °C)/Z(+20 °C)	3	2	2	2	
	Z(-40 °C)/Z(+20 °C)	4	3	3	3	
Endurance	After the life test with DC rated woking voltage at +125 °C ±2 °C for 3000 hours, the capacitors shall meet the limits specified below.					
	Capacitance change	±30 % of initially measured values (code U : ±35 %)				
	tan δ	≤ 300 % of initially specified values (code U : ±350 %)				
	DC leakage current	≤ initially specified values				
Shelf Life	After storage for 1000 hours at +125 °C±2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance. (With voltage treatment)					
ESR after the Life test	After the life test with DC rated working voltage at +125 °C±2 °C for 3000 hours, ESR value shall meet the specified below.					
	After 1000 hours	20 °C	≤ 150 % of the initially measured specified value.			
		-40 °C	≤ 200 % of the initially measured specified value.			
	After 2000 hours	20 °C	≤ 300 % of the initially measured specified value.			
		-40 °C	≤ 400 % of the initially measured specified value.			
	After 3000 hours	20 °C	≤ 1000 % of the initially measured specified value.			
-40 °C		≤ 1500 % of the initially measured specified value.				

■ Marking

Example: 10 V 220 μF (polarized)
Marking color: BLACK

Rated Voltage Mark	
A	10 V
C	16 V
E	25 V
V	35 V

■ Dimensions in mm (not to scale)

() reference size

(mm)								
Size code	D	L	A,B	H max.	I	W	P	K
F	8.0	10.2	8.3	10.0	3.4	0.90±0.2	3.1	0.70±0.20
G	10.0	10.2	10.3	12.0	3.5	0.90±0.2	4.6	0.70±0.20

■ Standard Products

Endurance : 125 °C 3000 h

W.V. (V)	Cap. (±20 %) (μF)	Case size			Specification			Part No. (RoHS:compliant)	Reflow	Min. Packaging Q'ty
		Dia. (mm)	Length (mm)	*Size Code	Ripple Current (100 kHz) (+125 °C) (mA r.m.s.)	ESR (100 kHz) (+20 °C) (Ω)	tan δ (120 Hz) (+20 °C)			Taping (pcs)
10	220	8	10.2	F	197	0.3	0.30	EEETK1A221P	(8)	500
	330	8	10.2	(F)	197	0.3	0.30	EEETK1A331UP	(8)	500
		10	10.2	G	270	0.2	0.30	EEETK1A331P	(8)	500
	470	10	10.2	(G)	270	0.2	0.30	EEETK1A471UP	(8)	500
16	100	8	10.2	F	197	0.3	0.23	EEETK1C101P	(8)	500
	220	8	10.2	(F)	197	0.3	0.23	EEETK1C221UP	(8)	500
		10	10.2	G	270	0.2	0.23	EEETK1C221P	(8)	500
	330	10	10.2	(G)	270	0.2	0.23	EEETK1C331UP	(8)	500
25	100	8	10.2	F	197	0.3	0.18	EEETK1E101P	(8)	500
	220	8	10.2	(F)	197	0.3	0.18	EEETK1E221UP	(8)	500
		10	10.2	G	270	0.2	0.18	EEETK1E221P	(8)	500
	330	10	10.2	(G)	270	0.2	0.18	EEETK1E331UP	(8)	500
35	47	8	10.2	F	197	0.3	0.16	EEETK1V470P	(8)	500
	100	8	10.2	(F)	197	0.3	0.16	EEETK1V101UP	(8)	500
		10	10.2	G	270	0.2	0.16	EEETK1V101P	(8)	500
	220	10	10.2	(G)	270	0.2	0.16	EEETK1V221UP	(8)	500

* Size code() : Miniaturization product

The taping dimensions are explained on p.177 of our Catalog. Please use it as a reference guide.

Reflow Profile(Fig-1 to Fig-8) listed on p.175 of our Catalog.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[EEE-TK1A221P](#) [EEE-TK1A331P](#) [EEE-TK1A331UP](#) [EEE-TK1A471UP](#) [EEE-TK1C101P](#) [EEE-TK1C221P](#) [EEE-TK1C221UP](#) [EEE-TK1C331UP](#) [EEE-TK1E101P](#) [EEE-TK1E221P](#) [EEE-TK1E221UP](#) [EEE-TK1E331UP](#) [EEE-TK1V101P](#) [EEE-TK1V101UP](#) [EEE-TK1V221UP](#) [EEE-TK1V470P](#)