


125Amp, High-Current, Waterproof Connector

EV Series



■Features

1. High Current Capacity

Rated up to 125 Amps.

2. Waterproof Structure

The EV series is IP67 water resistant in unmated state (when EV1-62RA-3SB, EV1-62RA-2SB is used). It is IP68/X9K water resistant in mated. The use of special rubber component for the internal seals enhance oil and water resistance.

3. Standard Tool for Contact Assembly

Contacts can be crimped using readily available JIS standard tools (JIS C 9711).

4. Downsizing

Staggered panel flange design saves space.

5. Lightweight

The shell is constructed of an aluminum alloy material enabling it to be lightweight.

6. Multi-Point Contact Spring


Highly reliable contact structure allows for a high current capability, guards against vibration to the contact and decreases contact resistance.

7. Shield Design

The metal shell enhances EMI shielding.

8. Touchproof

Contact and connector design protects against accidental electrical shock using IEC 60601 test procedure.



Measurement Condition

The plug has three contacts where 20 mm² electric wires are connected and then covered with a corrugated housing. Measurement was taken by connecting copper bus bars of 3 mm x 12 mm to the three contacts of the receptacle and wiring in series.

Remarks

Derating curve and temperature rise curve changes slightly by a given cable that is being used and slight variations occur under the same conditions. Therefore, the values indicated above are reference values and not guaranteed values.

■Product Specifications

Ratings	Current rating	125A (max. 180A *1) (Per cable specification and derating curve)	Operating Temperature	-40 to +150℃ (Including temperature rise by conduction)
	Voltage rating	AC 460 V, DC 650 V	Storage Temperature Range	-10 to +60℃

Note1: Under the assumption that it is used at normal temperature (20℃±15℃).

Items	Specifications	Conditions
1. Contact resistance	0.5 mΩ or less	Measured at DC 1 A
2. Insulation resistance	1000 MΩ or greater	Measured at DC 500 V
3. Withstanding voltage	No flashover or breakdown	AC 2000 V for 1 min.
4. Vibration resistance	No electric outage of 10 μs or greater	JIS D 1601, Type 3D -Grade 110
5. Shock	No electric outage of 10 μs or greater	Acceleration 490 m/s ² , sustained period 11 ms, Sine wave tests were conducted a total of 18 times, three times each in 6 directions.
6. Temperature cycle	1 mΩ or less Insulation resistance: 100 MΩ or greater	Left for a total of 5 cycles of the following: -40℃: 30 mins. → Normal temperature: 2-3 min. → 150℃: 30 mins. → Normal temperature: 2-3 mins.
7. Humidity resistance	Insulation resistance: 10 MΩ or greater (when highly humid) 100 MΩ or greater (when dry)	Left for 96 hours at temperature 40℃ and humidity 95%.
8. Water proof	IP68 IPX9K	—

■Materials

Part		Materials	Treatment	Remarks
Plug	Outer shell	Aluminum alloy	Nickel plated	—
	Insulator	Polyamide(black)	—	UL94V-0
	Rubber sealant	Hydrogenated nitrile rubber	—	—
	Gasket	Fluorosilicone rubber	—	—
	Hexagonal bolt Hexagonal bolt w/ hole	Copper	Tervalent chromate filming	—
Receptacle	Insulator	Polyamide (black)	—	UL94V-0
	Female contact	Copper Alloy	Silver plated *2	—
	Contact spring	Copper Alloy	Silver plated *2	—
	Rubber ring (O ring)	Hydrogenated nitrile rubber (Fluorosilicone rubber)	—	—
	Hexagonal bolt Hexagonal nut	Copper/Brass Brass	Tervalent chromate filming / Nickel plated Nickel plated	—
Male Contact	Contact	Copper alloy	Silver plated *2	—
	Cap	Polyamide (black)	—	UL94V-0

Note2 : Silver-plated contacts can discolor by reacting to sulfur in the air (formation of silver sulfide coat), however, they can be used without any problem. Contact resistance may increase in an extremely rare case. If it has increased significantly, please check contact resistance before use.

■ Structure of Product Number

● Plug

EV 1 - 62 P * - 3 P C (**)

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

● Receptacle

EV 1 - 62 R * - 3 S B (**)

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

● Male Contact

EV 1 - P C * - 1 1 2 (**)

① ② ⑦ ⑧ ⑤ ⑩ ⑪ ⑫ ⑨

①	Model Name: EV Series
②	Series Number: 1
③	Shell Size: The shell size shows the case width of the plug's mating area or outer diameter.
④	Type of Shell: P: Straight plug R: Straight receptacle
⑤	Symbol for Body Form Type and Applicable Cable Range Type: A: Single unit waterproof receptacle 1: Notched
⑥	Number of Contacts: Number of contacts is indicated.
⑦	Contact Polarity: P: Male Contact S: Female Contact
⑧	Cable Termination Method: None: Solder termination B: Termination by screw clamping C: Crimp Termination
⑨	Other Specifications: Two-digit figures will be added if changes other than the above are made in the specifications.
⑩	Contact Type: 1: Loose piece contacts
⑪	Contact Form, Size: Serial numbers (1,2,3, ...) will be changed.
⑫	Plating Specification: 2: Silver plated

◆Contact Extraction Tool



◆Manual Oil Pressure Crimping Tool




◆Electric Oil Pressure Crimping Tool



◆Panel cut out Dimensions for Plug and Receptacle

Recommended Panel cut out Dimensions



Remarks: The dimensions of the panel mounting hole are the dimensions when seen from the plug mating side.

◆PRECAUTIONS

1. Always make sure to turn the power off before inserting or extracting the connectors.
2. Always check the condition of the connectors and terminals for damage or debris before mating.
3. Use of non-recommended wire can affect the performance. Only use the recommended cables to maintain waterproof performance, shielding performance and cable crimping strength.
4. Please contact a Hirose sales representative for the harnessing procedure.



HIROSE ELECTRIC CO.,LTD.

2-6-3,Nakagawa Chuoh,Tsuzuki-Ku,Yokohama-Shi 224-8540,JAPAN
 TEL: +81-45-620-3526 Fax: +81-45-591-3726
<http://www.hirose.com>
<http://www.hirose-connectors.com>