

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

H

UPDATE PER ECO-11-013056

23 JUN 11

CAS

MKS

SUGGESTED PANEL CUT-OUT

2X R.063

ø.440

.420±.002

WIRE LENGTH SPECIFIED IN NANONICS PART NUMBER

.550

.065

.350

ø.395±.005

.060

M11.0 X 0.75-6g THREAD

.125 MAX PANEL THICKNESS FOR THREADED COUPLING

.250 MAX PANEL THICKNESS FOR QUICK DISCONNECT

HEX FLANGE AND JAM NUT

.563

(.650)

O-RING SEAL

JAM NUT

.414

POSITION 1

POSITION 6

POSITION 12

POSITION 19

POSITION 27

POSITION 34

POSITION 40

1 CONNECTOR BODY AND JAM NUT MATERIAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E  
LOCKING RING MATERIAL: BERYLLIUM COPPER, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E  
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138 OR POLYPHENYLENE SULFIDE (PPS) PER ASTM D4067  
O-RING MATERIAL: FLUOROSILICONE

2 WIRE TERMINATION: 28 AWG SOLID, 30 AWG STRANDED WIRE OR SMALLER

3 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION

4 THIS DRAWING PREVIOUSLY IDENTIFIED AS NANONICS 303-0031

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± .010

3 PLC ± .005

4 PLC ± -

ANGLES ± 1°

MATERIAL SEE NOTES

FINISH SEE NOTES

DWN M. STORRY 23 APR 99

CHK E. PAULUS 7 MAY 99

APVD S. KAIN 27 JAN 00

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

RECEPTACLE ASSEMBLY, CIRCULAR, PANEL MOUNT, THREADED COUPLING/ QUICK DISCONNECT, METAL, 44 POSITION

SIZE A2

CAGE CODE 0PJN9

DRAWING NO C=1589062

RESTRICTED TO -

SCALE 5:1

SHEET 1 of 1

REV H

1589062

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[QCM044SC0DM060P](#)