




SULLINS ELECTRONICS CORP

SAN MARCOS, CA 760-744-0125 FAX 760-744-6081



A =	3.600+- .020	[91.44+-0.51]
B =	3.500+- .008	[88.90+-0.20]
C =	0.100+- .003	[2.54+-0.08]
D =	0.100+- .005	[2.54+-0.13]
E =	0.050+- .005	[1.27+-0.13]
F =	0.318+- .015	[8.08+-0.38]
G =	0.100+- .005	[2.54+-0.13]
H =	0.320+- .015	[8.13+-0.38]

**.025[0.64] SQUARE POSTS FIT .040[1.02] MINIMUM DIAMETER HOLE**

- 1.0 SPECIFICATIONS FOR A SINGLE ROW 36 POSITION HEADER
- 2.0 INSULATOR MATERIAL: BLACK THERMOPLASTIC POLYESTER
- 3.0 CONTACT MATERIAL: CA510, PHOSPHOR BRONZE GRADE A
- 4.0 PLATING: .000100" TIN OVERALL, .000050" NICKEL UNDERPLATE
- 5.0 TEMPERATURE: TO 125 DEGREES C CONTINUOUS
- 6.0 UL FLAMMABILITY RATING: 94V-0
- 7.0 VOLTAGE RATING: 600 VDC MINIMUM AT SEA LEVEL
- 8.0 CURRENT RATING: 3 AMPERES
- 9.0 INSULATION RESISTANCE: 5,000 MEGA OHMS
- 10.0 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- 11.0 NOT DRAWN TO SCALE

SULLINS PART NUMBER: PTC36SFCN**DATE: 1-23-03**[Print PDF](#)