Molex.com

English 타호령 Register | Login で 管体中文 My Parts (0 items)

Search site:Search: Enter Part No. or K Go **Product Name** Cross-Ref

Catalog Literature

Industries

Standards

Contact Us

About Us

Investors

Careers

Switch Language

English

Need Assistance?

Contact Us Find a Distributor **Order Samples Tech Library** Ecocare Electrical Models

Printer-friendly page

Email this page

Home

Quick Disconnects

Datasheet

Part Number:

0190080027

Status:

Active

Description:

Flag Krimptite™ Quick Disconnect, Female, for 14-16 (2.00-1.30) Wire, Mylar Tape, Tab 6.35mm (.250") x 0.81mm (.032

Documents: Note - Please disable browser pop-up blockers for documents on www.molex.com

Drawing (PDF) Datasheet (PDF) Series image - Reference only

RoHS

EU RoHS ELV and RoHS Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free Status

Halogen-Free



Molex Connector Part Nur	nber - 0190080027	
		Need more infor environmental c
		Email producted
		For a multiple part Compliance, click h
		Please visit the Corproduct compliance
		Search Parts i
		<u>19008</u> Series
		Application To
		Tooling specifica
		found by selecting Crimp Height Sp
		contained in the

rmation on product compliance?

ompliance@molex.com

number RoHS Certificate of

ntact Us section for any none questions.

in this Series

ooling | FAQ

ations and manuals are ing the products below. pecifications are then Application Tooling Specification document.

Global

Description

Product #

Page 2 of 4

ATP Perishable Tool Kit 0190270085 used in ATP presses that process product on tape

Crimp Quality Equipment

Molex also offers wire strippers, pull testers, shut-height gauges, micrometers and more

Click here for details

Certificate of Compliance (PDF)

Order Products:

Part Detail: (show all)

GeneralPhysicalElectricalAgency CertificationMaterial InfoReference - Drawing Numbers

_				
(-	Δ	n	Δ	ra

Product Family	Quick Disconnects
Series	<u>19008</u>
Product Name	Krimptite™
Туре	Quick Disconnect

Physical

3	
Barrel Type	Closed
Gender	Female
Glow-Wire Compliant	No
Insulation	None
Lock to Mating Part	None
Material - Metal	Brass
Orientation	Flag
Packaging Type	Adhesive Tape on Reel
Polarized to Mating Part	No
Tab Thickness	0.81mm (.032")
Tab Width	6.35mm (.250")
Temperature Range - Operating	Per Wire Specification
Termination Interface: Style	Crimp or Compression
Wire Size AWG	14, 16
Wire Size mm²	1.30 - 2.00

Electrical(Please review the Product Specification for specific details.)

Voltage - Maximum Per Wire Specification

Agency Certification

CSA LR18689 UL E79133

Material Info

Old Part Number BB-1159T

Reference - Drawing Numbers

Sales Drawing CDFG250, SD-19008-013

● Find us on:

Privacy Legal Site Map Help

Page 4 of 4

Copyright 2005-2010