Product data sheet Characteristics

XS7C40FP260

inductive sensor XS7 40x40x117 - plastic - Sn15mm - 24..240VAC - terminals



Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS7
Sensor design	Form 40 x 40 x 117
Size	117 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Plastic
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	2-wire
[Sd] sensing range	> 815 mm
[Sn] nominal sensing distance	15 mm
Discrete output function	1 NO or 1 NC programmable
Output circuit type	AC
Electrical connection	Screw-clamp terminals, clamping capacity: 2 x 1.5 mm ²
[Us] rated supply voltage	24240 V AC 50/60 Hz
Switching capacity in mA	5500 mA
IP degree of protection	IP67 conforming to IEC 60529

Complementary

Complementary		
Detection face	5 positions turret head	
Operating zone	012 mm	
Differential travel	320% of Sr	
Repeat accuracy	<= 3% of Sr	
Cable entry	1 entry tapped for Pg 13.5 cable gland	
Status LED	1 LED yellow for output state	
Supply voltage limits	20264 V AC	
Residual current	<= 1.5 mA for open state	
Switching frequency	<= 25 Hz	
Voltage drop	<= 5.5 V at closed state	
Delay first up	<= 120 ms	
Delay response	<= 30 ms	
Delay recovery	<= 20 ms	
Marking	CE	
Height	117 mm	
Width	40 mm	
CAD overall height	117 mm	
CAD overall depth	41 mm	
Product weight	0.22 kg	
· 		

Environment

Product certifications	CCC CSA C-Tick UL
Ambient air temperature for operation	-2570 °C
RoHS EUR status	Compliant
RoHS EUR conformity date	0836



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric:

XS7C40FP260 XS7C40FP260H7 XS7V12NA332S XS7E1A1DBL5 XS7C40NC449H7 XS7C40MP230TT

XS7C40FP260TT XS7C40PC440H29 XS7T4NC440 XS7C40FP260R30 XS7T4DA214LD XS7C40NC440

XS7F1A1DBL5 XS7C40DA210 XS7T4DA214LD01 XS7H10PA340 XS7C40DP210 XS7J1A1NAL5 XS7D1A1DBL5

XS7C40DP210H29 XS7C40NC440H7 XS7C40MP230H29 XS7C40NC440H29 XS7C40PC440H7 XS7C1A1DBL10

XS7C40PC440D XS7C40NC440TT XS7T4PC440LD01 XS7C40FP260H29 XS7T4PC440LD XS7C40PC440TF

XS7C40PC449 XS7C40MP230K30 XS7C40MP230TF XS7C40NC449 XS7T4DA210 XS7T4PC440 XS7C40KPM40

XS7C40KPM40H7 XS7C40MP230H7