


ESCC (e) 4001/023 Qualified R Failure Rate High Precision (10 ppm/°C, 0.05 %) Thin Film Chip Resistors



Vishay Sfernice Thin Film division holds ESCC QML qualification (ESCC technology flow qualification).

These HiRel components are ideal for low noise and precision applications, superior stability, low temperature coefficient of resistance, and low voltage coefficient, Vishay Sfernice's precision thin film wraparound resistors exceed requirements of MIL-PRF-55342G characteristics Y (± 10 ppm/°C).

FEATURES

**HALOGEN
FREE**

- Load life stability at ± 70 °C for 2000 h: 0.25 % under Pn
- Temperature coefficient to: 10 ppm/°C
- Very low noise (< -35 dB) and voltage coefficient (< 0.01 ppm/V)
- Resistance range: 100 Ω to 3.01 M Ω (depending on size)
- Tolerances down to 0.05 %
- SnPb terminations over nickel barrier
- ESCC 4001 (generic specification)
- ESCC 4001/023 (detail specification)
- ESCC qualified
- R failure rate (0.01 % per 1000 h)
- SMD wraparound chip resistor
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	SIZE	ESCC VARIANT NUMBER	RESISTANCE RANGE Ω	RATED POWER AT + 70 °C (Pn) W	LIMITING ELEMENT VOLTAGE (UL) V	INSULATION VOLTAGE (U _i) V	TOLERANCE \pm %	TEMPERATURE COEFFICIENT \pm ppm/°C
PFRR 0402 (e)	0402	15	100 to 150K	0.05	30	40	0.05, 0.1	10, 25
PFRR 0603 (e)	0603	09	100 to 500K	0.1	50	100	0.05, 0.1	10, 25
PFRR 0805 (e)	0805	10	100 to 750K	0.125	100	200	0.05, 0.1	10, 25
PFRR 1206 (e)	1206	11	100 to 3.5M	0.25	150	300	0.05, 0.1	10, 25
PFRR 2010 (e)	2010	12	100 to 6M	0.50	200	300	0.05, 0.1	10, 25

CLIMATIC SPECIFICATIONS


Operating temperature range	-55 °C; +155 °C
Soldering temperature (T _{sol})	260 °C, immersion 10 s

MECHANICAL SPECIFICATIONS


Substrate material	Alumina
Technology	Thin Film
Film	Nickel Chromium with mineral passivation
Protection	Epoxy and Silicon
Terminations	B type: SnPb over nickel barrier for solder reflow

QUALIFIED OHMIC RANGE: MAX. VALUE

PFRR0402	PFRR0603	PFRR0805	PFRR1206	PFRR2010
100 k Ω	261 k Ω	301 k Ω	1 M Ω	3.01 M Ω

DIMENSIONS in millimeters


VARIANT NUMBER	STYLE	A		B		C		D		E	
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
09	0603	1.39	2.16	0.62	1.01	0.25	1.02	0.17	0.51	0.25	0.51
10	0805	1.78	2.55	1.14	1.53	0.25	1.02	0.17	0.51	0.25	0.51
11	1206	2.87	3.64	1.47	1.86	0.25	1.02	0.17	0.51	0.25	0.51
12	2010	4.95	5.72	2.41	2.8	0.25	1.02	0.35	0.85	0.35	0.85
15	0402	0.87	1.64	0.47	0.86	0.25	1.02	0.09	0.38	0.12	0.38

LAND PATTERN DIMENSIONS in millimeters


CHIP SIZE	Z _{max.}	G _{min.}	X _{max.}
0402	1.55	0.15	0.73
0603	2.37	0.35	0.98
0705/0805	2.76	0.74	1.40
1206	3.91	1.85	1.73
2010	5.93	3.71	2.67

Note

- Suggested land pattern: According to IPC-7351

TRACEABILITY DEFINITIONS

The two major traceability elements are defined as:

- The primary process lot number named Front End lot (FE lot). One "FE lot" is composed of several wafers issued from the same thin film deposition sequence.
- The date code named Batch Number (BN). The "BN" is defined after completion of the end of production testing sequence.

The lot homogeneity is given by the "FE lot" and not by the "BN".

According to the applied rules validated by the ESCC through the product qualification, the following situations are agreed:

- Parts coming from different "FE lot" might have the same "BN".
- A maximum of two different "BN" might be applied to the same "FE lot" to enable the use of overruns from a previous PO.
- Unless requested / approved by the customer the "BN" will be 2 years old maximum.

SPECIFIC TRACEABILITY REQUIREMENTS

The following specific requirements have to be treated as:

- A customer who requires "Lot Homogeneity" has to mention it on the PO as "SINGLE PRODUCTION LOT".
- A customer who requires "Lot Homogeneity" in addition to a "Single Batch Number" has to mention it on the PO as "SINGLE PRODUCTION LOT AND OPTION R0101".

END OF PRODUCTION TESTING

Mandatory testing performed at the end of the production process:

- 100 % overload: Voltage $\sqrt{(6.25 P_n \times R_n)}$ or $2 U_L$ whichever is less - duration 2 s

**GLOBAL PART NUMBER INFORMATION**

New Global Part Numbering: PFRR0603Y1003BBT (preferred part number format)

P	F	R	R	0	6	0	3	Y	1	0	0	3	B	B	T
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

TYPE

PFRR0402
PFRR0603
PFRR0805
PFRR1206
PFRR2010

TCR

Y = ± 10 ppm/ $^{\circ}$ C
E = ± 25 ppm/ $^{\circ}$ C

OHMIC
VALUE

The first three digits are significant figures and the last digit specifies the number of zeros to follow.
Example:

3901 = 3900 Ω
1004 = 1 M Ω

TOLERANCE

W = ± 0.05 %
B = ± 0.10 %

TERMINATION

B: SnPb over nickel barrier

PACKAGING

For more information see Codification of Packaging table

CODIFICATION OF PACKAGING

CODE 18	PACKAGING
WAFFLE PACK	
W	100 min., 1 mult
WA	100 min., 100 mult (available only in size 1206)
PLASTIC TAPE (in standard for all sizes except 0402)	
T	100 min., 1 mult
TA	100 min., 100 mult
TB	250 min., 250 mult
TC	500 min., 500 mult
TD	1000 min., 1000 mult
TE	2500min., 2500 mult
TF	Full tape (quantity depending on size of chips)
PAPER TAPE (in standard for 0402, option for other sizes)	
PT	100 min., 1 mult
PA	100 min., 100 mult
PB	250 min., 250 mult
PC	500 min., 500 mult
PD	1000 min., 1000 mult
PE	2500min., 2500 mult
PF	Full tape (quantity depending on size of chips)

GLOBAL PART NUMBER INFORMATION

ESCC Code

4	0	0	1	0	2	3	0	9	R	1	0	0	3	B	1
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

ESCC SPEC

4001023

VARIANT

0402 = 15
0603 = 09
0805 = 10
1206 = 11
2010 = 12

FAILURE RATE

R

OHMIC VALUE

The first three digits are significant figures and the last digit specifies the number of zeros to follow.

Example:
3901 = 3900 Ω
1004 = 1 M Ω

TOLERANCE

W = ± 0.05 %
B = ± 0.10 %

TCR

1 = ± 10 ppm/ $^{\circ}$ C
2 = ± 25 ppm/ $^{\circ}$ C



Vishay Sfernice thin film is the first passive manufacturer to hold the ESCC Technology Flow Qualification, official certificate is available on ESCIES web site <https://escies.org/ReadArticle?docId=727>.

This qualification open the door to a new concept at ESA: The Failure Rate option (similar to the one offered in the MIL system), for instance R failure rate: 0.01 % per 1000 h.

New specifications describing this new concept have been released by the ESA:

2544001: Requirements for the Technology Flow Qualification of Film Resistors

<https://escies.org/escs/specifications/2544001.pdf>

26000: Failure Rate Level Sampling Plans and Procedures

<https://escies.org/escs/specifications/26000.pdf>

21300: Terms, Definitions, Abbreviations, Symbols and Units
<https://escies.org/escs/specifications/21300.pdf>

21700: General Requirements for the Marking of the ESCC Components

<https://escies.org/escs/specifications/21700.pdf>

4001: Generic Specification Resistors Fixed Film

<https://escies.org/escs/specifications/4001.pdf>

4001023: Resistors, Fixed, Chip, Thin Film, Type PHR and PFRR

<https://escies.org/escs/specifications/4001023.pdf>

Parts are delivered with space C.O.C.

Parts undergo 100 % overload at end of production process.

ESCC/PFRR CODIFICATION CORRESPONDANCE TABLES

VARIANT	MODEL	CASE SIZE	TERMINATION
15	PFRR	0402	B (tin/lead)
09	PFRR	0603	B (tin/lead)
10	PFRR	0805	B (tin/lead)
11	PFRR	1206	B (tin/lead)
12	PFRR	1210	B (tin/lead)

TEMPERATURE COEFFICIENT	ESCC CODE	PFRR CODE
10 ppm/°C (- 55 °C; + 155 °C)	1	Y
25 ppm/°C (- 55 °C; + 155 °C)	2	E


TOLERANCE	MODEL	CASE SIZE
0.1 %	B	B
0.05 %	W	W

PACKAGING

Two types of packaging are available: waffle-pack and tape and reel.

SIZE	NUMBER OF PIECES PER PACKAGE		TAPE WIDTH	
	WAFFLE PACK 2" x 2"	TAPE AND REEL		
		MIN.		MAX.
0402	340	100	5000	8 mm
0603	100		4000	
0805				
1206				
2010				

POWER DERATING CURVE



EXTENDED FEATURES

You may consult Vishay Sfernice for chip sizes, ohmic values and tolerances outside of the qualified range.



PERFORMANCE				
TEST	CONDITIONS	REQUIREMENTS		TYPICAL
		ESA/SCC 4001/023	MIL-PRF-55342G	
Short time overload	$U = \sqrt{(6.25 \text{ Pr} \times \text{Rn})}$ $U_{\text{max.}} < 2 \text{ UL} - 2 \text{ s}$	$\pm 0.05 \% + (0.05 \Omega \times 100/\text{Rn})$	0.10 %	$\pm 0.01 \%$
Rapid temperature change	- 55 °C/+ 155 °C 5 cycles CEI 66-2-14 Test Na	$\pm 0.05 \% + (0.05 \Omega \times 100/\text{Rn})$	0.1 % (for 100 cycles)	$\pm 0.01 \%$ $\pm 0.015 \% \text{ (for 500 cycles)}$
Soldering (thermal shock)	260 °C/10 s CEI 68-2-20 A Test T6 (met. 1A)	$\pm 0.05 \% + (0.05 \Omega \times 100/\text{Rn})$	-	$\pm 0.005 \%$
Terminal strength: Adhesion bend strength of end plated facing	CEI 115-1 Clause 4.32 CEI 115-1 Clause 4.33	$\pm 0.05 \% + (0.05 \Omega \times 100/\text{Rn})$	-	$\pm 0.01 \%$
Climatic sequence	CEI 67-2-1/CEI 68-2-2 CEI 67-2-13/CEI 68-2-30	$\pm 0.10 \% + (0.05 \Omega \times 100/\text{Rn})$	-	$\pm 0.02 \%$ Insulation resistance > 1 GΩ
Load life	2000 h Pr at + 70 °C 90°/30° cycle 8000 h	$\pm 0.25 \% + (0.05 \Omega \times 100/\text{Rn})$ 1 % + (0.05 Ω x 100/Rn)	0.5 %	$\pm 0.05 \%$ (8000 h) Insulation resistance > 1 GΩ
High temperature exposure	2000 h Pr at + 155 °C CEI 68-2-20A Test B	$\pm 0.15 \% + (0.05 \Omega \times 100/\text{Rn})$	$\pm 0.10 \%$ (duration 1000 h)	$\pm 0.05 \%$ Insulation resistance > 1 GΩ



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.