


2- and 4-Post Premier Aluminum Distribution Racks

**Tough racks with
a high-grade finish,
choice of three
heights, and extensive
management options.**



FEATURES

- » Sturdy aluminum racks support up to 1000 pounds.
- » Racks feature standard 19" rails with prethreaded 12-24 EIA holes.
- » Shelves hold equipment that's not rackmountable.
- » Cable Managers keep your cables hidden, protected, and organized.

OVERVIEW

For the ultimate in flexibility and durability, choose [2- and 4-Post Premier Aluminum Distribution Racks](#) and Cable Managers from Black Box.

These EIA standard 19" distribution racks are constructed of high-strength aluminum for lightweight strength—the racks support up to 1000 pounds—and have excellent grounding characteristics.

The 2-post distribution racks are available in black powdercoated aluminum finish in 72", 84", 96", and 108" heights and mill finish (natural aluminum) in 72" and 84" heights. The 4-post distribution racks are available in black finish in 96" and 108" heights. For both 2- and 4-post racks, the 5/8", 3/8", 1/2" mounting-hole pattern fits all EIA standard equipment.

The racks are easy to assemble, and they're self-squaring and self-supporting.

And to accommodate your non-rackmountable equipment, shelves are available for our Premier Aluminum Distribution Racks. Like our racks, these shelves are sturdily constructed to withstand hard use. Each single shelf supports up to 50 pounds (22.7 kg); each double shelf supports up to 125 pounds (56.7 kg). Choose from single- or double-sided shelves with or without vents.

For applications that require a great deal of cabling, add Premier Cable Managers to your distribution rack. These cable managers enable you to run your cables neatly up the sides of the distribution rack. They protect your cables from the inadvertent snags and bumps that can lead to connection failure.

Cable Managers are easy to install—all the hardware you need is included. And with their large, grommeted holes for cable pass-through and latches to separate and hold cabling, they're easy to use, too.

Optional Hinged Plexi Doors cover the Cable Managers to protect your cabling.

Premier Aluminum Distribution Racks

- Support up to 1000 pounds.
- Constructed of high-grade 6061-T6 aluminum.
- Self-squaring and self-supporting.
- Have 3" x 1 1/4" channels.
- Feature a 5/8", 3/8", 1/2" universal mounting hole pattern.
- Include 24 cross-recessed black panel mounting screws, 12-24 x 1/2" long.
- Add Premier Cable Managers (RM122–RM125, RM128–RM133) for additional cable management.
- Prethreaded 12-24 EIA holes for quick assembly.
- Equipped with 1/2" junctioning holes for securing multiple rack lineups.
- Brushed aluminum mill or black powdercoat finish.
- Standard 19" rails.
- 2-post rack is available in 72", 84", 96", and 108" heights.
- Select 4-post racks in 96" or 108" heights.

Premier Rack Shelves

- Constructed of 11-gauge aluminum.
- EIA standard.
- UL® approved.
- Double-sided shelves consist of a pair of shelves that join in the center of the rack.
- Aluminum mill finish.
- Choose from solid or vented shelves.

Premier Cable Managers

- Heavy-gauge aluminum construction.
- Fit our Premier Aluminum Distribution Racks.
- Conceal and protect cables.
- Large grommeted holes provide easy pass-through for cables.
- Latches hold and separate wiring.
- Protective edge guards and all assembly hardware included.
- Choose from aluminum mill or black powdercoat finish.
- Narrow and wide styles available.
- Optional Plexi Covers feature an easy-to-use latch and slip hinges to make cover removal simple.

Plexi Covers

- Smoke-gray, acrylic covers give your cable managers a neat, sleek appearance while protecting your cable runs.
- Feature integrated slip hinges, which make it simple to remove the cover for complete cable access.
- A latch secures the cover to keep cables protected.



RM135:
Width — 19" (48.3 cm)
Depth — 15" (38.1 cm)
Capacity — 50 lb. (22.7 kg)

RM136:
Width — 19" (48.3 cm)
Depth — 10.8" (27.4 cm)
Capacity — 125 lb. (56.7 kg)

RM137:
Width — 19" (48.3 cm)
Depth — 15" (38.1 cm)
Capacity — 50 lb. (22.7 kg)

RM138:
Width — 19" (48.3 cm)
Depth — 10.8" (27.4 cm)
Capacity — 125 lb. (56.7 kg)

RM122:
Height — 84" (213.4 cm)
Channel Width — 3" (7.6 cm)
Weight — 25 lb. (11.3 kg)

RM123:
Height — 84" (213.4 cm)
Channel Width — 6" (15.2 cm)
Weight — 26 lb. (11.8 kg)

RM128:
Height — 84" (213.4 cm)
Channel Width — 3" (7.6 cm)
Weight — 25 lb. (11.3 kg)

RM129:
Height — 84" (213.4 cm)
Channel Width — 6" (15.2 cm)
Weight — 26 lb. (11.8 kg)

RM124:
Height — 84" (213.4 cm)
Channel Width — 3" (7.6 cm)
Weight — 26 lb. (11.8 kg)

RM125:
Height — 84" (213.4 cm)
Channel Width — 6" (15.2 cm)
Weight — 27 lb. (12.2 kg)

RM130:
Height — 84" (213.4 cm)
Channel Width — 3" (7.6 cm)
Weight — 26 lb. (11.8 kg)

RM131:
Height — 84" (213.4 cm)
Channel Width — 6" (15.2 cm)
Weight — 27 lb. (12.2 kg)

RM132:
Height — 84"H (213.4 cm)
Channel Width — 3" (7.6 cm)
Weight — 5 lb. (2.3 kg)

RM133:
Height — 84" (213.4 cm)
Channel Width — 6" (15.2 cm)
Weight — 6 lb. (2.7 kg)

TECH SPECS

RM155A-R2:
Overall Height — 72" (38U)
Exterior Width — 19" (48.3 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 15" (38.1 cm)
Weight — 27.5 lb. (12.5 kg)

RM156A-R3:
Overall Height — 84" (45U)
Exterior Width — 20.3" (51.6 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 14" (35.6 cm)
Weight — 30.2 lb. (13.7 kg)

RM161A-R3:
Overall Height — 72" (38U)
Exterior Width — 19" (48.3 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 15" (38.1 cm)
Weight — 27.5 lb. (12.5 kg)

RM162A-R3:
Overall Height — 84" (45U)
Exterior Width — 19" (48.3 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 15" (38.1 cm)
Weight — 30.2 lb. (13.7 kg)

RM251A:
Overall Height — 96" (58U)
Exterior Width — 20.3" (51.6 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 14" (35.6 cm)
Weight — 27.5 lb. (12.5 kg)

RM252A:
Overall Height — 108" (45U)
Exterior Width — 20.3" (51.6 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 14" (35.6 cm)
Weight — 31 lb. (14.1 kg)

RM253A:
Overall Height — 96" (51U)
Exterior Width — 20.3" (51.6 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 40" (101.6 cm)
Weight — 70 lb. (31.8 kg)

RM254A:
Overall Height — 108" (58U)
Exterior Width — 20.3" (51.6 cm)
Interior Width — 17.8" (45.2 cm)
Hole-to-Hole Centers — 18.3" (46.5 cm)
Base Depth — 40" (101.6 cm)
Weight — 73 lb. (33.2 kg)

Item	Code
2-Post Premier Aluminum Distribution Racks	
Mill Finish	
72" (38U), 19"W	RM155A-R2
84" (45U), 19"W	RM156A-R3
Black Finish	
72" (38U), 19"W	RM161A-R3
84" (45U), 19"W	RM162A-R3
96" (51U), 19"W	RM251A
108" (58U), 19"W	RM252A
4-Post Premier Aluminum Distribution Racks	
Black Finish	
96" (51U), 19"W	RM253A
108" (58U), 19"W	RM254A
Premier Rack Shelves	
Mill Finish	
Solid	
Single-Sided	RMT135
Double-Sided	RMT136
Vented	
Single-Sided	RMT137
Double-Sided	RMT138

Item	Code
Premier Cable Managers, 84"	
Single-Sided	
Mill Finish	
3" Channel	RM122
6" Channel	RM123
Black Finish	
3" Channel	RM128
6" Channel	RM129
Double-Sided	
Mill Finish	
3" Channel	RM124
6" Channel	RM125
Black Finish	
3" Channel	RM130
6" Channel	RM131
Hinged Plexi Doors, 84"	
Smoked Plastic	
3" Channel	RM132
6" Channel	RM133