




SULLINS ELECTRONICS CORP


SAN MARCOS, CA 760-744-0125 FAX 760-744-6081



A	=	0.400+- .020	[10.16+-0.51]
B	=	0.300+- .008	[7.62+-0.20]
C	=	0.100+- .003	[2.54+-0.08]
D	=	0.240+- .005	[6.10+-0.13]
E	=	0.050+- .005	[1.27+-0.13]
F	=	0.100+- .005	[2.54+-0.13]
G	=	0.230+- .015	[5.84+-0.38]
H	=	0.100+- .005	[2.54+-0.13]
I	=	0.060+- .005	[1.52+-0.13]
J	=	0.100+- .005	[2.54+-0.13]
K	=	0.100+- .015	[2.54+-0.38]



.025[0.64] SQUARE POSTS FIT .040[1.02] MINIMUM DIAMETER HOLE



Right angle bent tails not shown in bottom view

- 1.0 SPECIFICATIONS FOR A DUAL 4/8 POSITION HEADER
- 2.0 INSULATOR MATERIAL: BLACK THERMOPLASTIC POLYESTER
- 3.0 CONTACT MATERIAL: CA510, PHOSPHOR BRONZE GRADE A
- 4.0 PLATING: .000100" TIN OVERALL, .000050" NICKEL UNDERPLATE
- 5.0 TEMPERATURE: TO 125 DEGREES C CONTINUOUS
- 6.0 UL FLAMMABILITY RATING: 94V-0
- 7.0 VOLTAGE RATING: 600 VDC MINIMUM AT SEA LEVEL
- 8.0 CURRENT RATING: 3 AMPERES
- 9.0 INSULATION RESISTANCE: 5,000 MEGA OHMS
- 10.0 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- 11.0 NOT DRAWN TO SCALE

SULLINS PART NUMBER: PTC04DBAN

DATE: 1-29-03

[Print PDF](#)