



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Power Distribution Unit (PDU) - Accessory adds additional outlet types to dual voltage UPS System

MODEL NUMBER: **PDU6K**

Description

Tripp Lite's PDU6K AC power distribution unit offers 24 amp, 240/120V capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 2U rackmount installation. Detachable flanges allow user configuration in dozens of potential mounting schemes. Includes 8 outlets total (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R), with NEMA L14-30P input plug. 4 ft. AC input cord.

PLUG/OUTLETS: Input: NEMA L14-30P/Output: 1 L5-30, 1 L5-20, 2 L6-30, 2 L6-20, 2 6-20R

ELECTRICAL: 240V AC input, 240/120V AC output

FORMAT: Supports 19 in. rackmount (2U), wallmount and under-counter

Features

- Corded AC power distribution unit with 8 output receptacles
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19 inch rackmount mounting in 2U format
- 4 120V and 4 240V output receptacles (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R)
- 4 ft. AC cord with L14-30 plug-in connection
- Removable plug enables hardwire input connection

Highlights

- 8 outlet PDU system adds 240 and 120V output receptacles to select dual voltage 240/120V UPS systems
- Includes 4 ft. cord with L14-30 plug
- Input plug supports hardwire input connection
- Supports installation in 2U rackmount, wallmount and under-counter applications

Package Includes

- PDU6K rackmount power strip
- Instruction manual

Specifications

OUTPUT	
Circuit Breaker (amps)	20
Overload Protection	20A resettable double pole breaker
INPUT	
Input Connection Type	Nema L14-30 input plug, removable for 4 wire hardwire installation
Input Cord Length (ft.)	4
Input Cord Length (m)	1.2
Voltage Compatibility (VAC)	240
PHYSICAL	
Shipping Dimensions (hwd / in.)	6.5 x 18.25 x 8.25
Shipping Dimensions (hwd / cm)	16.5 x 46.4 x 21
Shipping Weight (lbs.)	8
Shipping Weight (kg)	3.6



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Unit Dimensions (hwd / in.)	3.5 x 17.25 x 3.75
Unit Dimensions (hwd / cm)	8.9 x 43.8 x 9.5
Unit Weight (lbs.)	6.25
Unit Weight (kg)	2.8
Material of Construction	Sheet metal
Included Mounting Accessories	Recessed rackmount installation brackets
Receptacle Color	Black
Color (AC Line Cord)	Black
Form Factors Supported	2U rackmount, wallmount, under-counter
CERTIFICATIONS	
Approvals	UL1778 (USA), cUL (Canada), NOM (Mexico)

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<http://www.tripplite.com/products/product-certification-agencies>