

Precision Thin Film Nichrome Chip Resistors

PCF Series

- Precision thin film technology
- Extended ohmic range 1R - 3M
- Precision to $\pm 0.01\%$ and 5ppm/ $^{\circ}\text{C}$
- Passivated range for superior humidity performance
- Load life stability and humidity to 0.05%
- Pb-free standard with SnPb option
- AEC-Q200 grade available



 All Pb-free parts comply with EU Directive 2011/65/EU (RoHS2)

Electrical Data - Standard Range

Type	TCR (ppm/°C)	Power (W)	Limiting Element Voltage (V)	Ohmic Value Range ¹				
				1% & 0.5%	0.25%	0.1%	0.05%	0.01%
PCF0201	50	0.031	15	49R9-33K	-			
	25			49R9-5K				
PCF0402	50	0.063	25	10R-205K		-		
	25							
	15			-		49R9-33K	-	
	10					49R9-12K		
	5					49R9-5K		
PCF0603	50	0.063	50	2R-1M		4R7-1M	4R7-332K	-
	25					4R7-332K		
	15			-		24R9-15K		24R9-100K
	10							
	5							
PCF0805	50	0.1	100	1R-2M		4R7-2M	4R7-511K	-
	25					4R7-511K		
	15			-		24R9-30K ²		24R9-200K
	10							
	5							
PCF1206	50	0.125	150	1R-2M5		4R7-2M5	4R7-511K	-
	25					4R7-1M		
	15			-		24R9-50K ²		24R9-500K
	10							
	5							
PCF1210	50	0.2	150	1R-2M5		4R7-2M5	4R7-1M	-
	25					4R7-1M		
	15			-		24R9-50K ²		24R9-500K
	10							
	5							
PCF2010	50	0.25	150	1R-3M		4R7-3M	4R7-1M	-
	25					4R7-1M		
	15			-		24R9-100K		24R9-500K
	10							
	5							
PCF2512	50	0.5	150	1R-3M		4R7-3M	4R7-1M	-
	25					4R7-1M		
	15			-		24R9-100K		24R9-500K
	10							
	5							

Note 1: Standard values E24 or E96. Other values may be available by request.

Note 2: Higher values available on request.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.

All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Electrical Data - AEQ-Q200 Grade - Standard Range

Type	TCR (ppm/°C)	Power (W)	Limiting Element Voltage (V)	Ohmic Value Range *				
				1%	0.5%	0.25%	0.1%	0.05%
PCF0402...A	50 25	0.063	25	49R9 – 100K				49R9 – 10K
PCF0603...A	50 25	0.063	50	10R – 332K				10R – 49K9
PCF0805...A	50 25	0.1	100	10R – 1M0				10R – 100K
PCF1206...A	50 25	0.125	150					10R – 200K
PCF1210...A	50 25	0.25	150					10R – 499K
PCF2010...A	50 25	0.25	150					
PCF2512...A	50 25	0.5	150					

* Standard values E24 or E96.

Electrical Data - High Power Range

Type	TCR (ppm/°C)	Power (W)	Limiting Element Voltage (V)	Ohmic Value Range *					
				0.5%	0.25%	0.1%	0.05%	0.01%	
PCF0603H	50	0.1	75	4R7-1M			4R7-332K	24R9-100K	
	25								
	15			4R7-332K					
	10								
PCF0805H	5	0.125	150	24R9-15K			4R7-511K	24R9-200K	
	50			1R-1M					4R7-1M
	25			4R7-1M					
	15			4R7-511K					
PCF1206H	10	0.25	200	24R9-30K			4R7-1M	24R9-500K	
	5								
	50								
	25			4R7-1M					
PCF1210H	15	0.33	200	24R9-50K			4R7-1M	24R9-500K	
	10								
	5								
	50			4R7-1M					
PCF2010H	25	0.33	200	24R9-50K			4R7-1M	24R9-500K	
	15								
	10								
	5			4R7-1M					
PCF2512H	50	0.75	200	24R9-50K			1R-2K	4R7-2K	24R9-2K
	25								
	15								
	10								

* Standard values E24 or E96. Other values may be available by request.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Electrical Data - AEQ-Q200 Grade – High Power Range

Type	TCR (ppm/°C)	Power (W)	Limiting Element Voltage (V)	Ohmic Value Range *				
				1%	0.5%	0.25%	0.1%	0.05%
PCF0603H...A	50 25	0.1	75	10R – 332K				10R – 49K9
PCF0805H...A	50 25	0.125	150	10R – 1M0				10R – 100K
PCF1206H...A	50 25	0.25	200					10R – 200K
PCF1210H...A	50 25	0.33	200					10R – 499K
PCF2010H...A	50 25	0.33	200					

Electrical Data - Extended High Power Range

Type	TCR (ppm/°C)	Power (W)	Limiting Element Voltage (V)	Ohmic Value Range *				
				0.5%	0.25%	0.1%	0.05%	0.01%
PCF0603X	50 25	0.166	100	10R-332K				
PCF0805X	50 25	0.25	150	10R-500K				
PCF1206X	50 25	0.333	200	10R-1M				
PCF2512X	50 25	1	200	1R-100R		4R7-100R		


Electrical Data - Passivated Range

Type	TCR (ppm/°C)	Power (W)	Limiting Element Voltage (V)	Ohmic Value Range *		
				0.5%	0.25%	0.1%
PCF0402P	50	0.063	25	25R-25K		
	25			49R9-12K		
PCF0603P	50	0.063	50	25R-332K		
	25			25R-100K		
PCF0805P	50	0.1	100	10R-800K		
	25			25R-200K		
PCF1206P	50	0.125	150	10R-1M		
	25			25R-500K		
PCF2010P	50	0.25	150	10R-1M		
	25			25R-500K		
PCF2512P	50	0.5	150	10R-1M		
	25			10R-1M		

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Physical Data

Dimensions (mm) and Weight (mg)							
	L	W	T max	A	C	Wt	
0201	0.58 ± 0.05	0.29 ± 0.05	0.26	0.15 ± 0.05	0.12 ± 0.05	1	
0402	1.0 ± 0.05	0.5 ± 0.05	0.55	0.2 ± 0.1	0.2 ± 0.1	3	
0603	1.6 ± 0.2	0.8 ± 0.2	0.65	0.3 ± 0.2	0.3 ± 0.2	6	
0805	2.0 ± 0.2	1.25 ± 0.2	0.65	0.4 ± 0.25	0.3 ± 0.2	9	
1206	3.05 ± 0.15	1.55 ± 0.15	0.65	0.35 ± 0.25	0.42 ± 0.2	20	
1210	3.10 ± 0.15	2.4 ± 0.15	0.65	0.55 ± 0.25	0.4 ± 0.2	25	
2010	4.9 ± 0.2	2.4 ± 0.2	0.65	0.5 ± 0.25	0.6 ± 0.3	36	
2512	6.3 ± 0.2	3.1 ± 0.2	0.65	0.5 ± 0.25	0.6 ± 0.3	55	

Construction

A thin-film material is selectively deposited on a 96% alumina substrate together with metallic contacts at each end of the resistor. The unadjusted resistors are heat treated to give the required TCR and stability, then a precisely controlled laser trim process adjusts the resistance value. Epoxy protection is applied and wrap-around terminations are added and plated with Nickel then Tin. Each resistor is measured immediately before packing into tape.

Terminations

The standard termination is 100% Sn matte plated wrap-around suitable for soldering. SnPb plated option is available for standard range PCF over the restricted range below.

SnPb Termination Option Range

Type	TCR (ppm/°C)	Power (W)	Limiting Element Voltage (V)	Ohmic Value Range			
				1%	0.5%	0.25%	0.1%
PCF0805	50	0.1	100	10R – 250K			
	25			10R – 100K			
	15			10R – 100K			
	10			10R – 5KΩ			
PCF1206	50	0.125	150	10R – 500K			
	25			10R – 200K			
	15			10R – 200K			
	10			10R – 10K			

Performance Data - Standard Range

Test Parameters	Conditions	Maximum change (+0.05R)		
		>0.05% tolerance 0603 to 2512	Chip size 0201, 0402	≤0.05% tolerance 0603 to 2512
Load life	1000 hours rated load @ 70°C	0.25%	0.5%	0.05%
Humidity	1000 hours @ 40°C, 90 - 95%RH	0.3%	0.3%	0.05%
Short term overload	6.25 x rated Power, or 2 x LEV, for 5 sec	0.5%	0.5%	0.05%
High temperature operation	1000 hours at 125°C	0.25%	0.25%	0.25%
Temperature cycle	5 cycles -55°C, 125°C	0.1%	0.1%	0.05%
Resistance to solder heat	270°C, 10 sec	0.2%	0.2%	0.05%
Solderability	235°C, 2 sec	95% minimum coverage		

Performance Data - High Power Range/Extended High Power Range

Test Parameters	Conditions	Maximum change (+0.05R)	
		0.5%	0.05%
Load life	1000 hours rated load @ 70°C	0.5%	0.05%
Humidity	1000hrs @ 40°C, 90 - 95%RH	0.5%	0.05%
Short term overload	6.25 x rated Power, or 2 x LEV, for 5 sec	0.5%	0.05%
High temperature operation	1000 hours at 155°C	0.5%	0.05%
Temperature cycle	5 cycles -55°C, 150°C	0.25%	0.05%
Resistance to solder heat	270°C, 10 sec	0.2%	0.05%
Solderability	235°C, 2 sec	95% minimum coverage	

General Note


TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

PCF Series

Performance Data - Passivated Range

Test Parameters	Conditions	Maximum change (+0.05R)	
		0603 to 2512	0402
Load life	1000 hours rated load @ 70°C	0.05%	0.25%
Humidity	1000hrs @ 40°C, 90 - 95%RH	0.05%	0.5%
Short term overload	6.25 x rated Power, or 2 x LEV, for 5 sec	0.02%	0.1%
High temperature operation	1000 hours at 125°C	0.05%	0.5%
Temperature cycle	5 cycles -55 C, 125°C	0.02%	0.1%
Resistance to solder heat	270°C, 10 sec	0.02%	0.1%
Solderability	235°C, 2 sec	95% minimum coverage	

Derating Curve



Solderability

The terminations have an electroplated nickel barrier and tin coating. This ensures excellent 'leach' resistance properties and solderability.

Packaging

PCF Resistors are supplied taped and reeled as per IEC 286-3. Sizes 2010 and 2512 are in embossed plastic tape. Smaller sizes are in paper tape.

Application Notes

PCF resistors are ideally suited for handling by automatic methods due to their rectangular shape and the small dimensional tolerances. Electrical connection to a ceramic substrate or to a printed circuit board can be made by reflow or wave soldering of wrap-around terminations.

Wrap-around terminations provide good leach properties and ensure reliable contact. Due to the robust construction, the PCF can be immersed in the solder bath for 30 seconds at 260 C. This enables the resistor to be mounted on one side of a printed circuit board and wire-leaded components applied on the other side.

PCF resistors themselves can operate at a maximum temperature of 125 C (see performance above) (155 C for High Power grades). For soldered resistors, the joint temperature should not exceed 110 C. This condition is met when the stated power levels at 70 C are used.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Ordering Procedure

This product has two valid part numbers:

European (Welwyn) Part Number: PCF0603-11-1K54BI (0603, standard, 15ppm/°C, 1.54 kilohm ±0.1%, Pb-free)

P	C	F	0	6	0	3	-	1	1	-	1	K	5	4	B	I
1	2	3	4	5	6	7										

1 Type	2 Size	3 Range	4 TCR	5 Value	6 Tolerance	7 Termination & Packing
PCF	0201	Omit for Standard	-13 = ±5ppm/°C	E24 = 3/4 characters	L = ±0.01%	A = AEC-Q200 grade, Pb-free
	0402		-12 = ±10ppm/°C	E96 = 3/4 characters	W = ±0.05%	I = Standard grade, Pb-free
	0603	H = High Power	-11 = ±15ppm/°C	R = ohms	B = ±0.1%	PB = SnPb
	0805	X = Extended	R = ±25ppm/°C	K = kilohms	C = ±0.25%	0201, 0402 10,000/reel
	1206	P = Passivated	-02 = ±50ppm/°C	M = megohms	D = ±0.5%	0603 to 1210 5000/reel
	1210				F = ±1%	2010, 2512 4000/reel
	2010					T1* = Pb-free, 1K reel
	2512					0201 to 1206, 2010, 2512 1000/reel

* Non-standard; enquire to confirm availability

USA (IRC) Part Number*: PCF-W0603LF-11-1541-B-P-LT (0603, standard, 15ppm/°C, 1.54 kilohm ±0.1%, Pb-free)

P	C	F	-	W	0	6	0	3	L	F	-	1	1	-	1	5	4	1	-	B	-	P	-	L	T
1	2	3	4	5	6	7	8																		

1 Type	2 Model	3 Termination	4 TCR	5 Value	6 Tolerance	7 Tape	8 Packing
PCF	W0201	LF = Pb-free	13 = ±5ppm/°C	3 digits + multiplier	T = ±0.01%	P = Paper	LT = Tape & Reel
	W0402	(100%Sn)	12 = ±10ppm/°C	R = ohms for values <100 ohms	A = ±0.05%	(0201 to 1210)	0201, 0402 10,000/reel
	W0603	Omit for SnPb	11 = ±15ppm/°C		B = ±0.1%	E = Embossed	0603 to 1210 5000/reel
	W0805		03 = ±25ppm/°C		C = ±0.25%	(2010, 2512)	2010, 2512 4000/reel
	W1206		02 = ±50ppm/°C		D = ±0.5%		
	W1210				F = ±1%		
	W2010						
	W2512						

* Applies only to Standard Range parts.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.