



Part Number | . | .

PCA.00.250.CTAC29

Size/Series 00 / 00

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model PCA*: Free receptacle with cable collet

Keying Circular (can rotate)


Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing C29: 2.8 - 3.1 mm

Variant :

NEW COLLET

	A	L
mm.	6.5	25
in.	0.26	0.98



PERFORMANCE DETAILS

Insert Configuration 0.25 : 1 Coax (50 Ohm)

Insulator T: PTFE

Specifications

Contact Type: Coaxial 50 Ohm (Solder)

Max. Matings: 5000

Contact Dia.: 0.7 mm (0.028in)

Bucket Dia.: 0.6 mm (0.024in)

R (max): 6.1 mOhm

Vtest: 2100 V (AC), 3000 V (DC)

Rated Current: 4 A (AC/DC)

Impedance: 50 Ohm

VSWR: 1.09 + 0.11 * f/GHz

Cable type: RG 316 /U

OTHER CHARACTERISTICS

Endurance (Shell) 3839 mating cycles

F ret (min): 100 N

IP Rating 50

Catalog

[Download 3D draw](#)[Copyright](#) [Privacy policy](#) [Product safety](#)

