

SURGE CHECK Plus



P0902

- ~ Basic surge protection (70 joules).
- ~ 9 Outlets - 3 with extra spacing for adaptors and transformers.
- ~ Lighted on/off switch & 15 Amp circuit breaker.



P0903

- ~ Full surge protection (900 joules) with warning buzzer.
- ~ 8 Outlets - 2 with extra spacing for adaptors and transformers.
- ~ Modem/Fax/phone protection - 1 line in, 2 lines out.
- ~ Lighted on/off switch & 15 Amp circuit breaker.
- ~ **Bonus 6' telephone cord included!**



P0905

- ~ Full surge protection (900 joules) with warning buzzer.
- ~ 8 Outlets - 2 with extra spacing for adaptors and transformers.
- ~ Modem/Fax/phone protection - 1 line in, 2 lines out.
- ~ Satellite/TV/VCR protection (gold plated coax connectors).
- ~ Lighted on/off switch & 15 Amp circuit breaker.
- ~ **Bonus 6' telephone and 6' coax cord included!**



Surge Check Plus - Specifications

	P0902	P0903	P0905
Number of Outlets	9	8	8
Line Cord Length	6'	6'	6'
Alarm Buzzer	No	Yes	Yes
Internet/Phone Protection	No	Yes	Yes
Satellite/VCR Protection	No	No	Yes
Surge Indicator Light	Yes	Yes	Yes
Ground Indicator Light	No	Yes	Yes
Polarity Indicator Light	No	Yes	Yes
Ground Screw	No	No	Yes
Electrical Rating	125V, 15A	125V, 15A	125V, 15A
Maximum Surge Dissipation	70 Joules	900 Joules	900 Joules
Maximum Surge Voltage	6,000V	6,000V	6,000V
Maximum Spike Current	4,500A	10,000A	10,000A
Clamping Voltage	400V	400V	400V
Clamping Response Time	< 1 nanosecond	<1 nanosecond	<1 nanosecond
Noise Attenuation	None	10dB to 40dB @ 100 Khz. to 100 Mhz.	10dB to 40dB @ 100 Khz. to 100 Mhz.
Temperature Range	-40 C to +80 C	-40 C to +80 C	-40 C to +80 C
UL Listing	UL 1449	UL 1449	UL 1449

