


[Turbo Series](#)

TCH-V86-530-Q(M)



More Information

 [UL Recognized](#)


 [RoHS Compliant](#)

**Specifications**


<b>Mounting</b>	Panel Mount with Volume Control
<b>Operating Mode</b>	Medium Loud Moderate Chime Tone
<b>Operating Voltage</b>	5-30 Vdc
<b>Operating Frequency</b>	2900±250 Hz
<b>Typical Operating Current</b>	4 mA at 5 Vdc 40 mA at 30 Vdc
<b>Typical Sound Pressure</b>	70 ±5 dB(A) at 5 Vdc at 24 inches (61 cm), at 25°C 90 ±5 dB(A) at 30 Vdc at 24 inches (61 cm), at 25°C
<b>Termination</b>	Quick Connect Blades
<b>Termination Strength</b>	Pull test with a maximum of 22 pounds (10 kg) load
<b>Operating Temperature</b>	-20°C to +65°C
<b>Storage Temperature</b>	-40°C to +85°C
<b>Surge Voltage</b>	20% over maximum rated voltage for less than 5 minutes
<b>Reverse Voltage Protection</b>	To the maximum operating voltage
<b>Construction Materials</b>	Case- Plastic _NORYL_ N-190, Flame Retardant UL 94-VO, Black Internal Circuit- Audio-oscillator and piezoelectric driver Potting- 2 parts epoxy resin or silicone, black Diaphragm- Stainless Steel 304
<b>Gasket</b>	Gasket (Included) 0.125" thick, 60 Durometer Neoprene ASTM B117 Certified - Withstands exposure to salt spray for 300 hours IP 68 Certified - Withstands water submergence and dust exposure Humidity- 95% relative humidity at +40°C continuously for 100 hours. Vibration- Withstands vibration between 0 and 55 Hz. on all axes.
<b>Construction Materials</b>	10 years under normal operating conditions.
<b>Life Expectancy</b>	For a period of two years from the date of manufacture under normal operating conditions.
<b>Warranty</b>	
<b>Terms and Conditions of Sale</b>	<a href="#">Link here</a>

## Dimensions

REAR




RING




GASKET



SIDE




FRONT



PANEL MOUNTING



FITS PANELS UP TO  
0.50 in [12.7 mm] THICK



TOLERANCES ARE  $\pm 0.03$  in ( $\pm 0.76$  mm) UNLESS OTHERWISE SPECIFIED