


Capacitor, ceramic, 1 uF, +/-10% Tol, 50V, BX, Lead Spacing=0.2"



## **Dimensions (in)**

## **Specifications**

| ID | Dimension | Tolerance     | Manufacturer:            | KEMET          |
|----|-----------|---------------|--------------------------|----------------|
| W  | 0.09      | +/-0.01       | Capacitance:             | 1 uF           |
| Н  | 0.29      | +/-0.01       | Lead Spacing:            | 0.2"           |
| L  | 0.29      | +/-0.01       | Voltage:                 | 50V            |
| S  | 0.2       | +/-0.03       | Temperature Coefficient: | BX             |
| LL | 1.25      | min           | Tolerance:               | +/-10%         |
| F  | 0.025     | +0.004/-0.002 | Body Type:               | Radial Molded  |
|    |           |               | Lead Type:               | Standard Leads |
|    |           |               | Lead Form:               | Straight Leads |
|    |           |               | Package Kind:            | T&R            |
|    |           |               | Package Size:            | 12in           |
|    |           |               | Package Type:            | Type 1         |
|    |           |               | Package Quantity:        | 1500           |

## Notes:

- -Note A: Center line of the leads will be within 0.03 in [0.76 mm] of the center line of the body.
- -Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk

