


Item no.: 250-108  
Product description: 1-CONDUCTOR PCB TERMINAL STRIP 1 FRONT SOLDER  
PIN / POLE 8 POLE PIN SPACING 3.5 MM / 0.138 IN WITH  
PUSH BUTTONS WITH TEST SLOT FOR TEST PLUG TO 1.3  
MM Ø



Produkt kann von Bild abweichen / product may differ

Packing unit 160 4\*40 pieces

RoHS compliant

|                          |                     |
|--------------------------|---------------------|
| Product group            | 4 (Printed Circuit) |
| Weight                   | 3.76 g              |
| Color                    | gray                |
| No. of connection Points | 8                   |
| No. of potentials        | 8                   |
| pole count               | 8                   |
| Height                   | 13.1 mm             |
| Height                   | 0.516 in            |
| Width                    | 29.5 mm             |
| Width                    | 1.161 in            |
| Depth                    | 12 mm               |
| Depth                    | 0.472 in            |
| Pin spacing from         | 3.5 mm              |
| Pin spacing from         | 0.138 in            |
| Pollution degree         | 2                   |
| Measured voltage EN      | 160 V               |
| Measured shock voltage   | 2.5 kV              |

|                        |        |
|------------------------|--------|
| Current intensity EN   | 8 A    |
| Pollution degree       | 2      |
| Measured voltage EN    | 320 V  |
| Measured shock voltage | 2.5 kV |
| Current intensity EN   | 8 A    |



|                     |                                                      |
|---------------------|------------------------------------------------------|
| Cross section [mm²] | 0.2 - 1.5 mm²                                        |
| Wiring method       | solid                                                |
| Cross section [mm²] | 0.2 - 1.5 mm²                                        |
| Wiring method       | fine-stranded                                        |
| Cross section [mm²] | 0.25 - 1 mm²                                         |
| Wiring method       | fine-stranded (with ferrule and plastic collar)      |
| Cross section [mm²] | 0.25 - 1 mm²                                         |
| Wiring method       | fine-stranded (with ferrule, without plastic collar) |
| Cross section [AWG] | 24 - 16 AWG                                          |
| Strip length from   | 8.5 mm                                               |
| Strip length to     | 9.5 mm                                               |
| Material group      | I                                                    |
| Contact surface     | Copper                                               |
| xxx-xxx/000-002     | yellow                                               |
| xxx-xxx/000-004     | black                                                |
| xxx-xxx/000-005     | red                                                  |
| xxx-xxx/000-006     | blue                                                 |
| xxx-xxx/000-009     | light gray                                           |
| xxx-xxx/000-012     | orange                                               |
| xxx-xxx/000-014     | brown                                                |
| xxx-xxx/000-017     | light green                                          |
| xxx-xxx/000-024     | violet                                               |
| xxx-xxx/000-050     | white                                                |



| Item no. | Admission office | Approval no.      | Voltage [V] | Current [A] | Cross section [ mm² ] |
|----------|------------------|-------------------|-------------|-------------|-----------------------|
| 250-108  | ABS              | 04-HG469925/1-PDA | 250         | 2           | 0,5-1,5               |
| 250-108  | BV               | 11915/A0          | 200         | 2           | 0,5-1,5               |
| 250-108  | CCA              | NL6336            | 250         | 8           | 0,2-1,5               |
| 250-108  | CSA              | 154112-1132097    | 300         | 10          | 20-16                 |
| 250-108  | DNV              | E-9215            | 250         | 2           | 0,5-1,5               |
| 250-108  | GL               | 17296-00HH        | 250         | 2           | 0,5-1,5               |
| 250-108  | KEMA             | 2114919.01        | 250         | 8           | 0,2-1,5               |
| 250-108  | RMR              | 11130002          | 250         | 2           | 0,5-1,5               |
| 250-108  | UR               | E45172            | 300         | 5           | 24-16                 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected