

KZH Series

- Newly innovative electrolyte is employed to minimize impedance
- Endurance with ripple current: 5,000 to 6,000 hours at 105°C
- Non solvent resistant type
- RoHS Compliant

KZM P158
↑ Longer life
KZH
↑ Lower Z
KZE P163




◆ SPECIFICATIONS

Items	Characteristics					
Category	-40 to +105℃					
Temperature Range						
Rated Voltage Range	6.3 to 35V _{dc}					
Capacitance Tolerance	± 20% (M) (at 20℃, 120Hz)					
Leakage Current	I=0.01CV or 3μA, whichever is greater. Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20℃ after 2 minutes)					
Dissipation Factor (tan δ)	Rated voltage (V _{dc})	6.3V	10V	16V	25V	35V
	tan δ (Max.)	0.22	0.19	0.16	0.14	0.12
	When nominal capacitance exceeds 1,000μF, add 0.02 to the value above for each 1,000μF increase. (at 20℃, 120Hz)					
Low Temperature Characteristics (Max. Impedance Ratio)	Z (-25℃) / Z (+20℃)	2max.				
	Z (-40℃) / Z (+20℃)	3max.				
	(at 120Hz)					
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20℃ after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage)for the specified period of time at 105℃.					
	Time	φ 5 & φ 6.3 : 5,000hours φ 8 to φ 16 : 6,000hours				
	Capacitance change	≤ ± 25% of the initial value (6.3, 10V _{dc} : ≤ ± 30%)				
	D.F. (tan δ)	≤ 200% of the initial specified value				
	Leakage current	≤ The initial specified value				
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20℃ after exposing them for 500 hours at 105℃ without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4.					
	Capacitance change	≤ ± 25% of the initial value (6.3, 10V _{dc} : ≤ ± 30%)				
	D.F. (tan δ)	≤ 200% of the initial specified value				
	Leakage current	≤ The initial specified value				


◆ DIMENSIONS [mm]

● Terminal Code : E



φD	5	6.3	8	10	12.5	16
φd	0.5	0.5	0.6	0.6	0.6	0.8
F	2.0	2.5	3.5	5.0	5.0	7.5
φD'	φD+0.5max.					
L'	L+1.5max.					

◆ PART NUMBERING SYSTEM



Please refer to "Product code guide (radial lead type)"

◆STANDARD RATINGS

WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	Impedance (Ω max./100kHz)		Rated ripple current (mA _{rms} /105°C, 100kHz)	Part No.
			20°C	-10°C		
6.3	220	5×11	0.24	0.80	330	EKZH6R3E□□221ME11D
	470	6.3×11	0.11	0.35	500	EKZH6R3E□□471MF11D
	820	8×11.5	0.062	0.19	900	EKZH6R3E□□821MHB5D
	1,200	8×15	0.048	0.15	1,210	EKZH6R3E□□122MH15D
	1,200	10×12.5	0.045	0.14	1,240	EKZH6R3E□□122MJC5S
	1,500	8×20	0.033	0.11	1,410	EKZH6R3E□□152MH20D
	1,800	10×16	0.032	0.10	1,650	EKZH6R3E□□182MJ16S
	2,200	10×20	0.020	0.060	1,960	EKZH6R3E□□222MJ20S
	2,700	10×25	0.018	0.054	2,250	EKZH6R3E□□272MJ25S
	3,900	12.5×20	0.017	0.043	2,480	EKZH6R3E□□392MK20S
	4,700	12.5×25	0.015	0.038	2,900	EKZH6R3E□□472MK25S
	5,600	12.5×30	0.013	0.033	3,450	EKZH6R3E□□562MK30S
	6,800	12.5×35	0.012	0.031	3,570	EKZH6R3E□□682MK35S
	6,800	16×20	0.015	0.038	3,250	EKZH6R3E□□682ML20S
	8,200	16×25	0.013	0.035	3,630	EKZH6R3E□□822ML25S
10	150	5×11	0.24	0.80	330	EKZH100E□□151ME11D
	330	6.3×11	0.11	0.35	500	EKZH100E□□331MF11D
	680	8×11.5	0.062	0.19	900	EKZH100E□□681MHB5D
	1,000	8×15	0.048	0.15	1,210	EKZH100E□□102MH15D
	1,000	10×12.5	0.045	0.14	1,240	EKZH100E□□102MJC5S
	1,500	8×20	0.033	0.11	1,410	EKZH100E□□152MH20D
	1,500	10×16	0.032	0.10	1,650	EKZH100E□□152MJ16S
	1,800	10×20	0.020	0.060	1,960	EKZH100E□□182MJ20S
	2,200	10×25	0.018	0.054	2,250	EKZH100E□□222MJ25S
	3,300	12.5×20	0.017	0.043	2,480	EKZH100E□□332MK20S
	3,900	12.5×25	0.015	0.038	2,900	EKZH100E□□392MK25S
	4,700	12.5×30	0.013	0.033	3,450	EKZH100E□□472MK30S
	4,700	16×20	0.015	0.038	3,250	EKZH100E□□472ML20S
	5,600	12.5×35	0.012	0.031	3,570	EKZH100E□□562MK35S
	6,800	16×25	0.013	0.035	3,630	EKZH100E□□682ML25S
16	100	5×11	0.24	0.80	330	EKZH160E□□101ME11D
	220	6.3×11	0.11	0.35	500	EKZH160E□□221MF11D
	470	8×11.5	0.062	0.19	900	EKZH160E□□471MHB5D
	680	8×15	0.048	0.15	1,210	EKZH160E□□681MH15D
	680	10×12.5	0.045	0.14	1,240	EKZH160E□□681MJC5S
	1,000	8×20	0.033	0.11	1,410	EKZH160E□□102MH20D
	1,000	10×16	0.032	0.10	1,650	EKZH160E□□102MJ16S
	1,500	10×20	0.020	0.060	1,960	EKZH160E□□152MJ20S
25	1,800	10×25	0.018	0.054	2,250	EKZH160E□□182MJ25S
	2,200	12.5×20	0.017	0.043	2,480	EKZH160E□□222MK20S
	2,700	12.5×25	0.015	0.038	2,900	EKZH160E□□272MK25S
	3,300	12.5×30	0.013	0.033	3,450	EKZH160E□□332MK30S
	3,300	16×20	0.015	0.038	3,250	EKZH160E□□332ML20S
	3,900	12.5×35	0.012	0.031	3,570	EKZH160E□□392MK35S
	4,700	16×25	0.013	0.035	3,630	EKZH160E□□472ML25S
35	68	5×11	0.24	0.80	330	EKZH250E□□680ME11D
	150	6.3×11	0.11	0.35	500	EKZH250E□□151MF11D
	330	8×11.5	0.062	0.19	900	EKZH250E□□331MHB5D
	390	8×15	0.048	0.15	1,210	EKZH250E□□391MH15D
	470	10×12.5	0.045	0.14	1,240	EKZH250E□□471MJC5S
	560	8×20	0.033	0.11	1,410	EKZH250E□□561MH20D
	680	10×16	0.032	0.10	1,650	EKZH250E□□681MJ16S
	820	10×20	0.020	0.060	1,960	EKZH250E□□821MJ20S
	1,000	10×25	0.018	0.054	2,250	EKZH250E□□102MJ25S
	1,500	12.5×20	0.017	0.043	2,480	EKZH250E□□152MK20S
	1,800	12.5×25	0.015	0.038	2,900	EKZH250E□□182MK25S
	2,200	12.5×30	0.013	0.033	3,450	EKZH250E□□222MK30S
	2,200	16×20	0.015	0.038	3,250	EKZH250E□□222ML20S
	2,700	12.5×35	0.012	0.031	3,570	EKZH250E□□272MK35S
	3,300	16×25	0.013	0.035	3,630	EKZH250E□□332ML25S
6.3	47	5×11	0.24	0.80	330	EKZH350E□□470ME11D
	100	6.3×11	0.11	0.35	500	EKZH350E□□101MF11D
	220	8×11.5	0.062	0.19	900	EKZH350E□□221MHB5D
	270	8×15	0.048	0.15	1,210	EKZH350E□□271MH15D
	330	10×12.5	0.045	0.14	1,240	EKZH350E□□331MJC5S
	390	8×20	0.033	0.11	1,410	EKZH350E□□391MH20D
	470	10×16	0.032	0.10	1,650	EKZH350E□□471MJ16S
	560	10×20	0.020	0.060	1,960	EKZH350E□□561MJ20S
	680	10×25	0.018	0.054	2,250	EKZH350E□□681MJ25S
	1,000	12.5×20	0.017	0.043	2,480	EKZH350E□□102MK20S
	1,200	12.5×25	0.015	0.038	2,900	EKZH350E□□122MK25S
	1,500	12.5×30	0.013	0.033	3,450	EKZH350E□□152MK30S
	1,500	16×20	0.015	0.038	3,250	EKZH350E□□152ML20S
	1,800	12.5×35	0.012	0.031	3,570	EKZH350E□□182MK35S
	2,200	16×25	0.013	0.035	3,630	EKZH350E□□222ML25S

□□ : Enter the appropriate lead forming or taping code.

◆RATED RIPPLE CURRENT MULTIPLIERS

⊙ Frequency Multipliers

Capacitance(μF)	Frequency(Hz)	120	1k	10k	100k
0.47 to 150		0.40	0.75	0.90	1.00
220 to 560		0.50	0.85	0.94	1.00
680 to 1,800		0.60	0.87	0.95	1.00
2,200 to 3,900		0.75	0.90	0.95	1.00
4,700 to 8,200		0.85	0.95	0.98	1.00

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.