

NTC Thermistors, Standard Lug Sensors


RoHS
COMPLIANT

QUICK REFERENCE DATA		
PARAMETER	VALUE	UNIT
Resistance value at 25 °C ⁽²⁾	4.7K to 100K	Ω
Tolerance on R_{25} -value ⁽²⁾	± 1 to ± 5	%
$B_{25/85}$ -value	3435 to 4190	K
Tolerance on $B_{25/85}$ -value	± 0.5 to ± 1.5	%
Operating temperature range at:		°C
Zero dissipation	-40 to +150	
Maximum dissipation	0 to +55	
Dissipation factor ⁽³⁾	≈ 23	mW/K
Thermal time constant ⁽³⁾	≈ 7.5	s
Min. dielectric withstanding voltage between terminals and lug	1500 (1 s)	V _{AC}
Insulation resistance between terminals and lug at 500 V _{DC}	min. 100	MΩ
Climatic category (LCT / UCT / days)	40 / 150 / 56	
Weight	1.6	g

Notes

⁽²⁾ Other R_{25} -values and tolerances are available upon request.

⁽³⁾ Measured with screw mounted on an aluminum heatsink of 100 cm², thickness 1.5 mm, in still air at $T_{amb} = +25$ °C.

PACKAGING

The thermistors are packed in cardboard boxes; the smallest packaging quantity is 500 units.

MOUNTING

- By means of M3 screw. Leads to be soldered or crimped
- The device is suitable for screwing e.g. on metal surface
- The leads are suitable for soldering e.g. on PCB
- Other screw sizes are available on request

FEATURES

- Easy mounting using ring tongue terminal
- Rugged construction
- Cable of PTFE insulation according to NEMA HP-3, type E, rated 600 V_{RMS} ⁽¹⁾
- AEC-Q200 qualified (grade 1)
- UL recognized, file E148885 (UL category XGPU2)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


Note

⁽¹⁾ Formerly MIL-W-16878/4, type E.

APPLICATIONS

- Suitable for surface sensing applications, especially when a good electrical insulation and a good thermal contact with the chassis is required.
- Thermistor with negative temperature coefficient and two stranded PTFE insulated copper leads.
- The device is mounted inside the barrel of the ring tongue terminal.

DIMENSIONS



Notes

- The thermistor chip NTC is epoxy coated and attached to the metal lug via a middle buffer layer.
- Metal ring lug is tinned copper.
- Insulated leads: AWG#24 stranded, PTFE insulation, Ø 1.12 mm.
- Lead wire end twisted and tinned, other lead length and insulation, available on request.

DESIGNERS TOOL

- Other resistance curves and tolerances are available on request
- Consult Vishay for other lead length, other connector crimping or other features
- 3D solid models: www.vishay.com/doc?29106
- NTC curve computation: www.vishay.com/thermistors/curve-computation-list/



ELECTRICAL DATA AND ORDERING INFORMATION						
VISHAY SAP ORDERING NUMBER	R_{25}-VALUE (Ω)	R_{25} TOL. ($\pm$ %)	$B_{25/85}$-VALUE (K)	$B_{25/85}$ TOL. ($\pm$ %)	DESCRIPTION	UL CERTIFICATION
NTCALUG01A472H	4700	3	3984	0.5	NTC Lug01 4.7K 3 % 3984K PTFE AWG#24 38 mm	-
NTCALUG01A103FL	10 000	1	3435	1	NTC Lug01 10K 1 % 3435K PTFE AWG#24 38 mm	UL
NTCALUG01A103F	10 000	1	3984	0.5	NTC Lug01 10K 1 % 3984K PTFE AWG#24 38 mm	UL
NTCALUG01A103G	10 000	2	3984	0.5	NTC Lug01 10K 2 % 3984K PTFE AWG#24 38 mm	UL
NTCALUG01A103H	10 000	3	3984	0.5	NTC Lug01 10K 3 % 3984K PTFE AWG#24 38 mm	UL
NTCALUG01A103J ⁽¹⁾	10 000	5	3984	0.5	NTC Lug01 10K 5 % 3984K PTFE AWG#24 38 mm	UL
NTCALUG01A473H	47 000	3	4090	1.5	NTC Lug01 47K 3 % 4090K PTFE AWG#24 38 mm	-
NTCALUG01A104F	100 000	1	4190	1.5	NTC Lug01 100K 1 % 4190K PTFE AWG#24 38 mm	-
NTCALUG01A104G	100 000	2	4190	1.5	NTC Lug01 100K 2 % 4190K PTFE AWG#24 38 mm	-

Note

⁽¹⁾ NTCALUG01A103J identical to NTCALUGE2C90169 = 2381 645 90169.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.