


## Ultrafast Rectifier, 8 A FRED Pt®




TO-263AB (D²PAK)



TO-262AA



VS-MURB820PbF



VS-MURB820-1PbF

### FEATURES

- Ultrafast recovery time
- Low forward voltage drop
- Low leakage current
- 175 °C operating junction temperature
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- AEC-Q101 qualified
- Material categorization:  
for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### DESCRIPTION / APPLICATIONS

MUR.. series are the state of the art ultrafast recovery rectifiers specifically designed with optimized performance of forward voltage drop and ultrafast recovery time.

The planar structure and the platinum doped life time control, guarantee the best overall performance, ruggedness and reliability characteristics.

These devices are intended for use in the output rectification stage of SMPS, UPS, DC/DC converters as well as freewheeling diode in low voltage inverters and chopper motor drives.

Their extremely optimized stored charge and low recovery current minimize the switching losses and reduce over dissipation in the switching element and snubbers.

### PRODUCT SUMMARY

|                 |                            |
|-----------------|----------------------------|
| Package         | TO-263AB (D²PAK), TO-262AA |
| $I_{F(AV)}$     | 8 A                        |
| $V_R$           | 200 V                      |
| $V_F$ at $I_F$  | 0.895 V                    |
| $t_{rr}$        | 35 ns                      |
| $T_J$ max.      | 175 °C                     |
| Diode variation | Single die                 |

### ABSOLUTE MAXIMUM RATINGS

| PARAMETER                                   | SYMBOL         | TEST CONDITIONS                                   | MAX.        | UNITS |
|---|----------------|---|-------------|-------|
| Peak repetitive reverse voltage             | $V_{RRM}$      |   | 200         | V     |
| Average rectified forward current           | $I_{F(AV)}$    | Total device, rated $V_R$ , $T_C = 150$ °C        | 8           | A     |
| Non-repetitive peak surge current           | $I_{FSM}$      |   | 100         |       |
| Peak repetitive forward current             | $I_{FM}$       | Rated $V_R$ , square wave, 20 kHz, $T_C = 150$ °C | 16          |       |
| Operating junction and storage temperatures | $T_J, T_{Stg}$ |   | -65 to +175 | °C    |

### ELECTRICAL SPECIFICATIONS ( $T_J = 25$ °C unless otherwise specified)

| PARAMETER                           | SYMBOL        | TEST CONDITIONS                              | MIN. | TYP. | MAX.  | UNITS   |
|-------------------------------------|---------------|--|------|------|-------|---------|
| Breakdown voltage, blocking voltage | $V_{BR}, V_R$ | $I_R = 100$ $\mu$ A                          | 200  | -    | -     | V       |
| Forward voltage                     | $V_F$         | $I_F = 8$ A                                  | -    | -    | 0.975 |         |
|                                     |               | $I_F = 8$ A, $T_J = 150$ °C                  | -    | -    | 0.895 |         |
| Reverse leakage current             | $I_R$         | $V_R = V_R$ rated                            | -    | -    | 5     | $\mu$ A |
|                                     |               | $T_J = 150$ °C, $V_R = V_R$ rated            | -    | -    | 250   |         |
| Junction capacitance                | $C_T$         | $V_R = 200$ V                                | -    | 25   | -     | pF      |
| Series inductance                   | $L_S$         | Measured lead to lead 5 mm from package body | -    | 8.0  | -     | nH      |



| DYNAMIC RECOVERY CHARACTERISTICS ( $T_J = 25\text{ }^{\circ}\text{C}$ unless otherwise specified) |           |  |      |      |      |       |
|---|-----------|--|------|------|------|-------|
| PARAMETER   | SYMBOL    | TEST CONDITIONS  | MIN. | TYP. | MAX. | UNITS |
| Reverse recovery time   | $t_{rr}$  | $I_F = 1.0\text{ A}$ , $dI_F/dt = 50\text{ A}/\mu\text{s}$ , $V_R = 30\text{ V}$ | -    | -    | 35   | ns    |
|   |           | $I_F = 0.5\text{ A}$ , $I_R = 1.0\text{ A}$ , $I_{REC} = 0.25\text{ A}$          | -    | -    | 25   |       |
|   |           | $T_J = 25\text{ }^{\circ}\text{C}$   | -    | 20   | -    |       |
|   |           | $T_J = 125\text{ }^{\circ}\text{C}$  | -    | 34   | -    |       |
| Peak recovery current   | $I_{RRM}$ | $T_J = 25\text{ }^{\circ}\text{C}$   | -    | 1.7  | -    | A     |
|   |           | $T_J = 125\text{ }^{\circ}\text{C}$  | -    | 4.2  | -    |       |
| Reverse recovery charge   | $Q_{rr}$  | $T_J = 25\text{ }^{\circ}\text{C}$   | -    | 23   | -    | nC    |
|   |           | $T_J = 125\text{ }^{\circ}\text{C}$  | -    | 75   | -    |       |

| THERMAL - MECHANICAL SPECIFICATIONS            |                   |  |              |      |            |                             |
|--|-------------------|--|--------------|------|------------|-----------------------------|
| PARAMETER                                      | SYMBOL            | TEST CONDITIONS                            | MIN.         | TYP. | MAX.       | UNITS                       |
| Maximum junction and storage temperature range | $T_J$ , $T_{Stg}$ |  | -65          | -    | 175        | $^{\circ}\text{C}$          |
| Thermal resistance, junction to case           | $R_{thJC}$        |  | -            | -    | 3.0        | $^{\circ}\text{C}/\text{W}$ |
| Thermal resistance, junction to ambient        | $R_{thJA}$        |  | -            | -    | 50         |                             |
| Thermal resistance, case to heatsink           | $R_{thCS}$        | Mounting surface, flat, smooth and greased | -            | 0.5  | -          |                             |
| Weight   |                   |  | -            | 2.0  | -          | g                           |
|  |                   |  | -            | 0.07 | -          | oz.                         |
| Mounting torque                                |                   |  | 6.0<br>(5.0) | -    | 12<br>(10) | kgf · cm<br>(lbf · in)      |
| Marking device                                 |                   | Case style TO-263AB (D <sup>2</sup> PAK)   | MURB820      |      |            |                             |
|  |                   | Case style TO-262AA                        | MURB820-1    |      |            |                             |




Fig. 1 - Typical Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage





Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage


Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Typical Reverse Recovery Time vs.  $dI_F/dt$




Fig. 8 - Typical Stored Charge vs.  $dI_F/dt$

## Note

- (1) Formula used:  $T_C = T_J - (P_d + P_{dREV}) \times R_{thJC}$ ;  
 $P_d$  = Forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $P_{dREV}$  = Inverse power loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R$  at  $V_{R1}$  = Rated  $V_R$




Fig. 9 - Reverse Recovery Parameter Test Circuit




Fig. 10 - Reverse Recovery Waveform and Definitions



## ORDERING INFORMATION TABLE

|             |     |     |   |   |    |    |     |     |
|-------------|-----|-----|---|---|----|----|-----|-----|
| Device code | VS- | MUR | B | 8 | 20 | -1 | TRL | PbF |
|             | 1   | 2   | 3 | 4 | 5  | 6  | 7   | 8   |


- |          |   |  |
|----------|---|--|
| <b>1</b> | - | Vishay Semiconductors product  |
| <b>2</b> | - | Ultrafast MUR series   |
| <b>3</b> | - | B = D <sup>2</sup> PAK/TO-262  |
| <b>4</b> | - | Current rating (8 = 8 A)   |
| <b>5</b> | - | Voltage rating (20 = 200 V)  |
| <b>6</b> | - | <ul style="list-style-type: none"><li>• None = D<sup>2</sup>PAK</li><li>• -1 = TO-262</li></ul>  |
| <b>7</b> | - | <ul style="list-style-type: none"><li>• None = tube (50 pieces)</li><li>• TRL = tape and reel (left oriented, for D<sup>2</sup>PAK package)</li><li>• TRR = tape and reel (right oriented, for D<sup>2</sup>PAK package)</li></ul> |
| <b>8</b> | - | PbF = lead (Pb)-free   |

| LINKS TO RELATED DOCUMENTS |  |
|----------------------------|--|
| Dimensions                 | <a href="http://www.vishay.com/doc?95014">www.vishay.com/doc?95014</a> |
| Part marking information   | <a href="http://www.vishay.com/doc?95008">www.vishay.com/doc?95008</a> |
| Packaging information      | <a href="http://www.vishay.com/doc?95032">www.vishay.com/doc?95032</a> |

## D<sup>2</sup>PAK, TO-262

### DIMENSIONS FOR D<sup>2</sup>PAK in millimeters and inches

**Conforms to JEDEC outline D<sup>2</sup>PAK (SMD-220)**




| SYMBOL | MILLIMETERS |       | INCHES |       | NOTES |  | SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|--------|-------|-------|--|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.   | MAX.  |       |  |        | MIN.        | MAX.  |           |       |       |
| A      | 4.06        | 4.83  | 0.160  | 0.190 |       |  | D1     | 6.86        | 8.00  | 0.270     | 0.315 | 3     |
| A1     | 0.00        | 0.254 | 0.000  | 0.010 |       |  | E      | 9.65        | 10.67 | 0.380     | 0.420 | 2, 3  |
| b      | 0.51        | 0.99  | 0.020  | 0.039 |       |  | E1     | 7.90        | 8.80  | 0.311     | 0.346 | 3     |
| b1     | 0.51        | 0.89  | 0.020  | 0.035 | 4     |  | e      | 2.54 BSC    |       | 0.100 BSC |       |       |
| b2     | 1.14        | 1.78  | 0.045  | 0.070 |       |  | H      | 14.61       | 15.88 | 0.575     | 0.625 |       |
| b3     | 1.14        | 1.73  | 0.045  | 0.068 | 4     |  | L      | 1.78        | 2.79  | 0.070     | 0.110 |       |
| c      | 0.38        | 0.74  | 0.015  | 0.029 |       |  | L1     | -           | 1.65  | -         | 0.066 | 3     |
| c1     | 0.38        | 0.58  | 0.015  | 0.023 | 4     |  | L2     | 1.27        | 1.78  | 0.050     | 0.070 |       |
| c2     | 1.14        | 1.65  | 0.045  | 0.065 |       |  | L3     | 0.25 BSC    |       | 0.010 BSC |       |       |
| D      | 8.51        | 9.65  | 0.335  | 0.380 | 2     |  | L4     | 4.78        | 5.28  | 0.188     | 0.208 |       |

## Notes

- (1) Dimensioning and tolerancing per ASME Y14.5 M-1994
- (2) Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body
- (3) Thermal pad contour optional within dimension E, L1, D1 and E1
- (4) Dimension b1 and c1 apply to base metal only
- (5) Datum A and B to be determined at datum plane H
- (6) Controlling dimension: inch
- (7) Outline conforms to JEDEC outline TO-263AB

## DIMENSIONS FOR TO-262 in millimeters and inches



| SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.      | MAX.  |       |
| A      | 4.06        | 4.83  | 0.160     | 0.190 |       |
| A1     | 2.03        | 3.02  | 0.080     | 0.119 |       |
| b      | 0.51        | 0.99  | 0.020     | 0.039 |       |
| b1     | 0.51        | 0.89  | 0.020     | 0.035 | 4     |
| b2     | 1.14        | 1.78  | 0.045     | 0.070 |       |
| b3     | 1.14        | 1.73  | 0.045     | 0.068 | 4     |
| c      | 0.38        | 0.74  | 0.015     | 0.029 |       |
| c1     | 0.38        | 0.58  | 0.015     | 0.023 | 4     |
| c2     | 1.14        | 1.65  | 0.045     | 0.065 |       |
| D      | 8.51        | 9.65  | 0.335     | 0.380 | 2     |
| D1     | 6.86        | 8.00  | 0.270     | 0.315 | 3     |
| E      | 9.65        | 10.67 | 0.380     | 0.420 | 2, 3  |
| E1     | 7.90        | 8.80  | 0.311     | 0.346 | 3     |
| e      | 2.54 BSC    |       | 0.100 BSC |       |       |
| L      | 13.46       | 14.10 | 0.530     | 0.555 |       |
| L1     | -           | 1.65  | -         | 0.065 | 3     |
| L2     | 3.56        | 3.71  | 0.140     | 0.146 |       |

### Notes

- (1) Dimensioning and tolerancing as per ASME Y14.5M-1994
- (2) Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body
- (3) Thermal pad contour optional within dimension E, L1, D1 and E1
- (4) Dimension b1 and c1 apply to base metal only
- (5) Controlling dimension: inches

- (6) Outline conform to JEDEC TO-262 except A1 (maximum), b (minimum) and D1 (minimum) where dimensions derived the actual package outline





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[VS-MURB820-1PBF](#) [VS-MURB820TRRPBF](#) [MURB820](#) [MURB820-1](#) [VS-MURB820PBF](#) [MURB820TRL](#)  
[MURB820TRR](#) [VS-MURB820TRLPBF](#)