



# DEUTSCH 38999 CONNECTORS SERIES I, III, AND IV

Rugged Circular Connectors in Mil-Spec and Derivative Configurations to Meet the Widest Range of Harsh Environments and Applications

# DEUTSCH 38999 CONNECTORS

Series I, III, and IV



## Subminiature Circular Connectors Built for Harsh Environments

TE Connectivity (TE) is your one-stop source for MIL-DTL-38999 and 38999-style connectors. We offer mil-qualified Series I, III, and IV connectors in a wide array of configurations, materials and finishes to help meet the needs of ground, aerospace, and marine applications. The subminiature circular connectors are time tested for reliability in harsh environments. Our 38999 connectors include support for:

- Signals
- Power
- RF
- Optical
- Hermetic sealing
- EMI filtering

## Beyond Mil Specs

Because of the widespread popularity of 38999 Series III connectors, we have also used this form factor for designs to meet a variety of configurations beyond those of MIL-DTL-38999. This gives you a familiar, reliable connector and access to the full range of backshells and other accessories.

## TE Components . . . TE Technology . . . TE Know-how . . .

AMP | Agastat | CII | Hartman | Kilovac | Microdot | Nanonics | Polamco | Raychem | Rochester | DEUTSCH  
SEACON Phoenix | L.L. Rowe | Phoenix Optix | SEACON

Get your product to market faster with a smarter, better solution.





## Recent 38999 Highlights

### RoHS-Compatible Finishes

Our 38999-qualified connectors are available with cadmium-free, environment-resisting plating options offering 500-hour salt spray resistance and a -65°C to +175°C temperature range.

**Class T:** Nickel-PTFE

**Class Z:** Black zinc nickel



### PC Board-Mount Connectors

TE offers hundreds of different sizes and types of standard and extended-tail contacts. Direct board mounting not only saves weight and space, it enhances system reliability and performance by replacing a separable interface with a more reliable soldered interconnection.



### MC801 Connectors

Expanding your options from our already broad fiber-optic portfolio, MC801 connectors combine a 38999 shell with the capability to use industry-standard 801 optical termini. We support a full range of interface styles to help allow you to achieve the full benefits of fiber's bandwidth, reach, and noise immunity.



### CeeLok FAS-X Connectors

Take control of high-speed networking with connectors that support up to four 10G Ethernet channels with excellent signal integrity. Using standard 39029 contacts, the connectors can be field terminated using standard tools.



MIL-DTL-38999 Connectors

	Series I	Series III	Series IV
<b>Coupling Mechanism</b>	Bayonet 1/3 turn	Threaded 360° turn	Breech lock 1/4 turn
<b>Shell Materials</b>	Aluminum	Stainless steel Aluminum Composite	Aluminum
<b>Features</b>		Scoop proof Environmentally sealed Hermetic versions Filter versions Spring fingers for EMI control	
<b>Shell Platings</b>		Olive drab cadmium Passivated Electroless nickel Electrodeposited nickel Nickel PTFE (Series III) Black zinc-nickel (Series III)	
<b>Contact Sizes, Std</b>		23, 22, 20, 16, 12, 8	
<b>Shell Sizes</b>		9, 11, 13, 15, 17, 19, 21, 23, 25	
<b>No. of Signal Contacts, Max.</b>		187	
<b>Contact Type</b>		MIL-C-39029	
<b>Contact Styles</b>		Crimp Solder cup or eyelet PCB tail	
<b>Operating Temperatures</b>		-65°C to +200°C -65°C to +175°C -65°C to +150°C (Depends on shell finish)	
<b>Durability (Mating Cycles)</b>		500 (High-durability versions available)	
<b>Standard Configurations</b>		<p><b>Plugs</b> Straight, with or without EMI spring fingers Lanyard release</p> <p><b>Receptacles</b> Box mounting, both front and rear panel mounting Wall mounting, both front and rear panel mounting Jam nut, rear panel mounting Solder mounting Through-bulkhead</p>	



MIL-DTL-38999 CONNECTORS



MIL-DTL-38999 Series I

**Bayonet coupling ring with constant mating torque**

- Quick connect/disconnect: 1/3 turn
- Corrosion Resistant**
  - 500-hour salt spray resistance
  - Thermoplastic clips molded directly with insert
  - RFI fingers for EMI protection
- Typical Applications**
  - Ground vehicles



DTS Series Connectors MIL-DTL-38999 Series III

**Triple-start, self-locking threaded coupling**

- Disconnect: 360° turn
- Capable**
  - Light weight
  - VG 95319 qualified
  - EN3645 qualified
- Versatile**
  - More choice in shell sizes, materials, inserts, filtering and EMI protection, and environmental sealing
- Typical Applications**
  - Ground, aerospace, and marine
  - Most widely used 38999 style



DTS-K and -S Series Connectors MIL-DTL-38999 Series III Classes K and S

**Extreme Environments**

- -65°C to +200°C operating temperature
- Withstands high vibration and shock
- Corrosion-resistant stainless steel shell
- Fire tested to +1093°C
- Typical Applications**
  - Engines in ground vehicles, aerospace, and UAVs
  - High-temperature, high-vibration areas



DIV Series Connectors MIL-DTL-38999 Series IV

**Breech lock coupling**

- Quick connect/disconnect: Quarter turn
- High Performance**
  - Optimized for SWAMP area applications
  - Visual, audible and tactile full-mate indicators
- Typical Applications**
  - Missiles
  - Aircraft
  - Ground vehicles



ACT Series Connectors MIL-DTL-38999 Series III Composite Shells

**Weight Saving**

- Lightweight composite shell
- Rugged**
  - -65°C to +200°C operating temperature
  - Excellent corrosion resistance: withstands 2000-hour salt spray
  - Up to 1500-mating-cycle durability
- Typical Applications**
  - Commercial and military aerospace
  - UAVs



Lanyard-Release Plugs MIL-DTL-1760

**Instant Disconnection**

- Designed for munitions stores
- MIL-DTL-38999/31 qualified
- MIL-DTL-1760 Types 1 and 2**
  - Type 1 available in aluminum and composite versions for drop launch
  - Type 2 incorporates a replaceable buffer system for rail launch
- Typical Applications**
  - Ground and air-launched missiles
  - Smart bombs

38999-DERIVED CONNECTORS



Wildcat 38999 High-Density Connectors

**High Density**

- Nearly double the contact density of standard M38999 connectors
- Four shell sizes, 11 to 64 contacts
- 3 amps per contact
- Lightweight and Space Saving**
  - Aerospace grade aluminium
  - Rear removable crimp and PCB contacts
  - -65°C to +175°C / +200°C (plating dependent)
- Typical Applications**
  - Universal soldier
  - UAV
  - Communications



HDJ Series Connectors 38999 Series 1.5

**Reduced Profile**

- Based on 38999 Series I coupling interface lengths and Series II diameters
- Meets LN29729 standard
- Meets J 62.017 and DIN 65002 standards
- -55°C to +175°C operating temperature
- Typical Applications**
  - Military aerospace





38999-DERIVED CONNECTORS



DTB Series Connectors  
38999 Series III  
Bronze Shells

**Designed for Marine Application**

- Marine bronze shell for marine applications
- Excellent corrosion resistance
- Dry mate sealing down to 4 m immersion
- -65°C to +175°C operating temperature

**Compliant**

- STD CECC 75201-002
- RoHS compliant

**Typical Applications**

- Shipboard
- Ground vehicles



MC3 shown  
MC3 and MC4  
Optical Connectors

**MC3**

- 5, 8, or 12 fibers (shell size 19, 23, or 25)
- Aluminum shell
- 2.5 mm termini

**MC4**

- 2 fibers (shell size 9)
- Aluminum shell
- 2.5 mm termini



MC6 shown  
MC5 and MC6  
Optical Connectors

**MC5**

- 1, 2, 4, 6, 8, 10, 18, 30 fibers (shell sizes 11 through 25)
- Composite shell
- 1.25 mm termini

**MC6**

- 12 or 24 fibers
- Composite shell
- MT ferrules



MC801 Optical  
Connectors

**High Performance**

- Uses industry-standard ARINC 801 termini
- 1.25 mm ferrules for high contact density
- Multimode and single mode
- PC and APC finishes

**Lightweight**

- Aluminum shell

**Convenient**

- Compatible with LC termination processes and tooling



D38999 Series III  
QPL Fiber-Optic  
Connectors

**Capable**

- Up to 36 fibers
- MIL-PRF-29504/4 and /5 termini

**Rugged**

- Aluminum or composite shells
- Shock and vibration resistant
- Moisture and corrosion resistant



PRO BEAM Inserts

**Versatile**

- Expanded beam for size 11 and 15 shells
- 1, 2, 4, or 8 fibers

**Durable**

- No wear on fiber optic interface
- Vibration resistant
- Highly resistant to dirt and debris



PRO BEAM EB16  
Termini

**Convenient**

- Expanded beam termini for 38999 Series III size 16 cavities

**Durable**

- No wear on fiber optic interface
- Very vibration resistant
- Highly resistant to dirt and debris

**Repeatable Low-Loss Performance**

- Low sensitivity to thermal fluctuations and interface contamination
- Stable operation over life of system

**Easy To Use**

- Drop-in replacement for M29504/4 and /5 physical contact termini



High Power  
38999-Style  
Connectors

**High Current Capacity**

- Up to 1000 A in a size 25 shell
- Single and multicontact configurations

**Space Saving**

- Hybrid configurations with signal and power contacts
- Variety of shell sizes

**Rugged**

- Rear removable crimp contacts
- Dedicated sealed backfitting and cable support grommet
- Excellent contact retention under severe vibration



38999-DERIVED CONNECTORS



CBC Series Bussed Connectors

**Simple, Reliable Wire Bussing**

- Internal pc board connects contacts for grounding distribution, power distribution, and similar needs
- Range of standard and custom bussing configurations

**Weight and Space Saving**

- Composite and aluminum shells
- Eliminates external bussing components
- Shell sizes 9 through 25



Ruggedized Commercial Connectors

**Versatile**

- RJ45, with Cat 5e, 6, or 6A performance
- USB 2.1, up to 480 Mb/s
- USB 3.0, up to 5 Gb/s
- SIM card receptacle
- Micro SD card receptacle
- LC, for multimode and single-mode fiber

**Rugged**

- Shell options include aluminum, bronze, stainless steel, titanium, and composite
- Sealed up to IP68 for fluid and dust-laden environments



Hermetic Connectors

**High Performance**

- Glass-to-metal sealing
- Airtight under high pressures, vibration, and temperatures

**Rugged**

- Resists extreme changes in temperature or pressure
- -65°C to 200°C
- Wide range of special configurations

**Typical Applications**

- Pressurized systems
- Fuel tanks and other hazardous materials
- Harsh environments



Filter Connectors

**EMI Protection**

- Pi, LC, CL, C configurations
- Mixed capacitance, grounded or feedthrough lines
- Filter values from 100 pF to 1 µF, subject to specific requirements

**EMP Protection**

- Transient voltage suppression
- Resists EMP, NEMP, lightning strike, or ESD
- Fast transient clamping



Quadrax Connectors

**High Speed, High Density**

- Up to 8 Quadrax contacts in a size 25 shell
- One Quadrax contact in a size 9 shell
- Integral ground plane

**Rugged**

- High-strength aluminum alloy shell
- Nickel, zinc cobalt, or olive drab cadmium plating
- 360° shielding
- -65°C to +175°C

**Typical Applications**

- High-speed networking



CeeLok FAS-X Connectors

**High Speed**

- Supports 10G Ethernet and beyond
- One 10G Ethernet channel in size 11 shell
- Four channels in size 25 shell

**Compatible**

- AS39029 contacts
- Fast field termination and repair, using standard tools
- Available with aluminum or composite shells with a variety of finishes

**Typical Applications**

- High-speed networking



Feedthrough Connectors

**Convenient**

- Suited to bulkhead pass-through and connector-saver applications
- Wide range of gender matching, materials, and sizes



Backshells and Accessories

**Wide Backshell Range**

- AS85049-compliant band straps and adapters
- Available in all materials and finishes
- Straight, 45°, or 90°
- Options on low profile, extended length and alternative angles

**Shielded or Unshielded**

- Shielded for individual or overall 360° screening options

**Compatible**

- Compatible with Mil-Spec dimensions and performance

## For More Information

### TE Technical Support Center

North America	+1 800 522 6752
Asia Pacific	+86 0 400 820 6015
Austria	+43 1 905 601 228
Baltic Regions	+46 8 5072 5000
Benelux	+31 73 6246 999
Czech Republic	+420 800 701 462
France	+33 1 34 20 86 86
Germany	+49 6251 133 1999
Hungary	+36 809 874 04
Italy	+39 011 401 2632
Nordic	+46 8 5072 5000
Poland	+48 800 702 309
Russia	+7495 790 790 2
Spain/Portugal	+34 93 2910366
Switzerland	+41 52 633 66 26
United Kingdom	+44 800 267 666

Follow us on Twitter for all the latest product news  
@TEConnectivity, and on Facebook, TEConnectivity.

[te.com/38999](http://te.com/38999)

© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved.

1-1773858-4 ADM/RRD 2.5M 06/2015

CeeLok FAS-X, DEUTSCH, PRO BEAM, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.