




UNCONTROLLED DOCUMENT

P/N PREFIX/SUFFIX TABLE			
LCM-X		GXX	DESCRIPTION
STANDARD	S	SR	STN, REFLECTIVE
HIGH TEMP.	H	SF	STN, TRANSFLECTIVE(W/ BACKLIGHT)

TYPE	DIM.	A	B
WITH BACKLIGHT		13.8	9.4
NO BACKLIGHT		9.7	4.8

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10738. & #10BRDR.	5.21.01



**CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART**


UNCONTROLLED DOCUMENT

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10738, & #10BRDR.	5.21.01

A PIN CONFIGURATION

PIN NO.	SYMBOL	LEVEL	FUNCTION
1	V _{ss}	0V	GND
2	V _{DD}	5V	SUPPLY VOLTAGE FOR LOGIC
3	V _o	-	CONTRAST VOLTAGE FOR LCD DRIVE(VARIABLE)
4	R _D	L	READ SIGNAL
5	W _R	L	WRITE SIGNAL
6	CS	L	CHIP SELECT
7	A _O	H/L	DATA TYPE SELECT
8~15	D _{B0~D_{B7}}	H/L	DATA BUS
16	R _{ES}	L	RESET SIGNAL (NOTE 1)
17	V _{EE}	-	POWER SUPPLY VOLTAGE FOR LCD
18	A	4.2V	ANODE LED BACKLIGHT
19	K	-	CATHODE LED BACKLIGHT
20	(N/C)	-	NO CONNECTION

V_{DD}-V_o: LCD DRIVING VOLTAGE
VR: 10K Ω -20K Ω



NOTES:

1. R_{ES} IS A SCHMITT TRIGGER INPUT. THE PULSEWIDTH ON R_{ES} MUST BE AT LEAST 200 μ s. PULSES OF MORE THAN A FEW SECONDS WILL CAUSE DC VOLTAGES TO BE APPLIED TO THE LCD PANEL.

ELECTRICAL CHARACTERISTICS

V_{DD}=4.75V to 5.25V, T_A=25°C

ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT
			MIN.	TYP.	MAX.	
SUPPLY VOLTAGE FOR LOGIC	V _{DD} -V _{ss}	-	4.75	5.0	5.25	V
SUPPLY VOLTAGE FOR LCD DRIVE	V _{DD} -V _{EE}	-	-	18.2	-	V
SUPPLY CURRENT FOR LOGIC	I _{DD}	-	-	20	-	mA
INPUT VOLTAGE	V _{IH}	-	0.2	-	V _{DD}	V
	V _{IL}	-	0	-	0.8	V
OUTPUT VOLTAGE	V _{OH}	I _{OH} =-3.0mA	2.4	-	-	V
	V _{OL}	I _{OL} =3.0mA	-	-	0.4	V
*LED BACKLIGHT	V _f	I _f =560mA	-	4.2	4.5	V
	I _f	-	-	560	-	mA
	P _D	-	-	2.8	-	W
	L	I _f =560mA	60	-	-	cd/m ²
	COLOR	-	-	570	-	nm

*ONLY APPLIES TO MODULES WITH BACKLIGHT

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	TEST CONDITION	STANDARD VALUE		UNIT
			MIN	MAX	
SUPPLY VOLTAGE FOR LOGIC	V _{DD} -V _{ss}	T _A =25°C	0	7.0	V
SUPPLY VOLTAGE FOR LCD DRIVE	V _{DD} -V _{EE}	-	17.2@40°C	19.2@0°C	V
INPUT VOLTAGE	V _I	T _A =25°C	V _{ss}	V _{DD}	V
OPERATING TEMPERATURE	T _{opr}		LCM-S	50	°C
			LCM-H	-20	°C
STORAGE TEMPERATURE	T _{stg}		LCM-S	70	°C
			LCM-H	-30	85 °C

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), X.XX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX=-DECIMAL PRECISION

REV.	PART NUMBER
A	LCM-X160160GXX

160 x 160 DOT MATRIX GRAPHIC MODULE,
1/160 DUTY, STN WITH NEGATIVE CHARGE PUMP.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE: 12.1.98
SA/CT			PAGE: 2 OF 2 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Lumex](#):

[LCM-S160160GSR](#)