


Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	4 AWG, 3 AWG & 2 SOL
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	1-1/8 in.
Stud Size	#10
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	GRAY
Panduit Die Index No. on Barrel	P29
Alternate Industry Die Index No. ( ) on Barrel	(8)





Technical drawing of a mechanical part, likely a bracket or support, showing dimensions and callouts:

- Dimensions:**
  - Overall width:  $.55 \pm .04$
  - Overall height:  $.23 \pm .04$
  - Inner hole diameter:  $.20 \pm .02$  DIA
  - Radius:  $.31$  R Ref
- Callouts:**
  - PANDUIT** (Manufacturer/Brand)
  - 2 SOL CU** (2 Solid Copper)
  - 4-3 STR CU** (4-3 Strand Copper)
  - LCB4-10H** (LCB4-10H)



- Color coded barrel markings



						 <b>PANDUIT CORP. TINLEY PARK, ILLINOIS</b>	
						LCB4-10H-L	
01	2/03	SAC	PWS	EXTENDED WIRE RANGE AND UPDATED STAMPS AND MARKINGS	10543	Copper Lug - One-Hole, Long Barrel, 45° Angle Tongue	
<b>REV</b>	<b>DATE</b>	<b>BY</b>	<b>CHK</b>	<b>DESCRIPTION</b>	<b>ECN</b>	<b>SCALE</b> N/A	<b>DRAWING NO / CAD FILE</b> LCB4-10H-CUST

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

LCB4-10H-L