



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	2 AWG
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	1-1/4 in.
Stud Size	5/16 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BROWN
Panduit Die Index No. on Barrel	P33
Alternate Industry Die Index No. () on Barrel	(10)



								PANDUIT CORP. TINLEY PARK, ILLINOIS			
								LCB2-56W-Q Copper Lug - One-Hole, Long Barrel			
00	6/11	JHNU	JHNU	DRAWING RELEASED	10J012BY-LCB2-56W-CUST	RGB	RGB	SCALE N/A		DRAWING NO / CAD FILE	
REV	DATE	BY	CHK	DESCRIPTION	ECN	-R	SUP			LCB2-56W-CUST	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[LCB2-56W-Q](#)