





Double Metallized Polypropylene Film Capacitor Radial AC and Pulse Capacitor



FEATURES

- Material categorization:
for definitions of compliance please see
www.vishay.com/doc?99912

APPLICATIONS

High voltage, high current and high pulse operations, deflection circuits in TV sets (S-correction and fly-back tuning). Protection circuits in SMPS's. Snubber and electronic ballast circuits. Input and output filtering in SPS designs, storage, timing and integrating circuits.



QUICK REFERENCE DATA

Capacitance range	1000 pF to 0.68 μF		
Capacitance tolerances	± 20 % (M), ± 10 % (K), ± 5 % (J)		
Climatic testing class according to IEC 60068	55/100/56		
Dielectric	Polypropylene film		
Electrodes	Vacuum deposited aluminum		
Construction	Extended double-sided metallized polyester film, internal series connection, single-sided metallized polypropylene film (refer to general information)		
Coating	Flame retardant plastic case (UL-class 94 V-0), blue, epoxy resin sealed		
Leads	Tinned wire		
Marking	Manufacturer's logo / type / C-value / rated voltage / tolerance / date of manufacture		
Operating temperature range	-55 °C to +100 °C		
Rated DC voltages (U _R)	630 V _{DC} , 1000 V _{DC} , 1600 V _{DC} , 2000 V _{DC}		
Permissible AC voltages (RMS) up to 60 Hz	400 V _{AC} , 600 V _{AC} , 650 V _{AC} , 700 V _{AC}		
Test voltage (electrode/electrode)	1.6 x U _R for 2 s		
Insulation resistance	Measured at 100 V _{DC} after one minute For C ≤ 0.33 μF: 100 000 MΩ minimum value		
Time constant	Measured at 100 V _{DC} after one minute For C > 0.33 μF: 30 000 s minimum value		
Temperature coefficient	-250 x 10 ⁻⁶ /°C (typical value)		
Capacitance drift	Up to + 40 °C, ± 0.5 % for a period of two years		
Derating for DC and AC category voltage U _C	At +85 °C: U _C = 1.0 U _R At +100 °C: U _C = 0.7 U _R		
Self inductance	~ 6 nH measured with 2 mm long leads		
Pull test on leads	≥ 30 N in direction of leads according to IEC 60068-2-21		
Reliability	Operational life > 300 000 h Failure rate < 5 FIT (40 °C and 0.5 x U _R)		
Dissipation factor tan δ	MEASURED AT	C ≤ 0.1 μF	0.1 μF < C ≤ 1.0 μF
	1 kHz	0.3 x 10 ⁻³	0.3 x 10 ⁻³
	10 kHz	0.4 x 10 ⁻³	0.4 x 10 ⁻³
	100 kHz	1.5 x 10 ⁻³	-
	Maximum values		

Note


- For further details, please refer to the general information available at www.vishay.com/doc?26033

MAXIMUM PULSE RISE TIME

PCM (mm)	MAXIMUM PULSE RISE TIME dv/dt (V/ μ s)			
	630 V _{DC}	1000 V _{DC}	1600 V _{DC}	2000 V _{DC}
15	3430	6600	11 100	-
22.5	2120	2800	3800	6200
27.5	1524	2000	2680	4200
37.5	980	1280	1690	2600

Note

- If the maximum pulse voltage is less than the rated voltage higher dv/dt values can be permitted

**DIMENSIONS** in millimeters

W	Ø d
< 16.0	0.8
≥ 16.0	1.0

ELECTRICAL DATA

U_{RDC} (V)	CAP. (μF)	CAPACITANCE CODE	VOLTAGE CODE	V_{AC}	DIMENSIONS w x h x l (mm)	PCM (mm)
630	0.0068	-268	63	400	5.5 x 10.5 x 18.0	15
	0.010	-310			5.5 x 10.5 x 18.0	15
	0.015	-315			6.5 x 12.5 x 18.0	15
	0.022	-322			7.5 x 13.5 x 18.0	15
	0.033	-333			8.5 x 14.5 x 18.0	15
	0.047	-347			7.5 x 15.5 x 26.5	22.5
	0.068	-368			8.5 x 16.5 x 26.5	22.5
	0.10	-410			10.5 x 18.5 x 26.5	22.5
	0.15	-415			11.5 x 20.5 x 31.5	27.5
	0.22	-422			13.5 x 23.5 x 31.5	27.5
	0.33	-433			15.0 x 24.5 x 31.5	27.5
	0.47	-447			14.5 x 24.5 x 41.5	37.5
	0.68	-468			18.0 x 32.5 x 41.5	37.5
1000	0.0033	-233	10	600	5.5 x 10.5 x 18.0	15
	0.0047	-247			5.5 x 10.5 x 18.0	15
	0.0068	-268			6.5 x 12.5 x 18.0	15
	0.010	-310			6.5 x 14.5 x 26.5	22.5
	0.015	-315			6.5 x 14.5 x 26.5	22.5
	0.022	-322			6.5 x 14.5 x 26.5	22.5
	0.033	-333			7.5 x 15.5 x 26.5	22.5
	0.047	-347			10.5 x 18.5 x 26.5	22.5
	0.068	-368			11.0 x 21.0 x 26.5	22.5
	0.10	-410			11.5 x 20.5 x 31.5	27.5
	0.15	-415			13.5 x 23.5 x 31.5	27.5
	0.22	-422			16.5 x 29.5 x 31.5	27.5

**ELECTRICAL DATA**

U_{RDC} (V)	CAP. (μ F)	CAPACITANCE CODE	VOLTAGE CODE	V_{AC}	DIMENSIONS w x h x l (mm)	PCM (mm)
1600	0.0010	-210	13	650	5.5 x 10.5 x 18.0	15
	0.0015	-215			5.5 x 10.5 x 18.0	15
	0.0022	-222			5.5 x 10.5 x 18.0	15
	0.0033	-233			6.5 x 12.5 x 18.0	15
	0.0047	-247			7.5 x 13.5 x 18.0	15
	0.0068	-268			8.5 x 14.5 x 18.0	15
	0.010	-310			6.5 x 14.5 x 26.5	22.5
	0.015	-315			7.5 x 15.5 x 26.5	22.5
	0.022	-322			8.5 x 16.5 x 26.5	22.5
	0.033	-333			10.5 x 18.5 x 26.5	22.5
	0.047	-347			11.5 x 20.5 x 31.5	27.5
	0.068	-368			11.5 x 20.5 x 31.5	27.5
	0.10	-410			15.0 x 24.5 x 31.5	27.5
	0.15	-415			14.5 x 24.5 x 41.5	37.5
	0.22	-422			16.0 x 28.5 x 41.5	37.5
2000	0.0010	-210	20	700	6.5 x 14.5 x 26.5	22.5
	0.0015	-215			6.5 x 14.5 x 26.5	22.5
	0.0022	-222			6.5 x 14.5 x 26.5	22.5
	0.0033	-233			6.5 x 14.5 x 26.5	22.5
	0.0047	-247			6.5 x 14.5 x 26.5	22.5
	0.0068	-268			7.5 x 15.5 x 26.5	22.5
	0.010	-310			8.5 x 16.5 x 26.5	22.5
	0.015	-315			10.5 x 18.5 x 26.5	22.5
	0.022	-322			11.5 x 20.5 x 31.5	27.5
	0.033	-333			13.5 x 23.5 x 31.5	27.5
	0.047	-347			15.0 x 24.5 x 31.5	27.5
	0.068	-368			16.5 x 29.5 x 31.5	27.5
	0.10	-410			16.0 x 28.5 x 41.5	37.5

Note

(1) Further C-values upon request.


RECOMMENDED PACKAGING

LETTER CODE	TYPE OF PACKAGING	HEIGHT (H) (mm)	REEL DIAMETER (mm)	ORDERING CODE EXAMPLES	PCM 15	PCM 22.5 TO 27.5	PCM 37.5
D	Ammo	16.5	S ⁽¹⁾	MKP1846-310/635-D	X	-	-
G	Ammo	18.5	S ⁽¹⁾	MKP1846-310/635-G	X	-	-
F	Reel	16.5	350	MKP1846-310/635-F	X	-	-
W	Reel	18.5	350	MKP1846-310/635-W	X	-	-
V	Reel	18.5	500	MKP1846-410/105-V	X	X	-
G	Ammo	18.5	L ⁽¹⁾	MKP1846-410/105-G	-	X	-
-	Bulk	-	-	MKP1846-422-135	X	X	X


Note

(1) S = box size 55 mm x 210 mm x 340 mm (W x H x L)


L = box size 60 mm x 360 mm x 510 mm (W x H x L)




Permissible AC Voltage vs. Frequency



Permissible AC Voltage vs. Frequency



Permissible AC Voltage vs. Frequency



Permissible AC Voltage vs. Frequency



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[MKP1846222135](#) [MKP1846410634](#) [MKP1846410635](#)