






REV.	DESCRIPTION	DATE
A	NEW DRAWING	11/16/2005
B	added TR package option	11/7/2012



PCB LAYOUT
TOP VIEW



Note:
Add suffix "-TR" to the model number for
tape & reel packaging

TOLERANCE:
X.X ±0.2mm
X.XX ±0.1mm
X.XXX ±0.05mm



MODEL NO.	MJ-2523-SMT
SCHEMATIC	

SPECIFICATIONS:
 RATING: 12V DC @ 1A
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 50M OHMS MIN: 500V DC
 VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE
 LIFE: 5,000 CYCLES
 OPERATING TEMP: -25° ~ +85°C

	MATERIAL	PLATING	TITLE: 2.5mm SURFACE MOUNT AUDIO JACK-MONO	REV: B
TERMINAL 1	Copper Alloy	Silver	PART NO. MJ-2523-SMT	UNITS: MM [INCHES]
TERMINAL 2	Copper Alloy	Silver		
TERMINAL 3	Brass	Silver	DRAWN BY: ZRJ	APPROVED BY:
HOUSING	PA6T			
			SCALE: 4:1	

PC FILE NAME:
MJ-2523-SMT

COPYRIGHT 2012 BY CUI INC.



CUI INC

20050 SW 112th Ave.
Tualatin, OR 97062
Phone: 503-612-2300
800-275-4899
Fax: 503-372-1266
Website: www.cui.com