

KSA & KSL Series Sealed Tact Switch



Features/Benefits

- Designed for automatic or manual insertion
- Cambered terminals to ensure self retention
- Top or side actuated
- Large choice of caps
- RoHS compliant and compatible

Typical Applications

- Automotive
- Industrial
- Telecommunication networks

Specification

CONTACT ARRANGEMENT: SPST, N.O.
DOUBLE OVERMOLDING ON TERMINAL
SEALING: IP60
TERMINALS: PC pins, ground pin optional

Mechanical

Type	Actuation force N	Operating life (operations)	Travel to make
KSA0M211	1,4 ± 0,4	100,000	0,5 ± 0,2
KSA0M311	1,4 ± 0,4	1,000,000	0,5 ± 0,2
KSA0M411	3 ± 0,75	100,000	0,6 ± 0,2
KSA0M511	5 ± 1,5	100,000	0,7 ± 0,2
KSA0M911	3 ± 0,75	500,000	0,6 ± 0,2
KSL0M211	1,4 ± 0,4	100,000	0,5 ± 0,2
KSL0M311	1,4 ± 0,4	1,000,000	0,5 ± 0,2
KSL0M411	3 ± 0,75	100,000	0,6 ± 0,2
KSL0M511	5,4 ± 1,6	100,000	0,7 ± 0,2
KSL0M911	3 ± 0,75	500,000	0,6 ± 0,2

NOTE: Other versions in terms of force, termination length and corrosion protection available. Please contact your sales representative.
This data sheet does not provide enough information for applications which require a certain level of quality or safety such as automotive, medical systems, safety equipment. Please contact your sales representative to get contractual specification package.

Electrical

	Silver	Gold
MAXIMUM POWER:	1 VA	0.2 VA
MAXIMUM VOLTAGE:	32 VDC	32 VDC
MINIMUM VOLTAGE:	20 mV	20 mV
MAXIMUM CURRENT:	50 mA	10 mA
MINIMUM CURRENT:	1 mA	1 mA
DIELECTRIC STRENGTH:	250 Vrms	
CONTACT RESISTANCE:	≤ 100m Ω	
INSULATION RESISTANCE (100 V):	≥ 10 ⁹ Ω	
BOUNCE TIME:	≤ 1 ms	

Environmental

	Silver	Gold
OPERATING TEMPERATURE:	-40°C to 85°C	-40°C to 125°C
STORAGE TEMPERATURE:	-40°C to 85°C	-55°C to 125°C

Process

Wave soldering compatible with lead free soldering profile.

Packaging


Can be delivered in tubes of 65 pieces for automatic insertion or in boxes of 500 pieces for manual insertion (250 pieces for KSL, KSLV, KSAV).

How To Order


Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.

However, please note that all the combinations of these options are not feasible.

For any part number different from those listed above, please consult your local representative.



BUTTONS Buttons must be ordered separately and will be supplied in bulk.




*NOTE: Please note that all buttons are not RoHS compliant. Please check the compliance with your C&K sales representative.







KSA & KSL Series Sealed Tact Switch

ACTUATOR TYPE

KSA & KSL




Type	H mm	inch
KSA	4,75±0,3	(.185)
KSL	9,9±0,3	(.390)




GROUND TERMINAL

0 WITHOUT



1* WITH






*Not compatible with "V" insertion



First Angle
Projection


Dimensions are shown: mm (inches)
Specifications and dimensions subject to change

Tactile Switches

[illegible]

Type	L mm	inch
KSA0V	6,12 +0.2 /-0.4	.228
KSL0V	11,27+ 0.2 / -0.4	.437

OPTION CODE	OPERATING FORCE
2	1.3 N (130 grams) 100,000 operations
3	1.3 N (130 grams) 1,000,000 operations
4	3.0 N (300 grams) 100,000 operations
5	5.0 N (500 grams) 100,000 operations
9	3.0 N (300 grams) 500,000 operations



KSA & KSL Series Sealed Tact Switch

CONTACT MATERIAL



OPTION CODE	CONTACT MATERIAL
1	Silver contacts
3	Gold contacts

SEALING





OPTION CODE	SEALING
1	Sealing level IP60

BUTTONS



Buttons must be ordered separately and will be supplied in bulk.

BUTTON TYPE	KSA	KSL	KSAV	KSLV
K01	X			
K02	X			
K03	X	X	X	X
K04	X	X	X	X
K05		X		X
K06	X			
K07		X		X
K08		X		X
K09		X		X

K01



K02




First Angle
Projection


Dimensions are shown: mm (inches)
Specifications and dimensions subject to change

KSA & KSL Series Sealed Tact Switch


K03




K04




K05




K06




K07



K08



K09



Dimensions are shown: mm (inches)
 Specifications and dimensions subject to change

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

C&K Components:

[KSL0M511](#) [KSL0M512](#) [KSL0V411](#) [KSL0V311](#) [KSL0V511](#) [KSA0V411](#) [KSA0M211](#) [KSL0M212](#) [KSL0M211](#)
[KSA0M411](#) [KSL0M312](#) [KSL0M412](#) [KSL0M411](#) [KSA0V211](#) [KSA0M311](#) [KSA0M511](#) [KSL1M311](#) [KSL0M211 LFT](#)
[KSA0M211 LFT](#) [KSA0M411 LFT](#) [KSA0V211 ACTION.H2.9 LFT](#) [KSA0A311LFT](#) [KSA0A331LFT](#) [KSA0A411LFT](#)
[KSA0A431LFT](#) [KSA0A511LFT](#) [KSA0A531LFT](#) [KSA0A931LFT](#) [Ksa0a211Act2.9Lft](#) [KSA0M212LFT](#) [KSA0M311LFT](#)
[KSA0M312LFT](#) [KSA0M331LFT](#) [KSA0M332LFT](#) [KSA0M412LFT](#) [KSA0M431LFT](#) [KSA0M432LFT](#) [KSA0M511LFT](#)
[KSA0M512LFT](#) [KSA0M531LFT](#) [KSA0M532LFT](#) [KSA0M931LFT](#) [KSA0M911LFT](#) [Ksa0m211Act2.9Lft](#) [KSA0V211LFT](#)
[KSA0V311LFT](#) [KSA0V331LFT](#) [KSA0V411LFT](#) [KSA0V431LFT](#) [KSA0V511LFT](#) [KSA0V531LFT](#) [KSA0V911LFT](#)
[Ksa0v211Acti0n.H2.9Lft](#) [Ksa0v511Acti0n.H2.9Lft](#) [Ksa0v211SansEtrierLft](#) [Ksa0v511SansEtrierLft](#)
[Ksa0v211C0nnexi0ns3.3LFT](#) [Ksa0v411C0nnexi0ns3.3LFT](#) [Ksa0v511C0nnexi0n3.3LFT](#) [KSA1A211LFT](#)
[KSA1A331LFT](#) [KSA1A511LFT](#) [KSA1A531LFT](#) [KSA1M211LFT](#) [KSA1M311LFT](#) [KSA1M331LFT](#) [KSA1M411LFT](#)
[KSA1M431LFT](#) [KSA1M511LFT](#) [KSA1M531LFT](#) [KSL0A411LFT](#) [KSL0M212LFT](#) [KSL0M311LFT](#) [KSL0M312LFT](#)
[KSL0M331LFT](#) [KSL0M332LFT](#) [KSL0M411LFT](#) [KSL0M431LFT](#) [KSL0M432LFT](#) [KSL0M511LFT](#) [KSL0M512LFT](#)
[KSL0M531LFT](#) [KSL0M532LFT](#) [KSL0M931LFT](#) [KSL0V211LFT](#) [KSL0V311LFT](#) [KSL0V331LFT](#) [KSL0V431LFT](#)
[KSL0V511LFT](#) [KSL0V531LFT](#) [KSL1A211LFT](#) [KSL1M211LFT](#) [KSL1M331LFT](#) [KSL1M411LFT](#) [KSL1M431LFT](#)
[KSL1M511LFT](#) [KSAOM331LFT](#)