# GRM188F51C684ZA01#

"#" indicates a package specification code.













Deadline for last orders: 31 Mar 2018


Date of discontinuation: 30 Sep 2018

0.5mm min.

0603 (1608M)

< List of part numbers with package codes > GRM188F51C684ZA01D , GRM188F51C684ZA01J

### Shape



## Notes

Please use replacements or Recommended.

### References

Packaging	Specifications	Minimum quantity
D	ф180mm Paper taping	4000
J	ф330mm Paper taping	10000

Mass (typ.)	
1 piece	6.3mg
φ180mm Reel	144g

# Specifications

Size code in inch(mm)

Distance between external terminals g

Capacitance	0.68μF +80/-20%
Rated voltage	16Vdc
Temperature characteristics (complied standard)	Y5V(EIA)
Capacitance change rate	+22.0/-82.0%
Temperature range of temperature characteristics	-30 to 85°C
Operating temperature range	-30 to 85℃

1 of 1



<sup>1.</sup>This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

