

REV. Status
REVISION – 04/29/96 TS
REVISION A ADDED RoHS 12/05/05 MP
REVISION B ADDED TEMP RATING 5/6/15 MP

AUDIO COUPLING MINIATURE ENCAPSULATED TRANSFORMER DESIGNED TO OPERATE 40mW MAX IN SECONDARY AND REFLECT A PRIMARY SOURCE IMPEDANCE OF APPROXIMATELY 300Ω CT WITH 12Ω LOAD ON SECONDARY.

A. Electrical Specifications (@ 20 ° C)

- Pri Source Impedance; 300ΩCT
- Sec Load Impedance; 12Ω
- Pri DC Current; 7 mA MAX
- Operating Level; 40 mW MAX @ 300 Hz
- Frequency Response (relative to 1 KHz); ±2.0 dB, @ 300 Hz to 100 KHz
- Longitudinal Balance; 60 dB MIN @ 1 KHz
- DC Resistance;
 - (1-3) 42Ω ±20%
 - (4-5) 3.4Ω ±20%
- Turns Ratio; (1-3) : (4-5) = 5.07 : 1 ±2%
- Dielectric Strength; 60Hz 500Vrms 0.5 minute @ Pri – Sec





MODEL NUMBER

MET-44


B. Marking; MET-44, TAMURA, Primary and Secondary Impedance, pin numbers, date code and country of origin

- C. Operating Temperature: -20 to +85°C
Storage Temperature: -55 to +105°C

D. Schematic Diagram



E. Mechanical Specifications



TOLERANCES (mm)
≤ 4 ± 0.2
4 ≤ 20 ± 0.3
20 ≤ 50 ± 0.4

PREPARED BY:

C. POPPE

ENGINEER:	DRAWING CONTROL NO.	REV	MODEL DESCRIPTION	MODEL SPECIFICATION
MATHI P.	P-A1-11626	B	AUDIO COUPLING MINIATURE ENCAPSULATED XFMR	MET-44
SAFETY ENGINEER	CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE			DIM: mm[In] SCL: 2/1 SH: 1 OF 1
APPROVED:	PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.			
M. PITCHAI				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tamura:](#)

[MET-44](#)