

MEC1-130-02-L-D-EM2

MEC1-120-02-L-D-RA1-SL

MEC1-120-02-F-D-EM2

(1,00 mm) .0394"

MEC1-RA, MEC1-EM SERIES

RIGHT ANGLE/EDGE MOUNT SOCKETS

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?MEC1-RA

Insulator Material:

Black LCP

Contact Material:

Phosphor Bronze

Plating: Au or Sn over

50µ" (1,27 µm) Ni

Current Rating:

1.6 A per pin

(2 adjacent pins powered)

Operating Temp Range:

-55°C to +125°C

Insertion Depth:

(5,84 mm) .230" to

(8,13 mm) .320"

RoHS Compliant: Yes

Processing:

Lead-Free Solderable: Yes

SMT Lead Coplanarity:

(0,10 mm) .004" max (05-40)

(0,15 mm) .006" max (50-70)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



MEC1

1

POSITIONS
PER ROWCARD
SLOTPLATING
OPTION

D

RA1

NP

SL

Mates with:

(1,60 mm)

.062" card

05, 08, 20, 30,
40, 50, 60, 70

-02

= (1,60 mm)

.062" thick card

-F

= Gold flash on contact,

Matte Tin on tail

-L

= 10µ" (0,25 µm)

Gold on contact,

Matte Tin on tail

POSITIONS PER ROW	POLARIZED POSITIONS
05	3, 4
08	5, 6
20	15, 16
30	21, 22
40	31, 32
50	41, 42
60	31, 32, 63 & 64
70	53, 54, 115 & 116

-NP

= No Polarization

(8 positions only)

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

APPLICATION

Samtec recommends that pads on the mating board be Gold plated.

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?MEC1-EM

Insulator Material:

Black LCP

Contact Material:

Phosphor Bronze

Plating: Au or Sn over

50µ" (1,27 µm) Ni

Current Rating:

1.8 A per pin

(2 adjacent pins powered)

Operating Temp Range:

-55°C to +125°C

Insertion Depth:

(5,84 mm) .230" to

(8,13 mm) .320"

RoHS Compliant: Yes

Lead-Free Solderable:

Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



MEC1

1

POSITIONS
PER ROW

02

PLATING
OPTION

D

EM2

NP

Mates with:

(1,60 mm)

.062" card

05, 08, 20, 30,
40, 50, 60, 70

ALSO AVAILABLE (MOQ Required)

- Edge mount leads for (0,80 mm) .031" thick board
 - Other platings
- Contact Samtec.

-F

= Gold flash on contact,

Matte Tin on tail

-L

= 10µ" (0,25 µm) Gold on contact,

Matte Tin on tail

-NP

= No Polarization

(8 positions only)

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

Leave Blank for polarization

POSITIONS PER ROW	POLARIZED POSITIONS
05	3, 4
08	5, 6
20	15, 16
30	21, 22
40	31, 32
50	41, 42
60	31, 32, 63 & 64
70	53, 54, 115 & 116

Note: Some sizes, styles and options are non-standard, non-returnable.