

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

**Part Number:** [0014567027](#)  
**Status:** **Active**  
**Overview:** [SL™ Modular Connectors](#)  
**Description:** 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 0.38µm Gold (Au), 2 Circuits

**Documents:**

[3D Model](#)  
[Drawing \(PDF\)](#)  
[Product Specification PS-70400-001 \(PDF\)](#)  
[Packaging Specification PK-70873-0001 \(PDF\)](#)  
[RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

CSA LR19980  
UL E29179

**General**

Product Family Ribbon Cable / Wire Trap Connectors  
Series [70400](#)  
Comments Terminals Preloaded  
Component Type Housing  
Glow-Wire Compliant No  
Overview [SL™ Modular Connectors](#)  
Product Name SL  
UPC 800754218122

**Physical**


Circuits (Loaded) 2  
Color - Resin Black  
Durability (mating cycles max) 50  
Entry Angle Vertical  
Flammability 94V-0  
Lock to Mating Part Yes  
Material - Metal Phosphor Bronze  
Material - Plating Mating Gold  
Material - Plating Termination Tin  
Material - Resin Polyester Alloy  
Net Weight 0.364/g  
Number of Rows 1  
PCB Retention None  
Packaging Type Tube  
Pitch - Mating Interface 2.54mm  
Plating min - Mating 0.381µm  
Plating min - Termination 1.905µm  
Polarized to Mating Part Yes  
Stackable Yes  
Surface Mount Compatible (SMC) N/A  
Temperature Range - Operating -40°C to +105°C  
Termination Interface: Style IDT or Pierce  
Wire Insulation Diameter 1.35mm max.  
Wire Size AWG 22  
Wire/Cable Type Discrete Wire, Ribbon Cable

**Electrical**

Current - Maximum per Contact 3.0A  
Voltage - Maximum 250V

**Solder Process Data**

Lead-freeProcess Capability N/A



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**China RoHS**

**REACH SVHC**

Not Contained Per  
-ED/01/2017 (12  
January 2017)

**Halogen-Free**

**Status**

**Not Low-Halogen**

**Need more information on product  
environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any  
non-product compliance questions.

China ROHS Green Image  
ELV Not Relevant  
RoHS Phthalates Not Contained

**Search Parts in this Series**

[70400 Series](#)

**Mates With**

Single Row Housing [70018](#) , [70107](#) Version  
A, [70107](#) Version B, [70543](#) , [70545](#) , [70553](#) ,  
[70555](#)

**Use With**

[7307](#) Tinned 28AWG, [7767](#) Topcoat  
28AWG, [24241](#) Tinned 26AWG, [8996](#)  
Topcoat 26AWG, [24226](#) Tinned 24AWG,  
[8997](#) Topcoat 24AWG, [24369](#) High Flex  
26AWG, [24389](#) High Flex 24AWG

## Engineering Number

A704002976

### Packaging Specification

PK-70873-0001

## Product Specification

PS-70400-001

## Sales Drawing

SDA-70400-2976-2999

This document was generated on 12/12/2017

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

14-56-7027