

596-00854

HellermannTyton

Article Number: 596-00854



Description: Printable Solar Label, PHOTOVOLTAIC DC DISCONNECT, 3.75" X 1.00", Polyester, Red, 10/Pkg

Base Data		
	Local Order Number	596-00854
	Type	DCDISCT10
	Color	Red (RD)
	Features and Benefits	<ul style="list-style-type: none"> • Made with UV stable inks and materials for durability and weather resistance. • The labels are supplied with aggressive adhesive to ensure long life. • Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
	Quantity Per	pack
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Printable Solar Label, PHOTOVOLTAIC DC DISCONNECT, 3.75" X 1.0", Red
	Local Order Number 2	Cross Reference = 50 per roll: 596-00238; Printable Metal Solar Placard 5 pack: 596-00842; Engravable Metal Solar Placard 5 pack: 596-00858; Spanish version 50 per roll: 596-00814
	Short Description	Printable Solar Label, PHOTOVOLTAIC DC DISCONNECT, 3.75" X 1.00", Polyester, Red, 10/Pkg
Product Dimensions		
	Width W (Imperial)	3.75"
	Width W (Metric)	92.25mm
	Height H (Imperial)	1.0"
	Height H (Metric)	25.4mm
Material and Specifications		
	Material	Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate
	Material Shortcut	840/926
	Adhesive	Acrylic

596-00854

HellermannTyton

Material and Specifications	Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	10
	Package Quantity (Metric)	10
	Customs Number(Schedule B)	3919905060