



Shielded Power Inductors – LPS5015



- Very low DCR; excellent current handling
- 5.0 × 5.0 mm footprint; less than 1.5 mm tall

Designer's Kit C350 contains 3 each of all values

Core material Ferrite

Core and winding loss See www.coilcraft.com/coreloss

Environmental RoHS compliant, halogen free

Terminations RoHS compliant matte tin over nickel over silver.
Other terminations available at additional cost.

Weight 102 – 107 mg

Ambient temperature –40°C to +85°C with Irms current, +85°C to +125°C with derated current

Storage temperature Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 1000/7" reel; 3500/13" reel Plastic tape: 12 mm wide, 0.3 mm thick, 8 mm pocket spacing, 1.57 mm pocket depth

Recommended pick and place nozzle OD: 5 mm; ID: ≤ 2.5 mm

PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787_PCB_Washing.pdf](#).

Part number ¹	Inductance ² ±20% (μH)	DCR max ³ (Ohms)	SRF typ ⁴ (MHz)	Isat (A) ⁵			Irms (A) ⁶	
				10% drop	20% drop	30% drop	20°C rise	40°C rise
LPS5015-102MR_	1.0	0.050	183	3.6	3.8	3.9	1.90	2.65
LPS5015-132MR_	1.3	0.065	150	2.5	2.6	2.8	1.70	2.35
LPS5015-182MR_	1.8	0.075	128	2.6	2.8	2.9	1.50	2.15
LPS5015-222MR_	2.2	0.090	116	2.4	2.6	2.7	1.40	2.00
LPS5015-332MR_	3.3	0.125	88	1.9	2.0	2.0	1.30	1.80
LPS5015-472MR_	4.7	0.150	73	1.6	1.7	1.8	1.20	1.62
LPS5015-562MR_	5.6	0.175	67	1.6	1.6	1.6	1.10	1.45
LPS5015-682MR_	6.8	0.225	57	1.3	1.4	1.5	0.90	1.25
LPS5015-822MR_	8.2	0.280	49	1.3	1.3	1.4	0.85	1.05
LPS5015-103MR_	10	0.300	44	1.2	1.3	1.3	0.80	0.95
LPS5015-123MR_	12	0.350	40	1.0	1.1	1.2	0.75	0.84
LPS5015-153MR_	15	0.360	38	0.80	0.84	0.86	0.73	0.84
LPS5015-183MR_	18	0.550	35	0.75	0.77	0.80	0.70	0.83
LPS5015-223MR_	22	0.675	31	0.70	0.73	0.75	0.60	0.82
LPS5015-333MR_	33	0.750	24	0.55	0.59	0.60	0.50	0.70
LPS5015-473MR_	47	1.00	18	0.46	0.48	0.49	0.45	0.57
LPS5015-563MR_	56	1.13	17	0.40	0.43	0.45	0.40	0.52
LPS5015-683MR_	68	1.45	15	0.33	0.38	0.39	0.35	0.47
LPS5015-104MR_	100	1.95	12	0.30	0.33	0.34	0.30	0.42
LPS5015-124MR_	120	2.50	10	0.25	0.28	0.30	0.27	0.37
LPS5015-154MR_	150	3.40	9.3	0.23	0.25	0.26	0.25	0.33
LPS5015-224MR_	220	4.50	7.3	0.20	0.21	0.22	0.22	0.29
LPS5015-334MR_	330	7.40	5.7	0.15	0.17	0.18	0.17	0.22
LPS5015-474MR_	470	7.50	4.9	0.12	0.12	0.13	0.16	0.21
LPS5015-564MR_	560	8.50	4.3	0.10	0.11	0.12	0.14	0.190
LPS5015-684MR_	680	10.6	4.0	0.10	0.11	0.11	0.13	0.175
LPS5015-105MR_	1000	15.0	3.2	0.080	0.090	0.093	0.10	0.150
LPS5015-155MR_	1500	25.0	2.5	0.080	0.086	0.088	0.090	0.140
LPS5015-185MR_	1800	28.0	2.2	0.078	0.083	0.086	0.085	0.130
LPS5015-225MR_	2200	36.0	2.1	0.072	0.078	0.080	0.065	0.090

1. Please specify **termination** and **packaging** codes:

LPS5015-225MR_C

Termination: R= RoHS compliant matte tin over nickel over silver.
Special order, added cost:
Q = RoHS tin-silver-copper (95.5/4/0.5)
or P = non-RoHS tin-lead (63/37).

Packaging: C= 7" machine-ready reel. EIA-481 embossed plastic tape 1000 parts per full reel).

B= Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

D= 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (3500 parts per full reel).

- Inductance tested at 100 kHz, 0.1 Vrms using an Agilent/HP 4192A.
 - DCR measured on a micro-ohmmeter.
 - SRF measured using Agilent/HP 8753ES or equivalent.
 - DC current that causes the specified inductance drop from its value without current.
 - Current that causes the specified temperature rise from 25°C ambient.
 - Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 585-1 Revised 08/01/13

© Coilcraft Inc. 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Coilcraft:

[LPS5015-475MLB](#) [LPS5015-222MLB](#) [LPS5015-472MLB](#) [LPS5015-224MLB](#) [LPS5015-154MLC](#) [LPS5015-564MLC](#)
[LPS5015-155MLC](#) [LPS5015-334MLB](#) [LPS5015-155MLB](#) [LPS5015-132MLB](#) [LPS5015-822MLB](#) [LPS5015-564MLB](#)
[LPS5015-563MLC](#) [LPS5015-222MLC](#) [LPS5015-183MLC](#) [LPS5015-153MLB](#) [LPS5015-332MLB](#) [LPS5015-124MLB](#)
[LPS5015-472MLC](#) [LPS5015-684MLB](#) [LPS5015-105MLC](#) [LPS5015-333MLC](#) [LPS5015-474MLC](#) [LPS5015-474MLB](#)
[LPS5015-683MLC](#) [LPS5015-682MLC](#) [LPS5015-123MLB](#) [LPS5015-183MLB](#) [LPS5015-473MLC](#) [LPS5015-562MLC](#)
[LPS5015-153MLC](#) [LPS5015-104MLC](#) [LPS5015-182MLC](#) [LPS5015-185MLC](#) [LPS5015-225MLB](#) [LPS5015-562MLB](#)
[LPS5015-103MLC](#) [LPS5015-334MLC](#) [LPS5015-475MLC](#) [LPS5015-182MLB](#) [LPS5015-223MLB](#) [LPS5015-333MLB](#)
[LPS5015-154MLB](#) [LPS5015-683MLB](#) [LPS5015-105MLB](#) [LPS5015-822MLC](#) [LPS5015-224MLC](#) [LPS5015-332MLC](#)
[LPS5015-335MLC](#) [LPS5015-223MLC](#) [LPS5015-124MLC](#) [LPS5015-682MLB](#) [LPS5015-684MLC](#) [LPS5015-103MLB](#)
[LPS5015-473MLB](#) [LPS5015-185MLB](#) [LPS5015-335MLB](#) [LPS5015-123MLC](#) [LPS5015-563MLB](#) [LPS5015-104MLB](#)
[LPS5015-132MLC](#) [LPS5015-225MLC](#) [LPS5015-132MRB](#) [LPS5015-132MRC](#) [LPS5015-474MRC](#) [LPS5015-472MRC](#)
[LPS5015-224MRB](#) [LPS5015-103MRB](#) [LPS5015-562MRB](#) [LPS5015-332MRC](#) [LPS5015-683MRC](#) [LPS5015-104MRC](#)
[LPS5015-124MRB](#) [LPS5015-153MRC](#) [LPS5015-182MRC](#) [LPS5015-222MRC](#) [LPS5015-332MRB](#) [LPS5015-472MRB](#)
[LPS5015-474MRB](#) [LPS5015-563MRB](#) [LPS5015-563MRC](#) [LPS5015-562MRC](#) [LPS5015-682MRC](#)
[LPS5015-225MRB](#) [LPS5015-224MRC](#) [LPS5015-225MRC](#) [LPS5015-333MRB](#) [LPS5015-334MRB](#) [LPS5015-473MRB](#)
[LPS5015-473MRC](#) [LPS5015-183MRC](#) [LPS5015-185MRB](#) [LPS5015-185MRC](#) [LPS5015-222MRB](#) [LPS5015-223MRB](#)
[LPS5015-223MRC](#) [LPS5015-154MRB](#) [LPS5015-154MRC](#) [LPS5015-155MRB](#) [LPS5015-155MRC](#)